

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Astronics / EADS / Racal 1260-67A* at our website: ***Click HERE***

RACAL INSTRUMENTS 1260-67



High-Performance Microwave Switch Module

- **Five Switch Configurations in a C-size, Single-Slot, VXIbus Module**
- **48 SPST, 50MHz, 2A General Purpose Relays**
- **6 (1x2), 50MHz, 2A, 1-wire Multiplexers**
- **3 (1x4), 40MHz, 2A, 1-wire Multiplexers**
- **5 (2x8), 40MHz, 2A, 1-wire Matrices**
- **5 DPST, 10A Power Relays**

Racal Instruments™ 1260-67 is optimized for high- performance, high-density, microwave switching applications. This module uses high-quality sealed Narda relays for the ultimate in signal integrity.

The 1260-67 module was designed to switch signals used in modern communications systems including Cellular, PCS, and Satcom applications. It is also ideal for ATE systems designed for testing Military telecommunications, surveillance, and related equipment.

The 1260-67 provides highly reliable and repeatable operation over a conservatively specified lifetime of >1,000,000 operations. Narda's special microwave relay design includes a self-cleaning wiper that cleans the contacts every time it closes to maintain specifications over its lifetime.

Should relay replacement become required, relays can be removed and replaced in less than five minutes without removing the module from the VXI system. This maximizes system uptime and facilitates field upgrades.

User connections are made directly to the relay SMA connectors at the front panel of the VXI module, eliminating cumulative losses and induced noise.

The module is available in three standard configurations with 2, 4, or 6 six-throw relays, respectively. Custom configurations are available; contact the factory for details. For applications requiring terminations or frequencies up to 40GHz, the Racal Instruments 1260-64M.is recommended

An Option 01T is required to communicate with 1260 series modules, and provides message-based operation for ease of use and register-based operation for maximum speed. The Option 01T mounts on the leftmost 1260 series module and does not consume any VXI slots. The Option 01T provides a single point of software control for the switching system with advanced features such as include, exclude, scan, relay monitoring, user defined path names, and reset states.

The 1260 series line includes VXI *plug&play* support of Win95/NT frameworks including drivers for LabWindows/CVI and LabView. Please refer to the Option 01T data sheet for additional product features and specifications.

EADS NORTH AMERICA DEFENSE

1260-67 PRODUCT SPECIFICATIONS

MICROWAVE PERFORMANCE

Bandwidth (-3dB)
>18GHz

Impedance
50Ω

Maximum Power
100MHz: 490W
1GHz: 180W
10GHz: 60W
18GHz: 50W

Frequency Range (GHz)	DC-3	3-8	8-12.4	12.4-18
Insertion Loss (MAX dB)	0.15	0.25	0.35	0.45
Isolation (MIN dB)	85	75	65	65
VSWR (MAX)	1.15:1	1.25:1	1.35:1	1.45:1

Switching Sequence
Break Before Make

Operating Mode
Normally Open

VXIBUS INTERFACE DATA

Cooling
Airflow: 4.75 liter/sec
Backpressure: 0.5mm H_2O

Power Requirements
+5VDC at 1.4A w/Option 01T
+5VDC at 0.4A w/o Option 01T
+12VDC at 365mA per energized relay

ENVIRONMENTAL DATA

Temperature
Operating: 0℃ to 55℃
Storage: -40℃ to 75℃

Relative Humidity
85% ±5% non-condensing at <30℃

Altitude
Operating: 10,000 ft.
Non-Operating: 15,000 ft.

Shock
30g, 11ms, ½ sine wave

Vibration
0.013-inch: P-P, 5-55Hz

Bench Handling
4 inch drop at 45°

EMC

Emissions
EN55011A with limits in accordance with EN50081-1

Immunity
IEC801-2,3,4 with limits in accordance with EN50082-1

Safety
EN61010-1

RELIABILITY

Switching Time
<15ms (includes settling time)

Rated Switch Operations
Electrical: 1,000,000 operation at full rated load

MTBF
295,376 Telcordia (Bellcore)
324,239 (MIL-STD-211 FN2)

MTTR
<5 minutes

MECHANICAL

Weight
3.4 Lbs. w/ Option 01T
3 Lbs 2oz w/o Option 01T


Dimensions
C-size, Single-slot VXIbus module

Front Panel I/O Interface Connector
SMA male (not supplied)

***Note:* Front panel SMA connectors are in close proximity to each other; Racal P/N 991017 is recommended.**

TYPICAL CHANNEL

Power Input



Normally Open SP6T Switch

The CE Mark indicates that the product has completed and passed rigorous testing in the area of RF Emissions, Immunity to Electromagnetic Disturbances and complies with European electrical safety standards.

ORDERING INFORMATION

MODEL/DESCRIPTION	PART NUMBER
Racal Instruments 1260-67A, Six SP6T Microwave Switch, 18GHz	407716-001
Racal Instruments 1260-67B, Four SP6T Microwave Switch, 18GHz	407716-002
Racal Instruments 1260-67C, Two SP6T Microwave Switch, 18GHz	407716-003
5/16” Bit (to be used with MA-COM wrench, P/N 2098-5065-54)	991017
Option 01T, Message-Based and Register-Based Switch Controller (Installed)	OPT-405108-001

*One Option 01T must be ordered with switch system. Please specify the card on which Option 01T will be installed.

The EADS North America Defense Test and Services policy is one of continuous development, consequently the equipment may vary in detail from the description and specification in this publication.

EADS North America Defense Test and Services
1.800.722.2528/1.949.859.8999 sales@eads-nadefense.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP