

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

150 Watts
LPS150 Series

Total Power:	110-150 Watts
Input Voltage:	85-132 / 170-264 VAC 220-300 VDC
# of Outputs:	Single



Special Features

- Auto ranging input
- Remote sense
- Remote inhibit
- Power fail
- Single wire current sharing
- Built-in EMI filter
- Low output ripple
- Adjustable output
- 135 khz switching frequency
- Overvoltage protection
- Overload protection
- Optional cover (-C suffix).

Environmental

Operating temperature: 0° to 50°C ambient; derate each output at 2.5% per degree from 50° to 70°C

Electromagnetic susceptibility: Designed to meet IEC 801, -2, -3, -4, -5,-6, Level 3

Humidity: Operating; non-condensing 5% to 95%

Vibration: Three orthogonal axes, sweep at 1 oct/min, 5 min. dwell at four major resonances 0.75 G peak 5 Hz to 500 Hz, operational

Storage temperature: -40° to 85°C

Temperature coefficient: ±.04% per °C

MTBF demonstrated: >550,000 hours at full load and 25°C ambient conditions

Electrical Specs

Input

Input range	85-132 VAC or 170-264 VAC automatically selected. 220-300 VDC
Frequency	47-63 Hz
Inrush current	38 A max, cold start @ 25°C
Efficiency	75% typical at full load
EMI filter	FCC Class B conducted CISPR 22 Class B conducted EN55022 Class B conducted VDE 0878 PT3 Class B conducted
Safety ground leakage current	<0.5 mA @ 50/60 Hz, 264 VAC input

Output

Maximum power	110 W convection (75 W with cover) 150 W with 30 CFM forced air (130 W with cover)
Adjustment range	±5% minimum
Hold-up time	20 ms @ 110 W load, 115/230 VAC nominal line
Overload protection	Short circuit protection. Case overload protected @ 110% to 145% above peak rating
Overvoltage protection	5 V output: 5.7 to 6.7 VDC. Other outputs 10% to 25% above nominal output

Logic Control

Power Failure	TTL Logic signal goes high 50-150 msec after 5 V output. It goes low at least 3 ms before loss of regulation.
Remote inhibit	Requires an external TTL high signal to inhibit outputs.
Remote sense	Compensates for 0.5 V lead drop minimum, will operate without remote sense connected. Reverse connection protected.

Safety

VDE	0805/EN60950 (IEC950)	11774-3336-1260 (LC#88585)
UL	UL1950	EI32002
CSA	CSA 22.2-234 Level 3	LR53982
NEMKO	EN 60950/EMKO-TUE (74-sec) 203	P95102999
BABT	EN60950/BS7002	607019
CB	Certificate and report	2062
CE	Mark (LVD)	

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

AMERICAS
5810 Van Allen Way
Carlsbad, CA 92008
Telephone: 760-930-4600
Facsimile: 760-930-0698

EUROPE
Astec House, Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX, UK
Telephone: 44 (1384) 842-211
Facsimile: 44 (1384) 843-355

ASIA
Units 2111-2116, Level 21
Tower1, Metroplaza
223, Hing Fong Road
Fwai Fong, New Territories
Hong Kong
Telephone: 852-2437-9662
Facsimile: 852-2402-4426

Ordering Information

Model Number	Output Voltage	Minimum Load	Maximum Load with Convection Cooling	Maximum Load with 30 CFM Forced Air	Peak Load1	Regulation2	Ripple P/P (PARD)3
LPS152	5 V	0 A	22 A	30 A	35 A	±2%	50 mV
LPS153	12-(15) V	0 A	9.1 A	12.5 A	14.5 A	±2%	150 mV
LPS155	24-(28) V	0A	4.5 A	6.2 A	7.2 A	±2%	280 mV, max.

1. Peak current lasting <30 seconds with a maximum 10% duty cycle.
2. At 25°C including initial tolerance, line voltage, load currents and output voltages adjusted to factory settings.
3. Peak-to-peak with 20 MHz bandwidth and 10 µF in parallel with a 0.1 µF capacitor at rated line and load ranges.

Note: -C suffix added to the model number indicates cover option.

Pin Assignments

Connector		LPS152	LPS153	LPS155
SK1	PIN 1	INHIBIT -ve	INHIBIT -ve	INHIBIT -ve
	PIN 2	INHIBIT +ve	INHIBIT +ve	INHIBIT +ve
	PIN 3	VCC	VCC	VCC
	PIN 4	No Connection	No Connection	No Connection
	PIN 5	COMMON	COMMON	COMMON
	PIN 6	-SENSE	-SENSE	-SENSE
	PIN 7	+SENSE	+SENSE	+SENSE
	PIN 8	C SHARE	C SHARE	C SHARE
SK2				
	PIN 5	COMMON	COMMON	COMMON
	PIN 6	PIN REMOVED	PIN REMOVED	PIN REMOVED
	PIN 7	POK	POK	POK
SK3	TB-1	COMMON	COMMON	COMMON
	TB-2	+5 V	+12 to +15 V	+24 to +28 V
SK4	PIN 1	GROUND	GROUND	GROUND
	PIN 3	LINE	LINE	LINE
	PIN 5	NEUTRAL	NEUTRAL	NEUTRAL

Mating Connectors

(SK4) AC Input: Molex 09-50-8051 (USA)
Molex 09-91-0500 (UK)
PINS: 08-58-0111


(SK2) Power fail: Molex 09-50-8031 (USA)
Molex 09-91-0300 (UK)
PINS: 08-58-0111

(SK1) Remote sense/Remote inhibit:
Molex 51110-0851 (USA)
Pins: 50394-8100

Astec Connector Kit #70-841-009, includes al of the above.

Notes:

1. Specifications subject to change without notice.
2. All dimensions in inches (mm), tolerance is ±.02".
3. Specifications are for convection rating at factory settings unless otherwise stated.
4. Remote inhibit requires an external 5V @ 10mA to activate.
5. Mounting (6-32) maximum insertion depth is 0.12".
6. Warranty: 1 year
7. Weight: 1.75 lb. / 0.80 kg



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP