

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Promag 10D



More information and current pricing:
www.endress.com/10D

Benefits:

- Easy, fast centering of the sensor – innovative housing construction
- Energy-saving flow measurement – no pressure loss due to cross-section constriction
- Cost-effective – designed for easy applications and direct integration
- Safe operation – display provides easy readable process information
- Fully industry compliant – IEC/EN/NAMUR
- Maintenance-free – no moving parts

Specs at a glance

- **Max. measurement error** Volume flow: ±0.5 % o.r. ± 2 mm/s (±0.5 % o.r. ± 0.08 in/s)
- **Measuring range** 9 to 4700 dm3/min (2.5 to 1250 gal/min)
- **Medium temperature range** 0 to +60 °C (+32 to +140 °F)
- **Max. process pressure** PN 16, Class 150, 10K
- **Wetted materials** Liner: Polyamide Electrodes: 1.4435 (316L)

Field of application: Promag D, available as wafer version, is designed for all applications where space is at a minimum. It is the preferred choice for basic applications in the water industry. Combined with the highly cost-effective Promag 10 transmitter, Promag 10D is the ideal solution for measurement of liquids for various applications and available in a compact or remote version.

Features and specifications

Liquids

Measuring principle

Product headline

std_productprofile_product_usp_8063.
For basic water applications, optimized for limited space and plastic pipe installations.

Liquids

Sensor features

Easy, fast centering of the sensor – innovative housing construction. Energy-saving flow measurement – no pressure loss due to cross section constriction. Maintenance-free – no moving parts.
std_productprofile_product_differentiating_tech_features_8071.
std_productprofile_product_differentiating_tech_features_8072.
International drinking water approvals.

Transmitter features

std_productprofile_product_benefits_34707_1508943674.
std_productprofile_product_benefits_34705_1508943673.
std_productprofile_product_benefits_34706_1508943673.
2-line display with push buttons. Device as compact or remote version.
HART.

Nominal diameter range

DN 25 to 100 (1 to 4")

Wetted materials

Liner: Polyamide
Electrodes: 1.4435 (316L)

Measured variables

Volume flow

Max. measurement error

Volume flow: ±0.5 % o.r. ± 2 mm/s (±0.5 % o.r. ± 0.08 in/s)

Measuring range

9 to 4700 dm3/min (2.5 to 1250 gal/min)

Max. process pressure

PN 16, Class 150, 10K

Medium temperature range

0 to +60 °C (+32 to +140 °F)

Ambient temperature range

–20 to +60 °C (–4 to +140 °F)

Liquids

Sensor housing material
AlSi10Mg, coated
Sensor connection housing: AlSi10Mg, coated

Transmitter housing material
Powder-coated die-cast aluminum

Degree of protection
Compact version: IP66&67, type 4X enclosure
Sensor remote version: IP66/67, type 4X enclosure
Transmitter remote version: IP 67, type 4X enclosure

Display/Operation
2-line display with push buttons
Configuration via local display and operating tools possible

Outputs
4-20 mA HART (active)
Pulse/switch output (passive)

Inputs
None

Digital communication
HART

Power supply
DC 11 to 40 V
AC 85 to 250 V (45 to 65 Hz)
AC 20 to 28 V (45 to 65 Hz)

Hazardous area approvals
FM
CSA

Product safety
CE, C-tick, EAC marking

Liquids

Metrological approvals and certificates

Calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025)

Hygienic approvals and certificates

Drinking water approval: ACS, KTW/W270, NSF 61, WRAS BS 6920

More information **www.endress.com/10D**

Endress+Hauser AG
Switzerland

addresses.endress.com
info@endress.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP