



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com



MicronViewer 7290A

FIXED-MOUNT INFRARED IMAGING CAMERA



MicronViewer 7290AX

PORTABLE INFRARED IMAGING CAMERA

7290A shown with optional 25mm objective lens



The 7290AX includes a rechargeable shoulder pack battery, viewfinder with diopter focus and adjustable handstrap.



The MicronViewer 7290A and 7290AX models combine many unique features and benefits in one versatile and affordable camera: broad spectral response (400nm to over 2μm), excellent sensitivity and resolution, RS-170 60Hz or CCIR 50Hz video output, a variety of optional lenses and filters, and fixed-mount or handheld configurations, as well as extended-response versions!

- Accepts a variety of C-mount objective lenses
- Integral optical filter slide permits use of 25mm long-pass, short-pass, band-pass or neutral density filters
- 3-position manual gain or auto gain
- Standard video output: RS170 (60Hz) or CCIR (50Hz)
- Gen-lock input
- Tripod mount
- High-performance, lead-oxysulfide vidicon, 9.5 x 12.7mm imaging detector

APPLICATIONS

- Laser beam profiling and/or analysis: Nd:YAG (1.3μm), Er:Glass (1.5μm), Ho:YAG (2.1μm)
- Viewing and aligning IR sources
- Thermal imaging of objects hotter than 250°C
- Moisture detection
- Forensic analysis
- Semiconductor sub-surface inspection

MicronViewer 7290A
FIXED-MOUNT INFRARED IMAGING CAMERA

MicronViewer 7290AX
PORTABLE INFRARED IMAGING CAMERA

SPECIFICATIONS			
Spectral Sensitivity	0.4 to 1.9µm (7290A, 7290AX); 0.4 to 2.2µm (7290A, 7290AX)	Size (LxWxH)	9"x 4"x 3" (22x10x7 cm)
Horizontal Resolution	Up to 700 TV lines (7290A, 7290AX); Up to 650 TV lines (7290A-06, 7290AX-06)	Weight	1.13kg, 2.5lb. (7290A); 1.52kg, 3.2lb. (7290AX)
Dynamic Range	100:1 (7290A, 7290AX); 50:1 (7290A-06, 7290AX-06)	Mounts	1.0"-32 lens C-mount thread; ¼"-20 UNC-2B tripod mount on base Filter Slide accepts 25mm filters
Scanned Area	9.5x12.7mm ²	Ambient Temperature Range	-20°C to +50°C (-4°F to +122°F)
Damage Threshold	1mW/cm ² (CW), 10mJ (pulsed)	Operating Storage	20°C to +50°C (-4°F to +122°F); 54°C to +70°C (-65°F to +158°F)
Decay Lag after 50ms	45-60%	Gain Control	Three manual positions or automatic
Sweep Rate	RS-170 (7290A, 7290AX); CCIR (7290A-E, 7290AX-E)	Shading Correction	Internal control
Scanning	2:1 interlace	Sensitivity (target)	Internal control
Signal-to-Noise Ratio	55db (p-p/rms) or better	Video Output Connector	BNC
Deflection Distortion	±2% in circle of picture width	Sync Input Connector	BNC
Synchronization	Internal/Genlock (composite)	Power Connector	4-pin
Power	6W, 500mA		
Voltage Requirement	12-15VDC (7290A, 7290AX); Rechargeable battery and recharger (7290AX)		

Because of ongoing product enhancements, specifications are subject to change without notice.

ORDERING INFORMATION

ITEM	PART NO.	DESCRIPTION
7290A MicronViewer	914007	Fixed-mount camera with RS-170 60Hz video output. No lens. Requires AC power supply
7290AX MicronViewer	914059	Fixed-mount camera with RS-170 60Hz video output. Includes 1X 25mm Objective Lens, rechargeable shoulder pack and AC adapter/battery recharger
Option -06: Extended spectral range		Extends the sensitivity range of the standard camera to 2.2µm
Option -E: CCIR video format		Video format is CCIR 50Hz
1X Objective Lens	914566	25mm F1.3 with integral iris diaphragm
2X Objective Lens	903020	50mm F1.4 with integral iris diaphragm
0.5X-3X Zoom Objective Lens	908006	12.5-75mm F1.2 with integral iris diaphragm
Extension Tube Set	908007	Set of spacers that fit between lens and camera permitting close focusing
1" Long Pass Filters		Select cut-on wavelength (nm): 700, 750, 800, 850, 900, 950, 1000, more
1" Short Pass Filters		Select cut-off wavelength (nm): 700, 750, 800, 850, 900, 950, 1000, more
1" Band Pass Filters		Select center wavelength (nm): 700, 710, ..., 1050, 1060, more
1" Neutral Density Filters		Select optical density: 0.1, 0.2, ..., 0.9, 1.0, 1.5, 2.0, 3.0, more
G25 Filter Slide (extra)	914260	Holder for 1" filters
9" Bench-top Monitor	911000	120VAC, black and white
9" Bench-top Monitor	911002	240VAC, black and white
6' Video Cable	911001	
Camera Power Supply	905026	for 120VAC, includes 6' cord
Camera Power Supply	905027	for 240VAC, includes 6' cord

Contact us today to discuss how the MicronViewers 7290A and 7290AX can meet your application requirements.



373 Route 46, Fairfield, NJ 07004 973-882-0211 Fax: 973-882-0997 www.electrophysics.com





Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com