



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

Variable Light Source

FLS-210A



Variable power output

LED or laser options, single- or dual-wavelength

Equipped with EXFO's Universal Interface



Fiber-optic test, measurement
and monitoring instruments

EXFO

Manual and Automatic Test Capabilities

The FLS-210A is a high-performance light source that contains LED or laser sources with variable power output levels from 0 dB to 5 dB and from 0 dB to 10 dB, respectively. Combine the FLS-210A with the FOT-90A fiber-optic power meter to measure power and loss in singlemode and multimode fibers. The FLS-210A is the only source in its class capable of performing both manual and automatic tests when combined with a compatible power meter.



FasTesT-Compatible



FasTesT automatically performs a single- or dual-wavelength loss test at the touch of a button. Perform automated attenuation measurements by referencing the FOT-90A Power Meter and FLS-210A Variable Light Source, then simply press the FasTesT button on the FLS-210A. The compatible power meter at the other end will automatically acquire and store readings. The result is efficient data acquisition at a reduced risk of error.

Dual-Wavelength Selection

The FLS-210A is available in single- (1300 nm, 1550 nm) or dual-wavelength (850/1300 nm, 1310/1550 nm) configurations. Dual-wavelength models toggle between sources and use the same output connector for maximum efficiency and accuracy. For applications requiring stable sources, select the cooled laser option.

Variable Output Advantage

The FLS-210A features variable outputs over a 10 dB range for laser versions and a 5 dB range for LED versions. Either version can be adjusted by increments of 0.1 dB. The laser output is -2 dBm, -3 dBm or -7 dBm, depending on the chosen source.

Outstanding Features

The FLS-210A provides 2 kHz tone modulation, a large, backlit LCD, three-way powering (AC adapter/charger, NiCd, 9 V alkaline battery), low-battery indicator and auto-off function. The unit is housed in a durable polycarbonate case, designed to withstand any field conditions. The FLS-210A offers portable lab-quality performance.

Key Features

- FasTesT-compatible
- Three-way powering
- Automatic mode for streamlined documentation

Specifications

Single-wavelength source specifications¹

| Model | -02BL | -03BL |
|---|-----------|-----------|
| Wavelength (nm) | 1310 ± 15 | 1550 ± 20 |
| Spectral width (rms) ² (nm) | ≤ 5 | ≤ 5 |
| Emitter type | laser | laser |
| Typical output power (dBm) | | |
| 9/125 μm | -2 | -2 |
| 50/125 μm | -2 | -2 |
| Stability (dB) | | |
| 1 h | ± 0.05 | ± 0.05 |
| 8 h ⁴ | ± 0.12 | ± 0.12 |
| Temperature stability ⁵ (dB) | ± 0.3 | ± 0.3 |

Dual-wavelength source specifications¹

| Model | -12C | | -23B | | -23BL | | -23BLC | |
|---|-------------------|-------------------|-------------------|-------------------|------------------|------------------|------------------|------------------|
| Wavelength (nm) | 850 ± 30 | 1300 ± 30 | 1310 ± 30 | 1550 ± 30 | 1310 ± 15 | 1550 ± 20 | 1310 ± 15 | 1550 ± 20 |
| Spectral width (nm) | ≤ 50 ³ | ≤ 80 ³ | ≤ 80 ³ | ≤ 80 ³ | ≤ 5 ² | ≤ 5 ² | ≤ 5 ² | ≤ 5 ² |
| Emitter type | LED | LED | LED | LED | laser | laser | laser | laser |
| Typical output power (dBm) | | | | | | | | |
| 9/125 μm | — | -33 | -26 | -31 | -3.5 | -3.5 | -3.5 | -3.5 |
| 50/125 μm | -22 | -18 | -26 | -31 | -3.5 | -3.5 | -3.5 | -3.5 |
| Stability (dB) | | | | | | | | |
| 1 h | ± 0.04 | ± 0.04 | ± 0.05 | ± 0.05 | ± 0.05 | ± 0.05 | ± 0.04 | ± 0.04 |
| 8 h ⁴ | ± 0.1 | ± 0.1 | ± 0.15 | ± 0.15 | ± 0.12 | ± 0.12 | ± 0.06 | ± 0.06 |
| Temperature stability ⁵ (dB) | ± 0.3 | ± 0.3 | ± 0.3 | ± 0.3 | ± 0.3 | ± 0.3 | ± 0.2 | ± 0.2 |

General specifications

| | | |
|-------------|----------------------|--|
| Size | 22 cm x 11 cm x 5 cm | (8 ³ / ₄ in x 4 ¹ / ₂ in x 2 in) |
| Weight | | |
| unit | 0.75 kg | (1 ¹ / ₂ lb) |
| shipping | 2.5 kg | (5 ¹ / ₂ lb) |
| Temperature | | |
| operating | -10 °C to 40 °C | (14 °F to 104 °F) |
| storage | -30 °C to 60 °C | (-22 °F to 140 °F) |

Standard accessories

Instruction manual, AC adapter/charger, built-in NiCd batteries, 9 V alkaline battery, carrying case, protective holster, shoulder strap, and Certificate of Compliance.

Safety

This product complies with 21 CFR 1040.10 and 1040.11 and with IEC 60825-1:1993+A1:1997.

CLASS 1 LASER PRODUCT

CLASS 1 LED PRODUCT

Notes

- At 23 °C ± 2 °C (73 °F ± 4 °F) after a 10-minute warmup period.
- rms = root mean square
- Full width at half maximum (FWHM).
- At 23 °C ± 2 °C (73 °F ± 4 °F) after a 20-minute warmup period.
- For a temperature variation from -10 °C to 40 °C (14 °F to 104 °F).

Ordering Information

FLS-210A-XXXXX-XX

Source code

Single wavelength

02BL = 1310 nm laser

03BL = 1550 nm laser

Dual wavelength

12C = 850/1300 nm LED

23B = 1310/1550 nm LED

23BL = 1310/1550 nm laser

23BLC = (TEC) 1310/1550 nm laser

Connector code

50 = FC/PC

54 = SC/PC

58 = FC/APC narrow key

74 = ST/PC

88 = SC/APC

89 = FC/UPC

90 = ST/UPC

91 = SC/UPC

EI = UPC Universal Interface

EA = APC narrow key Universal Interface

The fixed baseplate (EI or EA) must be ordered with a removable universal connector adapter (EUI-XX). Please specify a EUI from the following list:

EUI-28 = DIN 47256

EUI-89 = FC

EUI-91 = SC

EUI-76 = HMS-10/AG (EI only)

EUI-90 = ST (EI only)

EUI-95 = E-2000

Example: FLS-210A-EI-89 for FC/UPC interface

FLS-210A-EA-89 for FC/APC interface

Find out more about EXFO's extensive line of high-performance portable instruments by visiting our Web site at www.exfo.com



Rugged Handheld Solutions

- OLTS
- Power Meter
- Light Source
- Talk Set



Modular Platforms

- OTDR
- OLTS
- and more



Advanced DWDM Test Systems

- OSA
- PMD
- Multiwavelength Meter

| | | | |
|-----------------------------------|--|--|--|
| CORPORATE HEADQUARTERS | 465 Godin Avenue | Vanier (Quebec) G1M 3G7 CANADA | Tel.: 1 418 683-0211 . Fax: 1 418 683-2170 |
| EXFO AMERICA | 1201 Richardson Drive, Suite 260 | Richardson TX 75080 USA | Tel.: 1 800 663-3936 . Fax: 1 972 907-2297 |
| EXFO EUROPE | Le Dynasteur, 10/12 rue Andras Beck | 92366 Meudon la Forêt Cedex FRANCE | Tel.: +33.1.40.83.85.85 . Fax: +33.1.40.83.04.42 |
| EXFO ASIA-PACIFIC | 151 Chin Swee Road, #03-29 Manhattan House | SINGAPORE 169876 | Tel.: +65 333 8241 . Fax: +65 333 8242 |
| TOLL-FREE (USA and Canada) | Tel.: 1 800 663-3936 | www.exfo.com • info@exfo.com | |

EXFO is certified ISO 9001 and attests to the quality of these products, which come with a 12-month warranty and after-sales support service. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices.

Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO Web site at <http://www.exfo.com/support/techdocs.asp>
In case of discrepancy, the Web version takes precedence over any printed literature.



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com