

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Connecting cables for valves, socket type C to EN 175301-803

FESTO



★	Festo Core Range Solves the majority of your automation tasks	With the Festo Core Range, we have selected the most important products and functions from our broad product catalogue, and added the quickest delivery.
Worldwide:	Quickest delivery – wherever, whenever	The Core Range offers you the best value for your automation tasks.
Simply good:	Expected high Festo quality	
Fast:	Easy and fast to select	

Just look for the star!

Type codes

001	Series	
KMEB	Connecting cable	

002	Variant	
1	Variant 1	
2	Variant 2	
3	Variant 3	

003	Rated operating voltage	
24	24 V DC	
230	230 V AC	
230AC	230 V AC	

004	Connection technology on the right, controller side	
	Open end	
M12	Plug M12x1 A-coded, EN 61076-2-101	

005	Cable length [m]	
0.5	0.5	
2.5	2.5	
5	5	
10	10	

006	Display	
	No display	
LED	LED signal status, DC	

Data sheet

Connecting cable KMEB

- For valves with EB solenoid coil
- Pre-assembled
- Cable lengths 2.5 m, 5 m and 10 m
- 24 V DC with LEDs and protective circuit
- Not suitable for energy chains
- KMEB-1 with PVC cable
- KMEB-2 with PUR cable
- KMEB-3 with PVC cable



General technical data

Type	KMEB-1	KMEB-2	KMEB-2-24-M12	KMEB-3
Electrical connection	Angled socket	Angled socket	Angled socket	Angled socket
	3-pin	4-pin	5-pin	2-pin
	Type C	Type C	Type C	Type C
	To EN 175301-803	To EN 175301-803	To EN 175301-803	To EN 175301-803
Reverse polarity protection	–	–	–	For all electrical connections
Cable ⌀ [mm]	5.2	6.2	4.6	5.2
Cable composition	3 x 0.5 mm²	3 x 0.75 mm²	3 x 0.5 mm²	2 x 0.75 mm²
Protective earth connection	Provided	Provided	Provided	Not provided
Type of mounting	On solenoid valve with M2.5 central screw	On solenoid valve with M2.5 central screw	On solenoid valve with M2.5 central screw	On solenoid valve with M2.5 central screw
Mounting position	Any	Any	Any	Any
Cable characteristic	–	–	–	Standard
Degree of protection	IP65	IP65	IP65	IP65
	To IEC 60529	To IEC 60529	To IEC 60529	To IEC 60529

Materials

Type	KMEB-1	KMEB-2	KMEB-2-24-M12	KMEB-3
Housing	PA66-GF30	PA, POM	PA, POM	PC
Pin contact	Bronze	Bronze	Bronze	Silver-plated bronze
Cable sheath	PVC	TPE-U(PUR)	TPE-U (PU)	PVC
Note on materials	–	RoHS-compliant	–	–
PWIS conformity	VDMA24364-B2-L	VDMA24364-B2-L	VDMA24364-B2-L	VDMA24364-B2-L

Operating and environmental conditions


Type	KMEB-1-24	KMEB-1-230AC	KMEB-2	KMEB-2-24-M12	KMEB-3
Ambient temperature [°C]	–20 … +80	–20 … +80	–20 … +80	–5 … +50	–20 … +80
Corrosion resistance class CRC[1)]	1	1	–	–	1
CE marking (see declaration of conformity)[2)]	To EU RoHS Directive	To EU Low Voltage Directive	To EU RoHS Directive	To EU RoHS Directive	To EU RoHS Directive
		To EU RoHS Directive			
UKCA marking (see declaration of conformity)[2)]	To UK RoHS instructions	To UK regulations for electrical equipment	To UK RoHS instructions	To UK RoHS instructions	To UK RoHS instructions
		To UK RoHS instructions			

1) Corrosion resistance class CRC 1 to Festo standard FN 940070
Low corrosion stress. Dry indoor application or transport and storage protection. Also applies to parts behind covers, in the non-visible interior area, and parts which are covered in the application (e.g. drive trunnions).
2) Additional information is available at www.festo.com/catalogue/... → Support/Downloads.

Data sheet

Dimensions Download CAD data ➔ www.festo.com


KMEB-1



[1] LED illuminated area (only with 24 V)
[2] Inscription label holder ASCF with label ASLR-L-432 (scope of delivery)
[3] 3-wire cable (3x 0.5 mm²)
[4] Plug pattern to EN 175301-803, type C
[5] Seal

Type	D1	D2	L1	L2	H1	H2	B1
KMEB-1-...-2.5	5.2	2.5	2500	29.1	19.3	4	16
KMEB-1-...-5	5.2	2.5	5000	29.1	19.3	4	16
KMEB-1-...-10	5.2	2.5	10000	29.1	19.3	4	16

KMEB-2



[1] LED illuminated area (integrated)
[2] Inscription label
[3] 3-wire cable 2.5 m or 5 m (3x 0.75 mm²)
[4] Plug pattern to EN 175301-803, type C
[5] Seal


Type	B1	D1	H1	H2	L1	L2	L3
KMEB-2-...-2.5	16	6.2	26	22	2550	34.6	16
KMEB-2-...-5	16	6.2	26	22	5050	34.6	16

Data sheet

Dimensions


Download CAD data ➔ www.festo.com

KMEB-2-24-M12



[1] 3-wire cable 0.5 m (3x 0.5 mm²)


KMEB-3



[1] LED illuminated area
[2] Inscription area
[3] 2-wire cable
[4] Plug pattern to EN 175301-803, type C
[5] Seal


Circuitry

KMEB-1 and KMEB-3 with signal status indication




The 24 V DC version is reverse polarity protected and has a protective circuit for peak voltages of up to 100 V DC as well as an operating status indicator with yellow LED.
(No gn/ye connection with KMEB-3)

KMEB-2-24-M12




KMEB without signal status indication



For KMEB-3
- No gn/ye connection
- Operating voltage 24 V DC


KMEB-2 with signal status indication







Data sheet

★ Core product range



Ordering data

	Signal status indication	Material Cable sheath	Operating voltage [V]	Cable length [m]	Weight [g]	Part no.	Type
KMEB-1							
	LED	PVC	24 DC	2.5	125	★ **151688**	**KMEB-1-24-2.5-LED**

Ordering data

	Signal status indication	Material Cable sheath	Operating voltage [V]	Cable length [m]	Weight [g]	Part no.	Type
KMEB-1							
	LED	PVC	24 DC	5	230	**151689**	**KMEB-1-24-5-LED**
				10	460	**193457**	**KMEB-1-24-10-LED**
	–	PVC	230 AC	2.5	125	**151690**	**KMEB-1-230AC-2.5**
				5	230	**151691**	**KMEB-1-230AC-5**
KMEB-2							
	LED	TPE-U(PUR)	24 DC	2.5	200	**174844**	**KMEB-2-24-2.5-LED**
				5	400	**174845**	**KMEB-2-24-5-LED**
	–	TPE-U(PUR)	230 AC	2.5	200	**174846**	**KMEB-2-230-2.5**
				5	400	**174847**	**KMEB-2-230-5**
KMEB-2-24-M12							
	LED	TPE-U (PU)	24 DC	0.5	–	**177677**	**KMEB-2-24-M12-0.5-LED**
KMEB-3							
	Yellow LED	PVC	24 DC	2.5	120	**547268**	**KMEB-3-24-2.5-LED**
				5	230	**547269**	**KMEB-3-24-5-LED**
	–	PVC	24 DC	2.5	120	**547270**	**KMEB-3-24-2.5**
				5	230	**547271**	**KMEB-3-24-5**

Ordering data – Accessories

	Description	Use	Part no.	Type
	Inscription labels 6x10 mm, 64 pieces, in frame	KMEB-3	**18576**	**IBS-6x10**
	Inscription labels 9x20 mm, 20 pieces, in frame	KMEB-2	**18182**	**IBS-9x20**
	Inscription label holders for identifying connecting cables	For cable diameter 4.2 ... 5.6 mm	**8143238**	**NEAU-LH-4**

Festo - Your Partner in Automation











1 Festo Inc.

5300 Explorer Drive
Mississauga, ON L4W 5G4
Canada

Festo Customer Interaction Center
Tel: 1 877 463 3786
Fax: 1 877 393 3786
Email: customer.service.ca@festo.com

2 Festo Pneumatic

Av. Ceylán 3,
Col. Tequesquináhuac
54020 Tlalnepantla,
Estado de México

Multinational Contact Center
01 800 337 8669

ventas.mexico@festo.com

3 Festo Corporation

1377 Motor Parkway
Suite 310
Islandia, NY 11749

4 Regional Service Center

7777 Columbia Road
Mason, OH 45040

Festo Customer Interaction Center
1 800 993 3786
1 800 963 3786
customer.service.us@festo.com

Connect with us

www.festo.com/socialmedia

www.festo.com

Subject to change

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP