

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

FUTUREDESIGN CONTROLS

FDC-L91



FDC-L91 1/16 DIN Limit Control

Safety, Simplicity.

Future Design's L91 is a 1/16DIN control designed to provide limit protection in process applications. Up to three discreet setpoints, two outputs, fast scan rates and user friendly prompts make it the right choice for safety protection. The L91 offers a full range of universal inputs. Power supply selections of 90-264 VAC (std) or 11-26 VAC/VDC allows the L91 to be used virtually anywhere. Output selections include Relay, SSR Drive or Triac. Optional features such as a second latching relay, DC power supply, remote reset or communications offer maximum flexibility for demandng applications. The L91 display can be be configured for PV, HSP, LSP or Safe, offering the simplicity required by operations personnel.

- Latching Outputs
- Annunciator Output
- Remote Reset
- RS-485 Interface
- Operations Friendly
- UL, FM, CE Approvals

FDC-L91 Specifications

Power

90-264 VAC, 49-63 Hz, 10VA, 5W maximum

11-26 VAC/VDC, 10VA, 5W maximum

Input

Thermocouple: (T/C): Type J,K,T,E,B,R,S,N,L

RTD: PT 100 ohm RTD (DIN or JIS)

Linear: 4-20, 0-20mA, 0-60Mv, 0-1, 0-5, 1-5, 0-10VDC

Range: Per table in manual

Accuracy: Typically better than ± .25% of span

Cold Junction Compensation: ± 1.5uV/˚C@25˚C

Sensor Break: 4 sec.for sensor input, 0.1 sec. for linear 4-20 mA or 1-5 VDC

Common Mode Rejection: 120dB

Sample Rate: 5 times per second

Limit Output types

Relay: Form C 2.0 Amp/240 VAC Resistive

SSR Drive: 5 Volt VDC@30 Ma

Triac: 1.0 Amp/240 VAC

Indication

Single LED Display: 0.4" Height, 4 Digits Red

Unit Display: ˚C and ˚F Indicator

Status Indicator: Out1, Out2, HSP1, LSP2, SP2, Lock

Options

Second Output: Relay Form A 2.0Amp@240 Res. (N.O.)
SSR Drive 5VDC@30mA
Triac 1.0 Amp@240 VAC

Second Output Types: Latching, Non-Latching, Annunciator

Communications: Modbus RTU

DC Power Supply: Isolated 20 VDC@25 MA
Isolated 12 VDC@40 Ma
Isolated 5 VDC@80 Ma

Remote Reset: External Contact Closure Reset

Environmental And Physical

Operating Temperature: -10 to 50˚C

Storage Temperature: -40 to 60˚C

Humidity: 0/90% RH (non-condensing)

Insulation: 20 M ohms Minimum (500 VDC)

Dielectric Strength: 2000 VAC, 50/60 Hz@1 Min.

Shock Resistance: 200m/s^2 (20G)

Vibration: 10-55Hz, 10m/s^2 for 2 hours

Molding: Flame retardant polycarbonate

Dimensions: 1.89" (H) x 1.89" (W) x 3.70" (D)

Weight: 5.3 oz. (150 grams)

P.O. Box 1196 • Bridgeview, IL 60455
888.751.5444 • 888.307.8014 Fax
www.futuredesigncontrols.com

Ordering Information

Enter a number in each box which corresponds to the specifications you want when ordering the L91.

FDC-L91 [ ] [ ] [ ] [ ]

Power Input

4: 90-264 VAC 49/63 Hz
5: 11-26 VAC/VDC
9: Special Order

Signal Input

1: Universal Input T/C, RTD, Mv
2: Voltage DC: 0-1, 0-5, 1-5
3: Voltage DC: 0-10
4: mA 0-20, 4-20
5: Special Order

Note: Instruments ordered with signal inputs 2, 3 & 4 are not FM approved.

Output 1

1: Form C Relay - 2.0 Amps@240 VAC Res.
2: SSR Drive - 5 VDC@30 ma
3: Triac - 1.0 Amp@240 VAC
4: Special Order

Options

0: None
1: Form A Relay - 2.0 Amps@240 VAC Res. (N.O.)
2: SSR Drive - 5 VDC@30 ma
6: Triac - 1.0 Amp@240 VAC
7: Isolated DC Power Supply - 20 VDC@25 mA
8: Isolated DC Power Supply - 12 VDC@40 mA
9: Isolated DC Power Supply - 5 VDC@80 mA
A: RS - 485 (Modbus RTU)
B: Remote Reset
C: Special Order

FM, CE Approved
UL Pending

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP