

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

9181 Series Inertial Reference Unit

Tactical inertial reference unit for 3-5 MIL performance applications including Assured PNT and mobile SATCOM antenna pointing





9181 Series Inertial Reference Units (IRU) provide navigational grade 3-5 MIL performance for platform navigation, system stabilization, and pointing applications. This IRU is based on a proprietary inertial gyroscope technology that reduces size, weight, power, and cost (SWaP-C) when compared to units with similar performance.

GE Aviation's IRUs are utilized on land, maritime, and airborne applications; with over 5,300 units fielded worldwide. This product family is scalable to customer's specific needs.

Standard IRU: compact unit that has 3-5 MIL performance, RS-422 interfaces, SAASM or commercial GPS

Enhanced IRU: slightly larger unit that has 3-5 MIL performance, expanded interfaces (like Ethernet), SAASM or commercial GPS, faster update rate, and spare processing

Features

- Ability to statically align in 3 to 5 minutes and navigate in GPS-denied environment providing assured Position, Navigation, and Timing (A/PNT)
- GPS-aided dynamic alignment within 1 to 3 minutes
- Standard or enhanced microprocessors
- Embedded military Selective Availability Anti-Spoofing Module (SAASM) GPS or embedded commercial GPS receivers
- Standard data ports include RS-422, RS-232, and 10/100 Ethernet
- Optional interfaces include ARINC 429, MIL-STD-1553, and others upon request
- High-accuracy continuous pitch, roll, true heading (non-magnetic), location, targeting information in any environment
- Future enhancements include M-Code and Global Navigation Satellite System (GNSS) solutions

Technical specifications

	Standard IRU	Enhanced IRU
Performance		
Static alignment heading accuracy (+/- 65° latitude)*	3 - 5 MILS RMS	3 - 5 MILS RMS
Static alignment time	3 to 5 minutes	3 to 5 minutes
Dynamic alignment heading accuracy	2 MILS RMS	2 MILS RMS
Dynamic alignment time	1 to 3 minutes	1 to 3 minutes
Position accuracy with GPS	10 meters CEP	10 meters CEP
Position accuracy without GPS	.25-.5% of distance traveled RMS	.25-.5% of distance traveled RMS
Elevation accuracy without GPS	1% (typical <.5%) of distance traveled RMS	1% (typical <.5%) of distance traveled RMS
Pitch and roll accuracy	1 MILS RMS	1 MILS RMS
Qualifications		
Environmentals	MIL-STD-810	MIL-STD-810
EMI	MIL-STD-461	MIL-STD-461
MTBF MIL-STD-1275 (hours)	13,200 - 16,100	12,500 - 15,000
Operating temperature	-32° C to 60° C	-32° C to 60° C
Power		
Supply voltage / MIL-STD-1275	18VDC to 32VDC	16VDC to 32VDC
Nominal power consumption	16W - 18W	18W - 21W
Connectivity		
Update rate	61 Hz	244 Hz

*Heading improves with lower latitude

	Model Specifics							
	Standard IRU				Enhanced IRU			
Model	9181C	9181E	9181G	9181J	9181D	9181F	9181H	9181K
Embedded GPS	N/A (DAGR compatible)	Mil/SAASM (MPE-S)	Commercial (Polaris Link)		N/A (DAGR compatible)	Mil/SAASM (MPE-S)	Commercial (Polaris Link)	
Size W x D x H (in.)	7.5 x 7.5 x 4.75	7.5 x 7.5 x 6.0			7.5 x 7.5 x 5.36	7.5 x 7.5 x 6.0		
Weight (lbs.)	7.5	8.5			8.5	9.0		
Export classification**	CCL 7A003.d.1 7A003.c.1	USML 12.d.2.2	USML 12.d.2.1	CCL 7A003.d.1 7A003.c.1	CCL 7A003.d.1 7A003.c.1	USML 12.d.2.2	USML 12.d.2.1	CCL 7A003.d.1 7A003.c.1
Standard I/O	(4) RS-422 Channels				(4) RS-422 Channels, (1) RS-232 Channel, (1) 10/100 Ethernet			
Optional I/O	N/A				(1) ARINC 429, NMEA Protocol (RS-422), VICTORY Protocol (Ethernet)			
Operating modes	Land	Land, Airborne			Land	Land, Seaborne, Airborne		

**Varies - contact GE Aviation to confirm Export Classification for each individual part number

Imagination at work

GE Avionics Systems
GE Aviation
3290 Patterson Avenue SE
Grand Rapids, MI 49512
U.S.A.
P: +616 430 0101
E: Reference.Products@ge.com

© 2017 GE Aviation Systems, LLC - All Rights Reserved

GE Aviation Systems, LLC is a subsidiary of the General Electric Company. The GE brand and logo are trademarks of the General Electric Company. Information is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
IRU 5/2017

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP