

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Abaco Systems / Condor Engineering CNIC-A2P* at our website: ***Click HERE***

GE
Intelligent Platforms



CNIC-A2P

Dual Port ARINC 664 Part 7 PMC Interface

Features

- AFDX/ARINC 664 Part 7 dual port interface (two independent 10/100 MHz full duplex ports)
- Available as PMC, PCI and cPCI
- 33/66 MHz, 32-bit PCI interface
- Includes AFDX and low-level Software Developer's Kit (SDK) at no additional charge.
- Advanced reception features
  - 20 nsec time-tags
  - IRIG-B synchronization
  - DMA transfer to host
  - Full throughput capability
  - Link level error detection
- Advanced transmission scheduling
  - Highly accurate
  - Flexible scheduling modes
  - DMA transfer from host
  - Full throughput capability
  - Link level error injection
- Advanced software support
  - Flexible packet capture API
  - AFDX/ARINC 664 Part 7 API
  - XML configuration format
  - Integrated log file format
  - Berkeley packet filter engine
- Four bi-directional avionics level discretes
- Input and output triggers per channel

Architecture

GE Intelligent Platforms' CNIC is a high performance interface for monitoring, generating or analyzing full-bandwidth AFDX/ARINC 664 Part 7 protocol traffic. GE's exclusive pipeline architecture maximizes packet throughput using parallel controllers and efficient DMA transfers, thereby avoiding the bottlenecks of CPU-based interface solutions.

Configurable as either one dual-redundant AFDX/ARINC 664 Part 7 interface or two independent ports, users have complete access to all frame and header data. Each incoming packet is tagged with a 20 nsec resolution, 64-bit time-tag. Real time traffic generation is highly accurate. An IRIG-B receiver/generator is included for synchronization to external IRIG-B time sources and for synchronizing multiple CNIC boards. In addition, I/O triggers, error detection/injection, BIT, and link/protocol level statistics are provided.

AFDX/ARINC 664 Part 7 Performance

Multiple CNICs in the same PC have been benchmarked at full bandwidth supporting all channels with 2000 VLs (Virtual Links), multiple Ports on each VL and minimum payloads (17 bytes).

Advanced Software Support

The CNIC comes with all the software development tools needed for user application development at no extra charge. The Cpcap, packet capture library, provides a complete set of functions for transmitting and receiving Ethernet frames. Frames from multiple ports can be logged or replayed using the open-source ntar log-file format. AFDX-A implements the AFDX/ARINC 664 Part 7 protocol stack including End Systems, redundancy management, Virtual Links, and Ports. An advanced XML-based Configuration File format is used to specify End Systems.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

CNIC-A2P – Dual Port ARINC 664 Part 7 PMC Interface

Specifications

Physical
- PMC mezzanine board
- Available for PCI and 3U or 6U cPCI formats

Environmental
- Commercial operating temp. range: 0°C to +70°C
- Optional temperature range: -40°C to +85°C
- Relative humidity: 5 to 90% (non-condensing)

Software
- Windows® 7 (32 and 64bit), Vista, XP, 2000, 2003 and Linux® support. Contact factory about availability of support for additional operating environments (including Linux, VxWorks®, and LabVIEW).
- Cpcap API Library
- AFDX-A API Library
- Ethereal GUI for ntar file analysis.

Connections
- Two IEEE 802.3 compliant Ethernet RJ-45 connectors
- High density 15-pin D-sub connector for In/Out triggers per port and four bi-directional avionics-level discretes

PCI Signal Compatibility
- Universal (5V or 3.3V)
- 66/33 MHz PCI bus operation
- DMA Tx/Rx data transfers
- CNIC-A2PX (on a PCI carrier) is compatible with PCI-X 1.0 and PCI slots

Timing Reference
- 64-bit time tag
- IRIG-B receiver (AM or TTL/DC)
- IRIG-B generator (TTL/DC)
- IRIG-B PPS synchronization with time tag
- Software-selectable internal wrap

Triggering
- Wait for external trigger to transmit
- Output when marked frame is transmitted
- Output when error-free packet received
- Output when error packet received

Port Parameters
- Full duplex IEEE 802.3 compliant ports
- Software-selectable 10/100 Mbps data rates
- Software-selectable auto-negotiation
- Software-selectable internal wrap

Ethernet Frame Reception
- Ethernet frames transferred to host buffers via DMA
- Min-to-copy capability
- High resolution time-tagging with 20 nsec resolution
- Link level error detection

Receive Statistics (64-bit counters)
- Separate counters for Link level errors
  - Physical symbol
  - Invalid preamble symbol
  - Invalid or missing SFD
  - Preamble length too short
  - Unaligned frame
  - IFG too short
  - Frame too short
  - Frame too long
  - CRC errors
- Total bytes received
- Total count of error free packets received
- Total count of packets with errors received
- Dropped packets

Ethernet Frame Transmission
- Ethernet frames transferred from host buffers via DMA
- Transmission scheduling with 20 nsec resolution
- Flexible scheduling modes
  - Minimum IFG delay (960 nsec between frames)
  - Per-frame specified delays (multiple conditions)
  - On external trigger
  - Playback delay modes
- Interrupt generation on user-identified frames

Transmit Statistics (64-bit counters)
- Total packets transmitted
- Total bytes transmitted

Error Injection
- Physical symbol error
- Preamble (symbol and length) errors
- Framing (byte alignment) error
- SFD (Start frame delimiter) error
- CRC error

Power (max.)
- +3.3 VDC: 950 mA

CNIC Architecture

User Level	Avionics Applications AFDX-A API Packet Capture Library (Cpcap)
OS level	CNIC Driver
Hardware Level	

Ordering Information

CNIC-A2P	Dual port 10/100 full duplex PMC module for AFDX/ARINC 664 Part 7 support
CNIC-A2PX	Dual port 10/100 full duplex PCI card (PMC on carrier) for AFDX/ARINC 664 Part 7 support
CNIC-A2P3	Dual port 10/100 full duplex 3U CompactPCI card (PMC on carrier) for AFDX/ARINC 664 Part 7 support

Ordering Options

-R suffix	Ruggedized, ext temp (only available on PMC native board)
-C suffix	Conduction cooled, conformal coated, extended temp, no front I/O (only available on PMC native board)

Optional Software

BT-AFDX-A	Visual analyzer for AFDX/ARINC 664 Part 7
BT-AIL-A2	Visual analyzer for AFDX/ARINC 664 Part 7 with ARINC 429 and generic EDE

About GE Intelligent Platforms

GE Intelligent Platforms is a division of GE that offers software, control systems, services, and expertise in automation and embedded computing. We offer a unique foundation of agile and reliable technology providing customers a sustainable competitive advantage in the industries they serve, including energy, water, consumer packaged goods, oil and gas, government and defense, and telecommunications. GE Intelligent Platforms is headquartered in Charlottesville, VA. For more information, visit www.ge-ip.com.

GE Intelligent Platforms Contact Information

Americas: **1 877 429 1553** Global regional phone numbers are listed by location on our web site at **defense.ge-ip.com/avionics-contacts**

defense.ge-ip.com/avionics

©2012 GE Intelligent Platforms, Inc. All rights reserved.
All other brands or names are property of their respective holders.
Specifications are subject to change without notice.

02.12 GFA-747A

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP