

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*



DATA SHEET

MODEL 412

Adaptor connects two VMEbus systems

Share memory and special purpose boards between two VMEbus systems with Bit 3's easy-to-use, cost-effectiv Adaptor. Model 412 provides high speed data transfers between two systems, with minimal software support.

The Model 412 Adaptor expands your computing environment by combining the power, memory and card capa systems. Interconnected by a Bit 3 Adaptor, each system can:

- Directly address the other's resources as though they were local.
- Pass blocks of data, I/O commands, and interrupts to the other system.
- Execute random access reads and writes to the remote VMEbus.

Plus, the Model 412 can function as a coprocessor or as the only bus controller in the remote VMEbus chassis.

With the Bit 3 Adaptor, each bus operates independently. The timing of the two buses is linked only when a me reference is made to an address on one system that translates to a reference on the other. The integrity of the int between the Adaptor cards is maintained by parity checks on address, control and data lines.

A32/D32 random access cycles, from either system, are supported by the Adaptor.

Other Bit 3 Adaptors, supporting a wide variety of buses, can be used with Model 412 Adaptors to connect mul computers and systems in star, daisy-chain or modified star/daisy-chain configurations.

COMMUNICATION BETWEEN SYSTEMS

Model 412 supports Memory Mapped inter-system communication. Memory Mapping controls random access RAM, dual-port memory, and remote bus I/O.

Memory Mapping provides an easy-to-use, flexible interface with low overhead that permits two processors to via random-access memory reads and writes. The transmitting system can access up to 4G bytes of memory in system through a window in the transmitting system's bus address space.

Memory Mapping permits high-speed random access 32-bit reads and writes to either system at speeds compar and writes to local memory. Also, a portion of memory space can be mapped in the opposite direction allowing to become a bus master on the other system's bus.

Two Memory Mapping techniques are supported: Direct Mode (with address biasing) and Page Mode. Either te be used to control access to remote bus memory and dual-port memory. Access to remote bus I/O is not affecte mapping mode.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Direct Mode has a one-to-one relationship between address windows. Data are transferred through one window an equal size window on the other bus. Window size is configured via jumper settings.

In Page Mode, a window in the transmitting bus address space is coupled with a 16-bit programmable register. within the window provides the lower 16-29 address bits. The I/O register provides the upper 16-12 bits of the receiving bus address. Thus, the transmitting system can scan 4G bytes of memory in the receiving system by p through the receiving system's address space.

Memory Mapping also controls access to dual-port memory. Dual Port RAM is an optional card installed on eit card. Dual Port RAM provides a memory buffer; saves the cost of additional memory cards; and requires no ad VMEbus card slots.

Optional Dual Port RAM provides shared memory space accessible by random access reads and writes from eit Dual Port RAM access uses only the bandwidth of the accessing bus. Consequently, transfer speed is increased be exchanged with minimal impact on the performance of the other system's bus. Both systems can access Dual simultaneously; the Adaptor arbitrates accesses.

Dual Port RAM cards now available from Bit 3 include: 32K, 128K, 1M, 2M, 4M, and 8M byte cards.

Memory Mapping is also used to control access to remote bus I/O.

INTERRUPT AND ERROR HANDLING

Any of the seven VMEbus interrupts may be passed to the remote system for handling by that system's process Programmed interrupts may be passed in either direction by writing to an I/O register on an Adaptor card.

There are three sources of interrupts from the Adaptor:

- Interrupts from the remote VMEbus backplane. Interrupt lines IRQ7 - IRQ1 may be passed from the rem
- Programmed interrupts from the remote card.
- An interface error interrupt that is activated when a timeout, parity error or bus error condition is detected Adaptor card.

VMEbus SYSTEM CONTROLLER CAPABILITY

In addition to VMEbus control and bus master capabilities, the Model 412 Adaptor can function as the VMEbu controller, if no other card is doing so. If the VMEbus system is to be used primarily as an expansion chassis fo VMEbus boards, this feature saves the expense of an additional VMEbus system controller.

If configured as the system controller, the Model 412 Adaptor card provides level 3 bus arbitration, the VMEbu clock and system reset, and the BERR global timeout.

TECHNICAL HIGHLIGHTS

- Random access reads and writes from system to system.
- Flexible mapping of address space between the systems' memory and I/O address space.
- A16, A32 or A24 Addressing, and D32, D16 and D8 Data Transfer mode support.
- Page Mode allows access to 4G bytes of memory through page size from 64K to 1M byte.
- Add up to 8M bytes of shared memory via optional Dual Port RAM cards.
- Support for byte and word swapping in hardware.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

- Interrupts can be exchanged between systems.
- Parity checking on address control and data lines and on the interface between Adaptor cards.
- Round EMI-shielded cable to 25 feet.
- Meets IEEE 1014C specifications.
- Recognized under the component program of Underwriter Laboratories, Inc.

REQUIRED COMPONENTS

- Two 6U VMEbus Adaptor cards (included in Model 412 package).
- A round EMI-shielded cable to connect the Adaptor cards (purchased separately from Bit 3).

Each Model 412 package contains: two VMEbus Adaptor cards, and a manual. A cable is required but is order so that you can specify the appropriate length and type for your installation.

OPTIONS

- Dual Port RAM

```
32K byte          Model 400-201

128K byte          Model 400-202

1M byte          Model 400-203

2M byte          Model 400-204

4M byte          Model 400-205

8M byte          Model 400-206
```

- Cable (one required)

```
8' Round EMI-Shielded          Model 400-107

25' Round EMI-Shielded          Model 400-108
```

Bulkhead connector configurations (contact Bit 3 for configurations)

- Fiber-Optic Interface Cards

Provide a high-speed fiber-optic link between two VMEbus chassis equipped with Bit 3 VMEbus Adaptor.

Model 400-5 Two-Fiber cards supports two fiber-optic data paths.

Model 400-6 Four-Fiber supports four fiber-optic data paths.

For more information, request the Model 400-5 & Model 400-6 data sheet.

- Fiber-Optic Cable

High-quality, OFNP-grade, 62.3/125 micron glass duplex cable with tight buffer construction and ST-style conr standard cable are 5 meters (approx. 16') in length; custom lengths to 2 km are available.

TRADEMARK DISCLAIMER

All trademarks are the property of their respective company.

Specifications subject to change without notice.

Pub. No. 100,178 10/91

Cable Configuration Guide Warranties

Repair Service Products List

How To Contact Bit 3 Home Page

Revised 6/11/96

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP