

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Electric Actuator Smart Controller (EASC)

Model SCC10



Models
SCC10-115/230 VAC 115 or 230 Volt A.C. Actuators
SCC10-24 VAC 24 Volt A.C. Actuators

EASC (Micro-Processor Based Analog Controller)

The Electric Actuator Smart Controller (EASC Model SCC-10) card provides accurate positioning control of electric motor actuators using an analog input signal. Setup and calibration is greatly simplified using microprocessor based technology. There are no dip switches to set or trim pots to adjust. Setup is quick and easy using the EASC menu viewed on an LED display. No external meters are required, even for potentiometer setup. Once the initial menu settings are chosen, the EASC performs a self-calibration routine, applying the menu selections to actual actuator performance. Calibration values are then stored in permanent non-volatile memory.

Features

- Onboard LED display facilitates setup and calibration using the EASC Menu Setup.
- Menu selection of input/output ranges including 4-20 mAdc, 1-5 VDC, 2-10 VDC and 0-10 VDC, or virtually any custom range required.
- Automatic calibration; no resistors to add; no jumpers, trim pots or dip switches to adjust. Calibration is as simple as pressing a button.
- Three relay outputs: fault, full closed and full open. (A.C. Models Only.)
- Current sensing (over torque protection). — Optional on A.C. Models. Standard on D.C. Models.
- Menu selectable fail options.
- Intelligent positioning reduces motor cycling, increases motor life and extends the actuator duty.
- Auto-jog feature. Constantly corrects and refines the positioning accuracy.
- Quick disconnect terminal strips facilitate fast and easy actuator maintenance and troubleshooting.
- Always wires the same; no need to determine rotation direction during installation; rotation is selected using the EASC Menu.
- Robust power switching components, designed specifically for actuator motors, virtually eliminates field failures.

North American Sales Company, Inc. - Tel: 310-459-8430 - email: sales@nasco-corp.com - www.nasco-corp.com

Electric Actuator Smart Controller (EASC)

Model SCC10

Specifications

Power Requirements
Model SCC10-115/230A: 115 or 230 VAC, 1 Phase, 50/60 Hz. (Jumper selectable)

Model SCC-24 VAC: 24 VAC, 50/60 Hz.

Model SCC-24 VDC: 10-28 VDC

Input Command Signal
Menu selectable factory defaults:

— 4 – 20 mADC
— 1 – 5 VDC
— 2 – 10 VDC
— 0 – 10 VDC

Infinite adjustment using EASC menu system

Signal Impedance
Input: 250Ω current, 200KΩ voltage
Output: maximum load 500Ω current, minimum 500KΩ voltage

Dimensions
3-1/2 x 1-5/8 x 4 in.

Output Command Signal
Menu selectable factory defaults:

— 4 – 20 mAdc
— 1 – 5 VDC
— 2 – 10 VDC
— 0 – 10 VDC

Infinite adjustment using EASC menu system

Power Output
Solid state, isolated from the input command and output position signals and rated at:

— 5 amps continuous at 115 VAC
— 5 amps continuous at 230 VAC
— 5 amps continuous at 24 VAC
— 10 amps continuous at 24 VDC

All ratings assume the EASC is mounted on the actuator base plate.

Sensitivity
Fully adjustable from 0.5% of total span, factory set to 1% of total span.

Dead Band
Automatically set during calibration. Factory default at 1% of total span. Additional settings available using the EASC Menu System.

Zero Adjustment
Automatically set during calibration.

Span Adjustment
Automatically set during calibration.

Split Range
Settable within the span range using at least 1.5VDC or 3mA of input.

Remote Control
Optional Modus RTU control of all controller functions over a RS-485 multi-drop network

Ambient Temperature
-40°F (with heater) to +150°F (-40°C to +65°C)

Action on Loss of Command Signal
Factory default:

— Fail in last position (no movement)

Additional settings available through EASC menu:

— Fail open (maximum signal value)
— Fail closed (minimum signal value)
— Fail to a preset position

Relay Outputs - A.C. Models Only
Three dry contacts outputs:

— Fault indicating loss of power, fuse failed, command signal loss or failure to move to position in preset time.
— End of travel open
— End of travel closed
— Contact Ratings: 1A @ 30VDC, 0.5A @ 135VAC resistive

North American Sales Company, Inc. - Tel: 310-459-8430 - email: sales@nasco-corp.com - www.nasco-corp.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP