ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *General Micro Systems GMSV36-01-E* at our website: *Click HERE*


REDEFINING EMBEDDED REAL-TIME COMPUTER DESIGN



V360 OEM Family

68030 Based VME Single Board Computer


DESIGNED FOR EMBEDDED CONTROL AND REAL-TIME APPLICATIONS



PROCESSORS:	68030 or 68EC030 at 25, 33 or 40 MHz
MEMORY:	2, 4, 8, 16 or 32 MB DRAM
VMEBUS:	VME A32:D32 Master Interface with System Controller Functions and 7 Level Interrupt Handler
STANDARD I/O:	SCSI, Ethernet and 8 Asynchronous Serial Channels
OPTIONAL:	Removable Ethernet, SCSI and VME Interfaces for Application Specific Customization
I/O FLEXIBILITY:	MiniSAM Expansion Interface supports non-standard I/O requirements.
100% CMOS:	Low power consumption and high reliability
REAL-TIME O/S:	Supports VxWorks, OS-9, pSOS+, and PDOS

GENERAL MICRO SYSTEMS
INCORPORATED

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



68030 with Expandable Memory and Modular I/O

Single Board Solution

The V36 is designed for real-time applications requiring a high performance single board computer with system control capabilities and extensive I/O flexibility.

Based upon the 68030 or 68EC030 CPU at 25, 33, or 40 MHz, the V36 features Ethernet, SCSI, battery-backed Real-Time Clock, VME Master Interface and 8 channels of asynchronous RS-232 or RS-422 serial I/O with 5 lines of optically isolated digital I/O. The Ethernet, SCSI and VME Interfaces are optionally removable, allowing designers to choose the features that best meet their application needs without paying for unnecessary components.

The V36 is available with 2, 4, 8, 16 or 32 MB of DRAM. The 2, 8 and 32 MB configurations are two-way interleaved, providing high speed burst transfers to the CPU cache. Non-volatile memory support includes 256 KB of battery-backed SRAM, dual accessed between the Ethernet Controller and the CPU, and (2) 32 pin JEDEC sockets allowing up to 2 MB of EPROM and 8 MB of Flash.

A variety of custom and off-the-shelf I/O functions can be added to the V36 via the A24:D32 MiniSAM (Special Application Module) Expansion Interface. Additional serial I/O requirements are supported by replacing the SCSI Interface with an additional 8 channels of asynchronous serial, or 2 channels of synchronous serial.

To better facilitate embedded design, all I/O functions on the V36 are routed through the P2 connector, allowing cabling to be attached to a break-out board on the back side of the card cage. Because there is no cabling attached to the front panel, the V36 is easy to remove during development and upgrades.

The V36 P2 I/O is plug compatible with the remaining members of the OEM family of boards, the V39, V46 and V49. The V3X and V4X family members are based on the 68030 and 68040 processors, respectively, while the VX9 members provide extensive VME capability via the VIC64 VME Interface Controller, including an A32:D64 Master/Slave Interface. The VX6 members provide a Master Only Interface for cost sensitive applications.

Through the use of buffers and independent local buses, the CPU, Ethernet and SCSI can operate simultaneously and independently, without monopolizing the CPU bus. Component level DMA allows the Ethernet and SCSI Controllers to transmit and receive data to/from their respective SRAM buffers, which are dual ported to the CPU. This configuration lets all three channels (CPU, Ethernet and SCSI) operate concurrently for maximum performance and collision free operation.

Extensive use of CMOS components guarantees low overall power consumption and reduced thermal stress, thereby providing a higher MTBF (Mean-Time Between Failure) rate.

Designed and manufactured in the U.S.A., all GMS products carry a one year warranty with extended warranties available.

Software Support

Software support is available for all major real-time operating systems, including VxWorks, OS-9, pSOS+, RTMX and PDOS, with POSIX compliance available. A debugger/monitor is also available, providing complete diagnostic capabilities in software, including a single line assembler/disassembler.

Standard Features

- ❒ 68030 or 68EC030 CPU at 25, 33 or 40 MHz
- ❒ 2, 4, 8, 16 or 32 MB DRAM (2, 8 and 32 two-way interleaved)
- ❒ (2) 32 pin JEDEC Sockets for EPROM/Flash
- ❒ 2, 4, 6, 8 MB Flash
- ❒ A32:D32 VME Master Interface
- ❒ A24:D32 Local Expansion Bus (MiniSAM)
- ❒ Ethernet Controller
- ❒ SCSI with dual ported, 32 KB buffer
- ❒ 256 KB SRAM
- ❒ 8 independent, asynchronous channels of Serial I/O (RS-232/422)
- ❒ 5 lines of optically isolated Digital I/O
- ❒ Epson 72421 battery-backed Real-Time Clock

Optional Features

- ❒ Fast/Wide SCSI 2 (AIO Module)
- ❒ Removable Ethernet, SCSI and VME Interfaces
- ❒ 68882 Co-Processor
- ❒ 1024 x 768 SVGA Controller Card
- ❒ Seriplex Controller

Performance	25 MHz	33 MHz	40 MHz
MIPS	23	31	38
MFLOPS	2	3	4

Specification	Typical	Maximum
Power Consumption	2A	2.4A
Operational Temperature	0 - 60°C	
Storage Temperature	-55 - +150°C	
Supply Voltage	5.0V DC	5.25V DC

GENERAL MICRO SYSTEMS

CORPORATE & WESTERN REGIONAL OFFICE:

8358 MAPLE PLACE ❒ P.O. BOX 3689
RANCHO CUCAMONGA ❒ CALIFORNIA 91730

Tel: (909) 980-4VME (4863) Fax: (909) 987-4VME (4863)
Sales Hotline: (800) 307-4VME (4863)
E-mail: sales@gms4vme.com

All trademarks are owned by their respective companies.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP