ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Grundfos MTC2-60/6 U-W-A-AUUV* at our website: *Click HERE*

Company name:
Created by:
Phone:

Date: 27/02/2020

Qty.	Description
1	**MTC2-60/6 A-W-A-AQQV**



Note! Product picture may differ from actual product

Product No.: 43634466
Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump has the following characteristics:
- Installation length according to DIN 5440.
- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
- Mechanical shaft seal according to EN 12756.

The pump is close-coupled with a 3-phase motor.

Liquid:

Pumped liquid:	Water
Liquid temperature range:	-10 .. 90 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³

Technical:

Rated flow:	50 l/min
Rated head:	53.4 m
Chambers:	6
Code for shaft seal:	AQQV
Curve tolerance:	ISO9906:2012 3B

Materials:

Pump housing:	Cast iron EN 1561 EN-GJL-200 ASTM A48-25B
Impeller:	Stainless steel EN 1.4301 AISI 304

Installation:

Maximum ambient temperature:	40 °C
Maximum operating pressure:	10 bar

GRUNDFOS

Company name:
Created by:
Phone:

Date: 27/02/2020

Qty.	Description	
	Max pressure at stated temp:	10 bar / 90 °C
	Type of connection:	NPT
	Size of outlet connection:	3/4 inch
	Electrical data:	
	Frame size:	MG80A2-D1
	Rated power - P2:	1.06 kW
	Mains frequency:	60 Hz
	Phases:	3
	Rated voltage:	208-230 YY/460 Y V
	Rated current:	4,35-4,05/2,02 A
	Maximum current consumption:	5-4,5/2,26 A
	Rated speed:	0 rpm
	Enclosure class (IEC 34-5):	IP54
	Insulation class (IEC 85):	F
	Built-in motor protection:	NONE
	Others:	
	Minimum efficiency index, MEI â‰¥:	0.7
	Net weight:	14.1 kg
	Gross weight:	14.1 kg

GRUNDFOS

Company name:
Created by:
Phone:

Date: 27/02/2020

Description	Value
General information:	
Product name:	MTC2-60/6 A-W-A-AQQV
Product No:	43634466
EAN number:	5700395990645
	5700395990645
Technical:	
Rated flow:	50 l/min
Rated head:	53.4 m
Chambers:	6
Impellers:	6
Code for shaft seal:	AQQV
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Model:	A
Materials:	
Pump housing:	Cast iron
	EN 1561 EN-GJL-200
	ASTM A48-25B
Impeller:	Stainless steel
	EN 1.4301
	AISI 304
Material code:	A
Installation:	
Maximum ambient temperature:	40 °C
Maximum operating pressure:	10 bar
Max pressure at stated temp:	10 bar / 90 °C
Type of connection:	NPT
Size of outlet connection:	3/4 inch
Connect code:	W
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-10 .. 90 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Frame size:	MG80A2-D1
Rated power - P2:	1.06 kW
Mains frequency:	60 Hz
Phases:	3
Rated voltage:	208-230 YY/460 Y V
Rated current:	4,35-4,05/2,02 A
Maximum current consumption:	5-4,5/2,26 A
Rated speed:	0 rpm
Enclosure class (IEC 34-5):	IP54
Insulation class (IEC 85):	F
Built-in motor protection:	NONE
Others:	
Minimum efficiency index, MEI â‰¥:	0.7
Net weight:	14.1 kg
Gross weight:	14.1 kg

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP