

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Emerson / Heurikon Baja4700* at our website: *Click HERE*

Baja4700 Technical Specs

Bus Interface

- **VMEbus**
- VME64 architecture: D64A32(7)
- Operates in Master or Slave Mode
- 64-bit and 32-bit wide block transfers using local DMA capability
- System level controller functions including 4 level arbitration
- Uses VIC64 VMEbus interface chip optimized via custom ASIC
- 2K D64 block transfer rates:
    - 166 MHz version:
        - Read - 64.46 MBytes/sec
        - Write - 62.95 MBytes/sec
    - 175 MHz version:
        - Read - 60.39 MBytes/sec
        - Write - 61.82 MBytes/sec

- **VME64 Extensions support**
- 5-row P1 & P2 backplane connectors (100% compatible with 3-row DIN backplanes)
- Provides 46 additional user-definable lines on P2 connector rows D&Z
- 35 additional signal ground lines
- Slot geographical addressing
- 3.3 Volt power
- EMC front panel reduces EMI & RFI radiation

- **Mailbox interrupts**
- Allows remote control of Baja4700 via specified VMEbus addresses
- CPU interrupt and VMEbus lock functions supported

- **PMC**
- PCI Mezzanine Card interface
- Two 32-bit PMC expansion interfaces
- Uses PLX PMC9060 controller with 2 DMA channels
- Accepts 2 single-wide or 1 double-wide PMC module
- I/O can be routed to front panel or out VMEbus P2 connector

---

Processor & Memory

- **IDT ORION R4700**
- IDT R4700 implementation of MIPS R4000 architecture
- Available at 166 or 175 MHz

- True 64-bit RISC processor
- 5-stage instruction pipeline
- 16 KB two-way set associative instruction cache
- 16 KB data cache
- 4-deep write buffer
- MMU and Translation Lookaside Buffer (TLB)
- On-chip system control coprocessor manages exception handler, virtual memory system and transitions between processor operating modes
- 64-bit floating point unit on-chip
- Instruction set fully compatible with R4000 processor family

- **Random Access Memory**
- 16 or 64 Mbytes DRAM with parity
- 64-bit data bus
- 2-way bank interleaved architecture
- One parity bit per byte
- Transparent discrete hardware refresh

- **Read Only Memory**
- Up to 512 Kbytes capacity
- Supports 64K, 128K and 512K

- **Flash Memory**
- 1 or 4 Mbytes flash memory
- 512 Kbytes used for monitor & power-on diagnostics
- Provides field upgradeable non-volatile program storage

- **EEPROM**
- 2 Kbytes Non-Volatile RAM
- Storage for user definable parameters such as baud rates, software and hardware revision levels and configuration information
- Provides field upgradeable non-volatile program storage

- **Timers/Counters**
- Real-time clock with 10 msec resolution
- Three 32-bit timer/counters with 62.5 nsec resolution
- Interrupt capability

Peripheral I/O

- **Ethernet Interface**
- Intel 82596CA 32-bit LAN coprocessor
- On-chip DMA, FIFO's, and memory management
- Conforms to IEEE 802.3
- AUI interface connector via cable off front panel
- 800 Kbytes/sec throughput obtained using TCP/IP protocol

- **Serial I/O**
- Two front panel serial I/O ports provided via ASIC
- Intel 8251A UART emulation
- RS-232 standard

- Transfer rates up to 1Mbit/sec (cable length dependent)

Software support

- Wind River Systems' VxWorks real-time operating system and development environment
- ISI's pSOS real-time operating system and development environment
- On-board monitor and power-on diagonostics

Physical Characteristics

- Multilayer with ground and VCC planes
- Board size: 233.5 mm x 160 mm (9.19 in. x 6.3 in.)
- Power requirements: +5VDC @ 5.8A, +12VDC @ 50mA, -12VDC@30mA (power measured with on 16MB board with no PMC modules and no Ethernet transceiver)
- Storage Temperature: -40C to 85C
- Operating range: 0-55C, 85% relative humidity (non-condensing)

- **Front Panel**
- Reset / Interrupt switch
- LED display
- Ethernet port connector
- Serial port connector

Target Applications

- Communications system control
- Network bridge
- Switch control
- Video on demand server
- Data acquisition
- Imaging

Copyright © 1994, 1995, 1996 Heurikon Corporation. All rights reserved.
Certain names, logos, designs, titles, words or phrases on this page may constitute trademarks, servicemarks, or tradenames of Heurikon Corporation or other entities which may be registered in certain jurisdictions.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP