ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Hexagon / Novatel ProPak-V3-424-L1L2* at our website: *Click HERE*

Antennas GPS-701-GG & GPS-702-GG

PINWHEEL® ANTENNAS ENHANCE FLEXIBILITY AND REDUCE COSTS



DUAL CONSTELLATION FOR ENHANCED POSITIONING

The GPS-701-GG uses the L1 frequency while the GPS-702-GG uses the L1 and L2 frequencies. Both antennas offer combined GPS+GLONASS signal reception. Customers can use the same antenna for GPS-only or dual constellation applications, resulting in increased flexibility and reduced equipment costs.

STABLE PHASE CENTER

The phase center of these two antennas remains constant as the azimuth and elevation angle of the satellites change. Signal reception is unaffected by the rotation of the antenna or satellite elevation, so placement and installation of the antennas can be completed with ease. With the phase center in the same location for both the L1 and L2 signals and with minimal phase center variation between the antennas, these antennas are ideal for baselines of any length.

DURABLE, FUTURE-PROOF DESIGN

These rugged antennas are enclosed in a durable, waterproof housing and meet MIL-STD-202F for vibration and MIL-STD-810G for salt spray. Sharing the same form factor as other NovAtel GPS-700 series antennas, the GPS-701-GG and GPS-702-GG antennas are compact and lightweight, making them highly portable and suitable for a wide variety of environments and applications.

Both antennas meet the European Union's directive for Restriction of Hazardous Substances (RoHS), so integrators can be confident these antennas can be used in system designs for years to come.

BENEFITS

+ Choke ring antenna performance without size and weight
+ Reduces equipment costs
+ Placement flexibility and precision positioning, even on long baselines
+ Eliminates need for future redesign

FEATURES

+ L1 or L1/L2 options
+ GPS+GLONASS signal reception
+ Excellent multipath rejection
+ Highly stable phase center
+ RoHS compliant

If you require more information about our antennas, visit www.novatel.com/antennas

GPS-701-GG & GPS-702-GG

PERFORMANCE

3 dB Pass Band	
L1	1588.5 ± 23.0 MHz (typical)
L2	1236 ± 18.3 MHz (typical)
Out-of-Band Rejection	
L1 ± 100 MHz	30 dBc (typical)
L2 ± 200 MHz	50 dBc (typical)
LNA Gain	29 dB (typical)
Gain Roll-Off (from Zenith to Horizon)	
L1	13 dB
L2	11 dB
Noise Figure	2.0 dB (typical)
VSWR	≤2.0 : 1
L1-L2 Differential Propagation Delay	5 ns (maximum)
Nominal Impedance	50 Ω
Altitude	9,000 m

PHYSICAL AND ELECTRICAL

Dimensions	185 mm diameter[1] × 69 mm
Weight	500 g
Power	
Input Voltage	+4.5 to +18.0 VDC
Current	35 mA (typical)
Connector	TNC female N-Type (optional)[2]

ENVIRONMENTAL

Temperature	
Operating	-40°C to +85°C
Storage	-55°C to +85°C
Humidity	95% non-condensing
Vibration (operating)	
Random	MIL-STD-202F
Sinusoidal	SAEJ1211, Section 4.7
Shock	IEC 68-2-27 (Ea)
Bump	IEC 68-2-29 (Eb)
Salt Spray	MIL-STD-810G, 509.5
Waterproof	IEC 60529 IPX7
Compliance	FCC, CE
RoHS	EU Directive 2011/65/EU

For the most recent details of this product:
www.novatel.com/products/gnss-antennas/high-performance-gnss-antennas/

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)
or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

Version 8 Specifications subject to change without notice.
©2015 NovAtel Inc. All rights reserved.
NovAtel and Pinwheel are registered trademarks of NovAtel Inc.
Printed in Canada.

D09719 November 2015

1. Not including tape measure tab. Full diameter with tape measure tab is 195 mm.
2. N-Type connector is available on the GPS-702-GG only.
3. L2 specifications apply to the GPS-702-GG only.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP