ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *HK / Honda MR-50LW* at our website: ***Click HERE***

Interface Connectors

MR series

Rectangular Connectors

Outline

The MR series of connectors are small-sized rectangular connectors developed for data terminal equipment. The connector provides highly reliable flat terminals, and has been developed with a view of improving cost efficiency.

Features

- Provides a dual mechanism of screws and spring-locks to withstand any shock.
- Provides a dust-tight mechanism capable of withstanding environments.
- Best suited for downsizing equipment due to the robust smaller-size, lightweight, and high density.
- Provides a case for relay connections.

Principal Applications

Factory automation, communications equipment, data terminal equipment, instrumentation equipment, medical equipment, leisure electronic equipment, etc.

Electrical Characteristics


Rated voltage	300V AC (r.m.s.)
Rated current	3 A/pin
Insulation resistance	Over 1000 megohms (at 500V DC)
Dielectric withstanding voltage	1000V AC (r.m.s.)
Contact resistance	7 (30) milliohms or less The value enclosed within parentheses ( ) is the contact resistance for right-angle type connectors.

Document Disclaimer


- When placing orders with us, minimum order quantities are set for every product.
- Be sure to contact us before starting preliminary design of PCBs using our connectors.
- The specifications and information shown in the catalog are subject to change without notice.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Recommended PCB layout for straight through hole type female connectors




8-contact connector




25-contact connector




16-contact connector



34-contact connector



20-contact connector




50-contact connector


Note: The dimensions shown in these figures are on the PCB mounted face.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Recommended PCB layout for straight through hole type male connectors




8-contact connector




25-contact connector




16-contact connector



34-contact connector



20-contact connector




50-contact connector


Note: The dimensions shown in these figures are on the PCB mounted face.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Recommended PCB layout for right-angle through hole type female connectors




8-contact connector




25-contact connector




16-contact connector



34-contact connector



20-contact connector




50-contact connector


Note: The dimensions shown in these figures are on the PCB mounted face.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Recommended PCB layout for right-angle through hole type male connectors




8-contact connector




25-contact connector




16-contact connector



34-contact connector



20-contact connector




50-contact connector


Note: The dimensions shown in these figures are on the PCB mounted face.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Recommended PCB layout for MRH series through hole type




MRH-20MD+
-20RMD+




MRH-50MD+
-50RMD+




MRH-20MA+
-20RMA+




MRH-50MA+
-50RMA+




MRH-20FD+
-20RFD+



MRH-50FD+
-50RFD+



MRH-20FA+
-20RFA+




MRH-50FA+
-50RFA+


Note: The dimensions shown in these figures are on the PCB mounted face.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Recommended PCB layout for MRF series through hole type




MRF-96FD( )+
-96FDW
-96FDWG+



MRF-96MD( )+



MRF-96FL( )+




MRF-96ML( )+

Note: The dimensions shown in these figures are on the PCB mounted face.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Recommended panel cut-out dimensions for soldering type, wire wrapping or crimping type



Recommended panel cut-out dimensions for soldering type, wire wrapping or crimping type

Connector	A	B	C	øD	E (Reference)	F
8-contact connector	17.4	12.4	11.5	2.8	63.6	20
16-contact connector	25.2	20.2			72.3	19
20-contact connector	27.8	22.8			74.9	
25-contact connector	33.0	28.0			80.1	20
34-contact connector	40.8	35.8			87.9	
50-contact connector	56.4	51.4			103.5	21
60-contact connector	52.6	46.8	14.5	3.3	98.7	23

Flow temperature profile (for reference purposes)



The flow temperature profile as shown above is for reference purposes. This profile depends on requirements such as the PCB size. Thus, this profile may not meet with your specific situation. Please evaluate your PCB-mounting soldering and set your own flow temperature profile.

●Applicable products

MR series through hole type connector

MRH series through hole type connector

MRF series through hole type connector


The profile shown in this drawing is applicable only for those products shown above.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Combination of Connectors, Case, and Locking Blocks


Note 1: Product Part No. in the square brackets [ ] shows a male or female connector, which is the opposite of the male or female connector as above.
Note 2: [ ] Product Part No. in the box shows a finished product Part No.

● Example of using vertical type or dual-purpose vertical and horizontal type case




Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

● Example of using skew type cases



● Example of using cases for relay connections



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Product List



Soldering type
female connector for panel
MR-( )F( )

M-16
MR series...14



Soldering type
male connector for panel
MR-( )M( )

M-17
MR series...15



Wire wrapping type
female connector for panel
MR-( )FW( )

M-18
MR series...16



Wire wrapping type
male connector for panel
MR-( )MW( )

M-19
MR series...17



Straight through hole type
female connector for PCB
MR-( )FD2( )

M-20
MR series...18



Straight through hole type
male connector for PCB
MR-( )MD2( )

M-21
MR series...19



Right-angle through hole type
female connector for PCB
MR-( )FA( )

M-22
MR series...20



Right-angle through hole type
male connector for PCB
MR-( )MA( )

M-23
MR series...21




Soldering type
female connector with locking
block for panel
MR-( )RF( )+

M-24
MR series...22



Soldering type
male connector with locking
block for panel
MR-( )RM( )+

M-25
MR series...23



Wire wrapping type
female connector with locking
block for panel
MR-( )RFW( )+

M-26
MR series...24




Wire wrapping type
male connector with locking
block for panel
MR-( )RMW( )+

M-27
MR series...25



Straight through hole type
female connector with locking
block for PCB
MR-( )RFD2( )+

M-28
MR series...26



Straight through hole type
male connector with locking
block for PCB
MR-( )RMD2( )+

M-29
MR series...27



Right-angle through hole type
female connector with locking
block for PCB
MR-( )RFA( )+

M-30
MR series...28



Right-angle through hole type
male connector with locking
block for PCB
MR-( )RMA( )+

M-31
MR series...29



Soldering type
female connector with brace
for panel
MR-( )SRF( )+

M-32
MR series...30



Soldering type
male connector with brace
for panel
MR-( )SRM( )+

M-33
MR series...31



Wire wrapping type
female connector with brace
for panel
MR-( )SRFW( )+

M-34
MR series...32



Wire wrapping type
male connector with brace
for panel
MR-( )SRMW( )+

M-35
MR series...33

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



Straight through hole type
female connector with brace
for PCB
MR-( )SRFD2( )+
M-36
MR series...34



Straight through hole type
male connector with brace
for PCB
MR-( )SRMD2( )+
M-37
MR series...35



Right-angle through hole type
female connector with brace
for PCB
MR-( )SRFA( )+
M-38
MR series...36



Right-angle through hole type
male connector with brace
for PCB
MR-( )SRMA( )+
M-39
MR series...37



Vertical type plastic case
MR-( )L+

M-40
MR series...38



Vertical type plastic case
for junction
MR-( )LK2+

M-41
MR series...39



Dual-purpose vertical and
horizontal type plastic case
MR-( )LW+

M-42
MR series...40



Skew type plastic case
MR-( )NS+

M-43
MR series...41



Skew type plastic case
MR-( )NSA+

M-44
MR series...42



Skew type plastic case
MR-( )NSB+

M-45
MR series...43



Locking block kit
MR-R( )+

M-46
MR series...44



Brace kit
MR-( )SR+

M-47
MR series...45



Brace kit
MR-( )SRA( )+

M-48
MR series...46



Dust cover for female connector
MR-( )CF

M-49
MR series...47



Key for preventing misinsertion
MR-PK

M-50
MR series...48



Tool for extracting male contact
MR-K1

M-51
MR series...49



Crimping type female insulator
for panel
MRP-( )F01

M-52
MR series...50



Crimping type male insulator
for panel
MRP-( )M01

M-53
MR series...51



Crimping type
female insulator with locking
block for panel
MRP-( )RF01+
M-54
MR series...52



Crimping type
male insulator with locking
block for panel
MRP-( )RM01+
M-55
MR series...53

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



Crimping type female contact
MRP-F1( )( )

M-56
MR series...54



Crimping type male contact
MRP-M1( )( )

M-57
MR series...55



Crimping type contact extraction tool
MRP-MF+

M-58
MR series...56



Straight through hole type female connector for PCB
MRH-( )FD( )+

M-59
MR series...57



Straight through hole type male connector for PCB
MRH-( )MD( )+

M-60
MR series...58



Right-angle through hole type female connector for PCB
MRH-( )FA( )+

M-61
MR series...59



Right-angle through hole type male connector for PCB
MRH-( )MA( )+

M-62
MR series...60



Straight through hole type female connector with locking block for PCB
MRH-( )RFD( )+
M-63
MR series...61



Straight through hole type male connector with locking block for PCB
MRH-( )RMD( )+
M-64
MR series...62



Right-angle through hole type female connector with locking block for PCB
MRH-( )RFA( )+
M-65
MR series...63



Right-angle through hole type male connector with locking block for PCB
MRH-( )RMA( )+
M-66
MR series...64



Straight through hole type female connector for PCB
MRF-96FD( )+

M-67
MR series...65



Right-angle through hole type female connector for PCB
MRF-96FL( )+

M-68
MR series...66




Wire wrapping type female connector for PCB
MRF-96FDW( )

M-69
MR series...67



Right-angle through hole type male connector PCB
MRF-96ML( )+

M-70
MR series...68



Straight through hole type male connector for PCB
MRF-96MD( )+

M-71
MR series...69

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Soldering type female connector for panel
MR-( )F( )

Rectangular connector
For panel
Soldering


RoHS





● Configuration of product Part No.

MR- ( ) F ( )
① ② ③ ④


① Series name
② No. of contacts: 8, 16, 20, 25, 34, 50 or 60
③ Type of contact: Soldering, female
④ Contact plating
None: Silver plate (standard)
G : Gold plate







8, 16, 20, 25, 34 or 50-contact connector



60-contact connector

● Components

①	Insulator
②	Contact (short)
③	Contact (long)

● Dimensions

Part No.	A	B	C	D
MR-8F( )	22.4	17.4	11.9	9.4
MR-16F( )	30.2	25.2	19.7	9
MR-20F( )	32.8	27.8	22.3	
MR-25F( )	38.0	33.0	27.5	
MR-34F( )	45.8	40.8	35.3	
MR-50F( )	61.4	56.4	50.9	
MR-60F( )	59.6	52.6	46.3	

Mating connectors: MH and MHH series male connectors

Applicable case: MR-( )L+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Soldering type male connector for panel
MR-( )M( )


RoHS





● **Configuration of product Part No.**

MR- ( ) M ( )
① ② ③ ④


① Series name
② No. of contacts: 8, 16, 20, 25, 34, 50 or 60
③ Type of contact: Soldering, male
④ Contact plating
None: Silver plate (standard)
G : Gold plate







8, 16, 20, 25, 34 or 50-contact connector



60-contact connector

● **Components**

①	Insulator
②	Contact (short)
③	Contact (long)

● **Dimensions**

Part No.	A	B	C	D
MR-8M( )	22.4	17.4	11.9	10.0
MR-16M( )	30.2	25.2	19.7	9.6
MR-20M( )	32.8	27.8	22.3	
MR-25M( )	38.0	33.0	27.5	
MR-34M( )	45.8	40.8	35.3	
MR-50M( )	61.4	56.4	50.9	
MR-60M( )	59.6	52.6	46.3	

Mating connectors: MR and MRH series female connectors


Applicable case: MR-( )L+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Wire wrapping type female connector for panel
MR-( )FW( )

Rectangular connector
For panel
Wire wrapping


RoHS




● Configuration of product Part No.

MR- ( ) FW ( )
① ② ③ ④

① Series name
② No. of contacts: 8, 16, 20, 25, 34, 50 or 60
③ Type of contact: Wire wrapping, female
④ Contact plating
None: Silver plate (standard)
G : Gold plate



8, 16, 20, 25, 34 or 50-contact connector



60-contact connector

● Components

①	Insulator
②	Contact

● Dimensions

Part No.	A	B	C	D
MR-8FW( )	22.4	17.4	11.9	9.4
MR-16FW( )	30.2	25.2	19.7	9
MR-20FW( )	32.8	27.8	22.3	
MR-25FW( )	38.0	33.0	27.5	
MR-34FW( )	45.8	40.8	35.3	
MR-50FW( )	61.4	56.4	50.9	
MR-60FW( )	59.6	52.6	46.3	

Mating connectors: MH and MHH series male connectors

Applicable case: MR-( )L+, etc.

Applicable cable sizes: ø0.32-0.40 mm

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Wire wrapping type male connector for panel
MR-( )MW( )


RoHS





● **Configuration of product Part No.**

MR- ( ) MW ( )
① ② ③ ④


① Series name
② No. of contacts: 8, 16, 20, 25, 34, 50 or 60
③ Type of contact: Wire wrapping, male
④ Contact plating
None: Silver plate (standard)
G : Gold plate







8, 16, 20, 25, 34 or 50-contact connector



60-contact connector

● **Components**

①	Insulator
②	Contact

● **Dimensions**

Part No.	A	B	C	D
MR-8MW( )	22.4	17.4	11.9	10.0
MR-16MW( )	30.2	25.2	19.7	9.6
MR-20MW( )	32.8	27.8	22.3	
MR-25MW( )	38.0	33.0	27.5	
MR-34MW( )	45.8	40.8	35.3	
MR-50MW( )	61.4	56.4	50.9	
MR-60MW( )	59.6	52.6	46.3	

Mating connectors: MR and MRH series female connectors

Applicable case: MR-( )L+, etc.

Applicable cable sizes: ø0.32-0.40 mm

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type female connector for PCB
MR-( )FD2( )

Rectangular connector
For PCB
Through hole


RoHS



● Configuration of product Part No.

MR- ( ) FD2 ( )
① ② ③ ④

① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ Type of contact: Through hole, female
④ Contact plating
None: Silver plate (standard)
G : Gold plate



8-contact connector

16, 20, 25, 34 or 50-contact connector

● Components

①	Insulator
②	Spacer
③	Contact
④	Small-sized Phillips flat head screw
⑤	Hexagon nut

● Dimensions

Part No.	A	B
MR-8FD2( )	22.4	17.4
MR-16FD2( )	30.2	25.2
MR-20FD2( )	32.8	27.8
MR-25FD2( )	38.0	33.0
MR-34FD2( )	45.8	40.8
MR-50FD2( )	61.4	56.4

Mating connectors: MR and MRH series male connectors

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type male connector for PCB
MR-( )MD2( )


RoHS





● Configuration of product Part No.


MR- ( ) MD2 ( )
① ② ③ ④


① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ Type of contact: Through hole, male
④ Contact plating
None: Silver plate (standard)
G : Gold plate












8-contact connector



16, 20, 25, 34 or 50-contact connector

● Components

①	Insulator
②	Spacer
③	Contact
④	Hexagon nut
⑤	Small-sized Phillips head screw

● Dimensions

Part No.	A	B
MR-8MD2( )	22.4	17.4
MR-16MD2( )	30.2	25.2
MR-20MD2( )	32.8	27.8
MR-25MD2( )	38.0	33.0
MR-34MD2( )	45.8	40.8
MR-50MD2( )	61.4	56.4

Mating connectors: MR and MRH series female connectors

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Right-angle through hole type female connector for PCB
MR-( )FA( )

Rectangular connector
For PCB
Right-angle Through hole


RoHS




● Configuration of product Part No.


MR- ( ) FA ( )
① ② ③ ④


① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ Type of contact: Right-angle through hole, female
④ Contact plating
None: Silver plate (standard)
G : Gold plate





8, 16, 25 or 34-contact connector





20 or 50-contact connector

● Components

①	Insulator
②	Bracket
③	Spacer
④	Contact (short)
⑤	Contact (middle)
⑥	Contact (long)
⑦	Tapping screw

● Dimensions

Part No.	A	B	C	D	E
MR-8FA( )	22.4	17.4	26.6	9.4	7.6
MR-16FA( )	30.2	25.2	34.4	9	8
MR-20FA( )	32.8	27.8	37.0		
MR-25FA( )	38.0	33.0	42.2		
MR-34FA( )	45.8	40.8	50.0		
MR-50FA( )	61.4	56.4	65.6		


Mating connectors: MR and MRH series male connectors

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Right-angle through hole type male connector for PCB
MR-( )MA( )


RoHS




● Configuration of product Part No.


MR- ( ) MA ( )
① ② ③ ④


① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ Type of contact: Right-angle through hole, male
④ Contact plating
None: Silver plate (standard)
G : Gold plate





8, 16, 25 or 34-contact connector





20 or 50-contact connector

● Components

①	Insulator
②	Bracket
③	Contact (short)
④	Contact (middle)
⑤	Contact (long)
⑥	Tapping screw

● Dimensions

Part No.	A	B	C	D	E
MR-8MA( )	22.4	17.4	26.6	10.0	5.6
MR-16MA( )	30.2	25.2	34.4	9.6	6
MR-20MA( )	32.8	27.8	37.0		
MR-25MA( )	38.0	33.0	42.2		
MR-34MA( )	45.8	40.8	50.0		
MR-50MA( )	61.4	56.4	65.6		

Mating connectors: MR and MRH series female connectors

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Rectangular connector
For panel
Soldering
With locking block

Soldering type female connector with locking block for panel
MR-( )RF( )+


RoHS




● Configuration of product Part No.


MR- ( ) R F ( )+
① ② ③ ④ ⑤


① Series name
② No. of contacts: 8, 16, 20, 25, 34, 50 or 60
③ With locking block
④ Type of contact: Soldering, female
⑤ Contact plating
None: Silver plate
G : Gold plate





8, 16, 20, 25, 34 or 50-contact connector





60-contact connector

● Components

①	Insulator
②	Contact (short)
③	Contact (long)
④	Locking block (Appended)
⑤	Spring washers (Appended)
⑥	Small-sized Phillips head screws (Appended)

● Dimensions

Part No.	A	B	C	D
MR-8RF( )+	22.4	17.4	11.9	9.4
MR-16RF( )+	30.2	25.2	19.7	9.0
MR-20RF( )+	32.8	27.8	22.3	
MR-25RF( )+	38.0	33.0	27.5	
MR-34RF( )+	45.8	40.8	35.3	
MR-50RF( )+	61.4	56.4	50.9	
MR-60R2F( )+	59.6	52.6	46.3	

Mating case: MR-( )L+, MR-( )LW+

Mating connectors with case: MR-( )LM( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Soldering type male connector with locking block for panel
MR-( )RM( )+

RoHS


Rectangular connector
For panel
Soldering
With locking block




● **Configuration of product Part No.**

MR- ( ) R M ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 8, 16, 20, 25, 34, 50 or 60
③ With locking block
④ Type of contact: Soldering, male
⑤ Contact plating
None: Silver plate
G : Gold plate



8, 16, 20, 25, 34 or 50-contact connector



60-contact connector

● **Components**

①	Insulator
②	Contact (short)
③	Contact (long)
④	Locking block (Appended)
⑤	Spring washers (Appended)
⑥	Small-sized Phillips head screws (Appended)

● **Dimensions**

Part No.	A	B	C	D
MR-8RM( )+	22.4	17.4	11.9	10.0
MR-16RM( )+	30.2	25.2	19.7	9.6
MR-20RM( )+	32.8	27.8	22.3	
MR-25RM( )+	38.0	33.0	27.5	
MR-34RM( )+	45.8	40.8	35.3	
MR-50RM( )+	61.4	56.4	50.9	
MR-60R2M( )+	59.6	52.6	46.3	

Mating case: MR-( )L+, MR-( )LW+

Mating connectors with case: MR-( )LF( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Wire wrapping type female connector with locking block for panel
MR-( )RFW( )+

RoHS


Rectangular connector
For panel
Wire wrapping
With locking block





● **Configuration of product Part No.**

MR- ( ) R FW ( )+
① ② ③ ④ ⑤


① Series name
② No. of contacts: 8, 16, 20, 25, 34, 50 or 60
③ With locking block
④ Type of contact: Wire wrapping, female
⑤ Contact plating
None: Silver plate (standard)
G : Gold plate







8, 16, 20, 25, 34 or 50-contact connector



60-contact connector

● **Components**

①	Insulator
②	Contact
③	Locking block (Appended)
④	Spring washers (Appended)
⑤	Small-sized Phillips head screws (Appended)

● **Dimensions**

Part No.	A	B	C	D
MR-8RFW( )+	22.4	17.4	11.9	9.4
MR-16RFW( )+	30.2	25.2	19.7	9.0
MR-20RFW( )+	32.8	27.8	22.3	
MR-25RFW( )+	38.0	33.0	27.5	
MR-34RFW( )+	45.8	40.8	35.3	
MR-50RFW( )+	61.4	56.4	50.9	
MR-60R2FW( )+	59.6	52.6	46.3	

Mating case: MR-( )L+, MR-( )LW+

Mating connectors with case: MR-( )LM( )+, etc.

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Wire wrapping type male connector with locking block for panel
MR-( )RMW( )+

RoHS


Rectangular connector
For panel
Wire wrapping
With locking block




● **Configuration of product Part No.**

MR- ( ) R MW ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 8, 16, 20, 25, 34, 50 or 60
③ Type locking block
④ Form of contact: Wire wrapping, male
⑤ Contact plating
None: Silver plate
G : Gold plate



8, 16, 20, 25, 34 or 50-contact connector



60-contact connector

● **Components**

①	Insulator
②	Contact
③	Locking block (Appended)
④	Spring washers (Appended)
⑤	Small-sized Phillips head screws (Appended)

● **Dimensions**

Part No.	A	B	C	D
MR-8RMW( )+	22.4	17.4	11.9	10.0
MR-16RMW( )+	30.2	25.2	19.7	9.6
MR-20RMW( )+	32.8	27.8	22.3	
MR-25RMW( )+	38.0	33.0	27.5	
MR-34RMW( )+	45.8	40.8	35.3	
MR-50RMW( )+	61.4	56.4	50.9	
MR-60R2MW( )+	59.6	52.6	46.3	

Mating case: MR-( )L+, MR-( )LW+

Mating connectors with case: MR-( )LF( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Rectangular connector
For PCB
Through hole
With locking block

Straight through hole type female connector with locking block for PCB
MR-( )RFD2( )+


RoHS




● Configuration of product Part No.

MR- ( ) R FD2 ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ With locking block
④ Type of contact: Through hole, male
⑤ Contact plating
None: Silver plate (standard)
G : Gold plate



8-contact connector



16, 20, 25, 34 or 50-contact connector

● Components

①	Insulator
②	Spacer
③	Contact
④	Locking block (Appended)
⑤	Small-sized Phillips head screws (Appended)

● Dimensions

Part No.	A	B
MR-8RFD2( )+	22.4	17.4
MR-16RFD2( )+	30.2	25.2
MR-20RFD2( )+	32.8	27.8
MR-25RFD2( )+	38.0	33.0
MR-34RFD2( )+	45.8	40.8
MR-50RFD2( )+	61.4	56.4

Mating case: MR-( )L+, MR-( )LW+

Mating connectors with case: MR-( )LM( )+, etc.

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type male connector with locking block for PCB
MR-( )RMD2( )+

RoHS


Rectangular connector
For PCB
Through hole
With locking block




● Configuration of product Part No.

MR- ( ) R MD2 ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ With locking block
④ Type of contact: Through hole, male
⑤ Contact plating
None: Silver plate (standard)
G : Gold plate



8-contact connector



16, 20, 25, 34 or 50-contact connector

● Components

①	Insulator
②	Spacer
③	Contact
④	Locking block (Appended)
⑤	Small-sized Phillips head screws (Appended)

● Dimensions

Part No.	A	B
MR-8RMD2( )+	22.4	17.4
MR-16RMD2( )+	30.2	25.2
MR-20RMD2( )+	32.8	27.8
MR-25RMD2( )+	38.0	33.0
MR-34RMD2( )+	45.8	40.8
MR-50RMD2( )+	61.4	56.4

Mating case: MR-( )L+, MR-( )LW+

Mating connectors with case: MR-( )LF( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

HONDA TSUSHIN KOGYO CO., LTD.

Right-angle through hole type female connector with locking block for PCB
MR-( )RFA( )+

RoHS


Rectangular connector
For PCB
Right-angle Through hole
With locking block




● **Configuration of product Part No.**


MR- ( ) R FA ( )+
① ② ③ ④ ⑤


① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ With locking block
④ Type of contact: Right-angle through hole, female
⑤ Contact plating
None: Silver plate (standard)
G : Gold plate





8, 16, 25 or 34-contact connector





20 or 50-contact connector

● **Components**

①	Insulator
②	Bracket
③	Spacer
④	Contact (short)
⑤	Contact (middle)
⑥	Contact (long)
⑦	Locking block
⑧	Small-sized Phillips flat head screw

● **Dimensions**

Part No.	A	B	C	D	E
MR-8RFA( )+	22.4	17.4	26.6	9.4	7.6
MR-16RFA( )+	30.2	25.2	34.4	9	8
MR-20RFA( )+	32.8	27.8	37.0		
MR-25RFA( )+	38.0	33.0	42.2		
MR-34RFA( )+	45.8	40.8	50.0		
MR-50RFA( )+	61.4	56.4	65.6		

Mating case: MR-( )L+, MR-( )LW+

Mating connectors with case: MR-( )LM( )+, etc.

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Rectangular connector
For PCB
Right-angle Through hole
With locking block

Right-angle through hole type male connector with locking block for PCB
MR-( )RMA( )+


RoHS




● Configuration of product Part No.


MR- ( ) R MA ( )+
① ② ③ ④ ⑤


① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ With locking block
④ Type of contact: Right-angle through hole, male
⑤ Contact plating
None: Silver plate (standard)
G : Gold plate





8, 16, 25 or 34-contact connector





20 or 50-contact connector

● Components

①	Insulator
②	Bracket
③	Contact (short)
④	Contact (middle)
⑤	Contact (long)
⑥	Locking block
⑦	Small-sized Phillips flat head screw

● Dimensions

Part No.	A	B	C	D	E
MR-8RMA( )+	22.4	17.4	26.6	10.0	5.6
MR-16RMA( )+	30.2	25.2	34.4	9.6	6
MR-20RMA( )+	32.8	27.8	37.0		
MR-25RMA( )+	38.0	33.0	42.2		
MR-34RMA( )+	45.8	40.8	50.0		
MR-50RMA( )+	61.4	56.4	65.6		

Mating case: MR-( )L+, MR-( )LW+

Mating connectors with case: MR-( )LF( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Soldering type female connector with brace for panel
MR-( )SRF( )+

Rectangular connector
For panel
Soldering
With brace


RoHS



● Configuration of product Part No.

MR- ( ) SR F ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With brace
④ Type of contact: Soldering, female
⑤ Contact plating
None: Silver plate
G : Gold plate



● Components

①	Insulator
②	Contact (short)
③	Contact (long)
④	Brace (Appended)
⑤	Small-sized Phillips head screws (Appended)
⑥	Hexagon nuts (Appended)

● Dimensions

Part No.	A	B
MR-16SRF ( )+	33.0	25.2
MR-20SRF ( )+		27.8
MR-25SRF ( )+	40.0	33.0
MR-34SRF ( )+	45.0	40.8
MR-50SRF ( )+	67.0	56.4

Mating case: MR-( )NS+

Mating connectors with case: MR-( )NSM( )+, etc.

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Soldering type male connector with brace for panel
MR-( )SRM( )+

RoHS


Rectangular connector
For panel
Soldering
With brace



● **Configuration of product Part No.**

MR- ( ) SR M ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With brace
④ Type of contact: Soldering, male
⑤ Contact plating
None: Silver plate
G : Gold plate



● **Components**

①	Insulator
②	Contact (short)
③	Contact (long)
④	Brace (Appended)
⑤	Small-sized Phillips head screws (Appended)
⑥	Hexagon nuts (Appended)

● **Dimensions**

Part No.	A	B
MR-16SRM( )+	33.0	25.2
MR-20SRM( )+		27.8
MR-25SRM( )+	40.0	33.0
MR-34SRM( )+	45.0	40.8
MR-50SRM( )+	67.0	56.4

Mating case: MR-( )NS+

Mating connectors with case: MR-( )NSF( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Wire wrapping type female connector with brace for panel
MR-( )SRFW( )+

RoHS


Rectangular connector
For panel
Wire wrapping
With brace



● **Configuration of product Part No.**

MR- ( ) SR FW ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With brace
④ Type of contact: Wire wrapping, female
⑤ Contact plating
None: Silver plate
G : Gold plate



● **Components**

①	Insulator
②	Contact
③	Brace (Appended)
④	Small-sized Phillips head screws (Appended)
⑤	Hexagon nuts (Appended)

● **Dimensions**

Part No.	A	B
MR-16SRFW( )+	33.0	25.2
MR-20SRFW( )+		27.8
MR-25SRFW( )+	40.0	33.0
MR-34SRFW( )+	45.0	40.8
MR-50SRFW( )+	67.0	56.4

Mating case: MR-( )NS+

Mating connectors with case: MR-( )NSM( )+, etc.

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Wire wrapping type male connector with brace for panel
MR-( )SRMW( )+

RoHS


Rectangular connector
For panel
Wire wrapping
With brace



● Configuration of product Part No.

MR- ( ) SR MW ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With brace
④ Type of contact: Wire wrapping, male
⑤ Contact plating
None: Silver plate
G : Gold plate



● Components

①	Insulator
②	Contact
③	Brace (Appended)
④	Small-sized Phillips head screw (Appended)
⑤	Hexagon nut (Appended)

● Dimensions

Part No.	A	B
MR-16SRMW( )+	33.0	25.2
MR-20SRMW( )+		27.8
MR-25SRMW( )+	40.0	33.0
MR-34SRMW( )+	45.0	40.8
MR-50SRMW( )+	67.0	56.4

Mating case: MR-( )NS+

Mating connectors with case: MR-( )NSF( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type female connector with brace for PCB
MR-( )SRFD2( )+

RoHS


Rectangular connector
For PCB
Straight Through hole
With brace





● **Configuration of product Part No.**

MR- ( ) SR FD2 ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With brace for skew type case
④ Type of contact: Straight through hole, female
⑤ Contact plating
None: Silver plate
G : Gold plate







● **Components**

①	Insulator
②	Contact
③	Brace
④	Small-sized Phillips head screw
⑤	Hexagon nut

● **Dimensions**

Part No.	A	B
MR-16SRFD2( )+	33.0	25.2
MR-20SRFD2( )+		27.8
MR-25SRFD2( )+	40.0	33.0
MR-34SRFD2N( )+	45.0	40.8
MR-50SRFD2( )+	67.0	56.4

Mating case: MR-( )NSA+

Mating connectors with case: MR-( )NS2M( )+, etc.

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type male connector with brace for PCB
MR-( )SRMD2( )+

RoHS


Rectangular connector
For PCB
Straight Through hole
With brace





● **Configuration of product Part No.**

MR- ( ) SR MD2 ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With brace for skew type case
④ Type of contact: Straight through hole, male
⑤ Contact plating
None: Silver plate
G : Gold plate







● **Components**

①	Insulator
②	Contact
③	Brace
④	Small-sized Phillips head screw
⑤	Hexagon nut

● **Dimensions**

Part No.	A	B
MR-16SRMD2( )+	33.0	25.2
MR-20SRMD2( )+		27.8
MR-25SRMD2( )+	40.0	33.0
MR-34SRMD2N( )+	45.0	40.8
MR-50SRMD2( )+	67.0	56.4

Mating case: MR-( )NS+

Mating connectors with case: MR-( )NS2F( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

HONDA TSUSHIN KOGYO CO., LTD.

Right-angle through hole type female connector with brace for PCB
MR-( )SRFA( )+

RoHS


Rectangular connector
For PCB
Right-angle Through hole
With brace




● **Configuration of product Part No.**


MR- ( ) SR FA ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With brace for skew type case
④ Type of contact: Right-angle through hole, female
⑤ Contact plating
None: Silver plate
G : Gold plate





16, 25 or 34-contact connector



20 or 50-contact connector

● **Components**

①	Insulator
②	Bracket
③	Spacer
④	Contact (short)
⑤	Contact (middle)
⑥	Contact (long)
⑦	Brace
⑧	Tapping screw

* 25 contacts are rivets.

● **Dimensions**

Part No.	A	B	C
MR-16SRFA( )+	33.0	25.2	34.4
MR-20SRFA( )+		27.8	37.0
MR-25SRFA( )+	40.0	33.0	42.2
MR-34SRFAN( )+	45.0	40.8	50.0
MR-50SRFA( )+	67.0	56.4	65.6

Mating case: MR-( )NSA+

Mating connectors with case: MR-( )NS2M( )+, etc.

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Rectangular connector
For PCB
Right-angle Through hole
With brace

Right-angle through hole type male connector with brace for PCB
MR-( )SRMA( )+


RoHS




● Configuration of product Part No.


MR- ( ) SR MA ( )+
① ② ③ ④ ⑤

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With brace for skew type case
④ Type of contact: Right-angle through hole, male
⑤ Contact plating
None: Silver plate
G : Gold plate





16, 25 or 34-contact connector



20 or 50-contact connector

● Components

①	Insulator
②	Bracket
③	Contact (short)
④	Contact (middle)
⑤	Contact (long)
⑥	Brace
⑦	Tapping screw
⑧	Spring washer

● Dimensions

Part No.	A	B	C
MR-16SRMA( )+	33.0	25.2	34.4
MR-20SRMA( )+		27.8	37.0
MR-25SRMA( )+	40.0	33.0	42.2
MR-34SRMAN( )+	45.0	40.8	50.0
MR-50SRMA( )+	67.0	56.4	65.6

Mating case: MR-( )NS+

Mating connectors with case: MR-( )NS2F( )+, etc.

Others | Wire wrapping | Crimping | Soldering | IDC | Press-in | SMT | Through hole

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Vertical type plastic case
MR-( )L+

RoHS


Rectangular connector
Case
Vertical type
Dual spring and screw locking





● **Configuration of product Part No.**

MR- ( ) L+
① ② ③

① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ Type of case: Vertical








Note: Capable of dual spring and screw locking

For MR-(16~50)L+



For MR-8L+

● **Components**

①	Case body
②	Locking screw
③	Spring lock
④	Cable clamp
⑤	Small-sized Phillips head screw
⑥	Hexagon nut

● **Dimensions**

Part No.	A	B	C	øD	E (Reference)
MR-8L+	31.0	19	39.8	11	36.6
MR-16L+	36.7	18		9	42.3
MR-20L+	39.3		40.5	11	44.9
MR-25L+	44.5		44.8	13.5	50.1
MR-34L+	52.3			15	57.9
MR-50L+	67.9			16	73.5

Applicable connectors: Female : MR-( )F( ), MR-( )FW( ), MRP-( )F01
Male : MR-( )M( ), MR-( )MW( ), MRP-( )M01

Mating connectors: Female : MR-( )RF( )+, MR-( )RFW( )+, MR-( )RFD2( )+, MR-( )RFA( )+, etc.
Male : MR-( )RM( )+, MR-( )RMW( )+, MR-( )RMD2( )+, MR-( )RMA( )+, etc.

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Vertical type plastic case for junction
MR-( )LK2+


RoHS





● Configuration of product Part No.

MR- ( ) LK2+
① ② ③


① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ Type of case: For junction







For MR-(16□50)LK2+



For MR-□LK2+

Note□For □, 25 or 34-contact connector, the Part No. of MR-( )L is marked on the case instead of MR-( )LK.

● Components

①	Case body
②	Cable clamp
③	Small-sized Phillips head screw
④	Hexagon nut

● Dimensions

Part No.	A	B	C	øD
MR-8LK2+	31	19	36.1	11
MR-16LK2+	36.7	18	35.8	9
MR-20LK2+	39.3			11
MR-25LK2+	44.5		36.5	13.5
MR-34LK2+	52.3			15
MR-50LK2+	67.9		40.8	16

Applicable connectors□Female: MR-( )RF( )+, MR-( )RFW( )+, MRP-( )RF01+
Male : MR-( )RM( )+, MR-( )RMW( )+, MRP-( )RM01+

Mating connectors with case□Female: MR-( )LF( )+, MR-( )LFW( )+, etc.
Male : MR-( )LM( )+, MR-( )LMW( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Rectangular connector
Case
Dual-purpose vertical and horizontal type
Spring lock

Dual-purpose vertical and horizontal type plastic case MR-( )LW+


RoHS



● Configuration of product Part No.

MR- ( ) LW+
① ② ③

① Series name
② No. of contacts: 8, 16, 20, 25, 34, 50 or 60
③ Type of case: Dual-purpose vertical and horizontal type



Note 1 Plate spring for latching is not provided for the MR- LW+ products.

● Components

①	Case body
②	Spring lock
③	Cable clamp
④	Cap
⑤	Small-sized Phillips head screw
⑥	Hexagon nut

Note 2 In the MR- LW+ plastic case, the male or female connectors with mounting hardware, such as MR- RM( ) or MR- RF( ), which have an "R" sign at the head of the M or F in the Product Part No., may not be used.

● Dimensions

Part No.	A	B	C	D	E
MR-8LW+	25.6	17	38.0	6.0	—
MR-16LW+	36.7		47.0	9.0	(42.3)
MR-20LW+	39.3	18		11.0	(44.9)
MR-25LW+	44.5	19	56.0	13.5	(50.1)
MR-34LW+	52.3		58.3	15.0	(57.9)
MR-50LW+	67.9	20	66.1	16.0	(73.5)
MR-60LW+	66.9	22	68.0	18.0	(71.7)

Applicable connectors Female : MR-(8~60)F( ), MR-(8~60)FW( ), MRP-( )F01
Male : MR-(8~60)M( ), MR-(8~60)MW( ), MRP-( )M01

Mating connectors Female : MH-8F( ), MH-8FW( ), MH-8FD2( )
MR-(16~60)RF( )+, MR-(16~60)RFW( )+, MR-(16~50)RFD2( )+, MR-(16~50)RFA( )+
Male : MR-8M( ), MR-8MW( ), MR-8MD2( )
MH-(16~60)RM( )+, MH-(16~60)RMW( )+, MR-(16~50)RMD2( )+, MH-(16~50)RMA( )+

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Skew type plastic case
MR-( )NS+


RoHS




● Configuration of product Part No.


MR- ( ) NS+
① ② ③


① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ Type of case: Skew type (with push button lock)






Cable hole dimensions







Mounting block (included with the product)

● Components

①	Cable clamp A
②	Cable clamp B
③	Case A
④	Case B
⑤	Push button
⑥	Clear board
⑦	Small-sized Phillips head screw
⑧	Hexagon nut

● Dimensions

Part No.	A	B	C	D
MR-16NS+	37	39	59	11
MR-20NS+				
MR-25NS+	44	46	62	13
MR-34NS+	49	51	64	16
MR-50NS+	71	73	76	24

Applicable connectors Female : MR-( )F, MR-( )FW( )
Male : MR-( )M( ), MR-( )MW( )

Mating connectors (panel mounted type) Female : MR-( )SRF( )+, MR-( )SRFW( )+
Male : MR-( )SHM( )+, MR-( )SHMW( )+

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Skew type plastic case
MR-( )NSA+

RoHS


Rectangular connector
Case
Skew type
Push button lock for PCB mounted connector



● Configuration of product Part No.


MR- ( ) NSA+
① ② ③

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ Type of case: Skew type (with puch button lock)




Note: The Part No. of MR-( )NS is marked on the housing instead of MR-( )NSA.

Cable hole dimensions







Mounting block (included with the product)

● Components

①	Cable clamp A
②	Cable clamp B
③	Case A
④	Case B
⑤	Push button
⑥	Clear board
⑦	Small-sized Phillips head screw
⑧	Hexagon nut

● Dimensions

Part No.	A	B	C	D
MR-16NSA+	37	39	59	11
MR-20NSA+				
MR-25NSA+	44	46	62	13
MR-34NSA+	49	51	64	16
MR-50NSA+	71	73	76	24

Applicable connectors: Female : MR-( )F( ), MR-( )FW( )
Male : MR-( )M( ), MR-( )MW( )

Mating connectors (PCB mounted type): Female : MR-( )SRFD2( )+, MR-( )SRFA( )+
Male : MR-( )SRMD2( )+, MR-( )SRFA( )+

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Skew type plastic case
MR-( )NSB+


RoHS





● Configuration of product Part No.

MR- ( ) NSB+
① ② ③

① Series name
② No. of contacts: 20 or 50
③ Type of case: Skew type







● Components

①	Case A
②	Case B
③	Spring lock
④	Cable clamp

● Dimensions

Part No.	A	B	C	D	E	F
MR-20NSB+	42.3	46	47	11	17	28.2
MR-50NSB+	71.3	75	61	16		27


Applicable connectors Female: MR-( )F( ), MR-( )FW( ), MRP-( )F01
Male : MR-( )M( ), MR-( )MW( ), MRP-( )M01

Mating connectors Female: MR-( )RF( )+, MR-( )RFW( )+, MR-( )RFD2( )+, MR-( )RFA( )+, etc.
Male : MR-( )RM( )+, MR-( )RMW( )+, MR-( )RMD2( )+, MR-( )RMA( )+, etc.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Locking block kit
MR-R( )+


RoHS



● Configuration of product Part No.

MR- R ( )+
① ② ③

① Series name
② Locking block
③ For use with connector
4: 8, 16, 20, 34 or 50 contacts
6: 60 contacts



MR-R4+

Note 1 Included in this kit are, locking block (MR-R+), a small-sized Phillips head screw and a spring washer.

MR-R6+

Note 2 Included in this kit are, locking block (MR-R2+), a small-sized Phillips head screw and a spring washer.

Note 3 This kit cannot be used for right-angle type connectors. Two kits are required for one connector.

● Components

①	Locking block
②	Spring washers (Appended)
③	Small-sized Phillips head screws (Appended)


Applicable connectors MR-( )F( ), MR-( )M( ), MR-( )FW, MR-( )MW, MR-( )FD2( ), MR-( )MD2( )

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Brace kit
MR-( )SR+


RoHS




● Configuration of product Part No.

MR- ( ) SR+
① ② ③

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ Brace for panel mounted connector





t=1.2

● Components

①	Brace
②	Hexagon nuts (Appended)
③	Small-sized Phillips head screws (Appended)
④	Toothed lock washers (Appended)

Note □Included in this kit are brace, two small-sized Phillips head screws, two hexagon nuts, and two toothed lock washers.

● Dimensions

Part No.	A	B	C	D
MR-16SR+	20.0	25.2	33.0	31.0
MR-20SR+	22.6	27.8		
MR-25SR+	27.8	33.0	40.0	36.0
MR-34SR+	35.6	40.8	45.0	41.0
MR-50SR+	51.2	56.4	67.0	63.0

Applicable connectors MR-( )F( ), MR-( )M( ), MR-( )FW, MR-( )MW

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Brace kit
MR-( )SRA( )+


RoHS




● Configuration of product Part No.

MR- ( ) SRA ( )+
① ② ③ ④

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ Brace for through hole type connector
④ For use with connector
None: 16 or 20 contacts
N : 25, 34 or 50 contacts





t=1.2

● Components

①	Brace
②	Hexagon nuts (Appended)
③	Small-sized Phillips head screws (Appended)

Note 1 This kit cannot be used for right-angle type connectors.
Note 2 Included in this kit are brace, two small-sized Phillips head screws and two hexagon nuts.

● Dimensions

Part No.	A	B	C	D
MR-16SRA+	24.6	25.2	33.0	31.0
MR-20SRA+	27.2	27.8		
MR-25SRAN+	32.4	33.0	40.0	36.0
MR-34SRAN+	40.2	40.8	45.0	41.0
MR-50SRAN+	55.8	56.4	67.0	63.0

Applicable connectors MR-( )FD2( ), MR-( )MD2( )

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Dust cover for female connector
MR-( )CF


RoHS



● Configuration of product Part No.


MR- ( ) CF
① ② ③


① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ Dust cover for female connector






For the MR-34 and MR-50CF dust covers, six protrusions are provided on the edge of the cover instead of four as shown above.







● Dimensions

Part No.	A	B
MR-16CF	19.6	18.0
MR-20CF	22.2	20.6
MR-25CF	27.4	25.8
MR-34CF	35.2	33.6
MR-50CF	50.8	49.2

Applicable connectors MR and MRH series female connectors

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Key for preventing misinsertion
MR-PK


RoHS



● Configuration of product Part No.

MR- PK
① ②

① Series name
② Key for preventing misinsertion



□How to use
In the state where contact was included in the insulator, this article is inserted from the mating side of a female contact. The female contact with the polarizing key once inserted can not be used.

Applicable connectors MH and MHH series female connectors

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Tool for extracting male contact
MR-K1


RoHS



● Configuration of product Part No.


MR- K1
① ②

① Series name
② Tool for extracting male contact



How to use

1. The male contact insertion hole of this tool is inserted in a male contact from a mating side.
2. Rotate the handle while pushing the tool to the bottom of insulator and twist the male contact cut.
3. Remove twisted male contact tip part from the tool.




Applicable connectors MR and MRH series male connectors

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Crimping type female insulator for panel
MRP-( )F01


RoHS



● Configuration of product Part No.

MRP- ( ) F01
① ② ③

① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ Female insulator



● Dimensions

Part No.	A	B	C	D	E	F	G
MRP-8F01	22.4	17.4	5	11.9	1.9	3.4	—
MRP-16F01	30.2	25.2		19.7			
MRP-20F01	32.8	27.8		22.3			21.3
MRP-25F01	38.0	33.0	10	27.5	2.4	3	
MRP-34F01	45.8	40.8		35.3			—
MRP-50F01	61.4	56.4		50.9			

● Components

①	Insulator

Applicable contacts MRP-F1( )( )

Applicable case MR-( )L+, MR-( )LW+

Mating connectors MR and MRH series male connectors

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Crimping type male insulator for panel
MRP-( )M01


RoHS



● Configuration of product Part No.

MRP- ( ) M01
① ② ③

① Series name
② No. of contacts: 8, 16, 20, 25, 34 or 50
③ Male insulator



● Dimensions

Part No.	A	B	C	D	E	F	G
MRP-8M01	22.4	17.4	5	11.9	2.8	3.4	—
MRP-16M01	30.2	25.2		19.7			
MRP-20M01	32.8	27.8		22.3			21.3
MRP-25M01	38.0	33.0	10	27.5	2.4	3	
MRP-34M01	45.8	40.8		35.3			—
MRP-50M01	61.4	56.4		50.9			

● Components

①	Insulator

Applicable contacts MRP-M1( )( )

Applicable case MR-( )L+, MR-( )LW+

Mating connectors MR and MRH series female connectors

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Rectangular connector
For panel
Crimping
With locking block

Crimping type female insulator with locking block for panel
MRP-( )RF01+


RoHS



● Configuration of product Part No.

MRP- ( ) R F01+
① ② ③ ④

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With locking block
④ Female insulator



● Components

①	Female insulator
②	Locking block (Appended)
③	Spring washer (Appended)
④	Small-sized Phillips head screw (Appended)

● Dimensions

Part No.	A	B	C	D	E
MRP-16RF01+	32.4	30.2	25.2	—	19.7
MRP-20RF01+	35.0	32.8	27.8	21.3	22.3
MRP-25RF01+	40.2	38	33	—	27.5
MRP-34RF01+	48.0	45.8	40.8		35.3
MRP-50RF01+	63.6	61.4	56.4		50.9

Applicable contacts MRP-F1( )( )

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Crimping type male insulator with locking block for panel MRP-( )RM01+

RoHS


Rectangular connector
For panel
Crimping
With locking block



● Configuration of product Part No.

MRP- ( ) R M01+
① ② ③ ④

① Series name
② No. of contacts: 16, 20, 25, 34 or 50
③ With locking block
④ Male insulator



● Components

①	Male insulator
②	Locking block (Appended)
③	Spring washer (Appended)
④	Small-sized Phillips head screw (Appended)

● Dimensions

Part No.	A	B	C	D	E
MRP-16RM01+	32.4	30.2	25.2	–	19.7
MRP-20RM01+	35.0	32.8	27.8	21.3	22.3
MRP-25RM01+	40.2	38	33	–	27.5
MRP-34RM01+	48.0	45.8	40.8		35.3
MRP-50RM01+	63.6	61.4	56.4		50.9

Applicable contacts MRP-M1( )( )

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Crimping type female contact
MRP-F1( )( )


RoHS



● Configuration of product Part No.

MRP- F1 ( ) ( )
① ② ③ ④

① Series name
② Female contact
③ Type of contact
0: Strip form terminal (1 reel: 10,000 contacts)
1: Loose piece terminal
④ Contact plating
2: Silver plate
3: Gold plate



● Components

①	Contact

Applicable insulators MRP-( )F01

For use with cable AWG#24~28 (Outside diameter: ø1.2-ø1.5mm)

Automatic crimping machine Press body: HTK-211, Applicator: KP-202

Manual crimping tool KP-308 (Refer to page Tool-7)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Crimping type male contact
MRP-M1( )( )


RoHS




● Configuration of product Part No.

MRP- M1 ( ) ( )
① ② ③ ④

① Series name
② Male contacts
③ Type of contact
0: Strip form terminal (1 reel: 10,000 contacts)
1: Loose piece terminal
④ Contact plating
2: Silver plate
3: Gold plate





● Components

①	Contact

Applicable insulators MRP-( )M01

For use with cable AWG#24~28 (Outside diameter: ø1.2-ø1.5mm)

Automatic crimping machine Press body: HTK-211, Applicator: KP-202

Manual crimping tool KP-308 (Refer to page Tool-7)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Crimping type contact extraction tool
MRP-MF+


RoHS



● Configuration of product Part No.

MRP- MF+
① ②

① Series name
② Contact extraction tool



● Components

①	Body B
②	Body A
③	Spacer
④	Pushing pin

Applicable connectors MHP series crimping type connectors

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type female connector for PCB
MRH-( )FD+


Rectangular connector
For PCB
Straight Through hole
RoHS



Configuration of product Part No.

MRH-( ) FD+

- Series name
- No. of contacts: 20 or 50
- Type of contact: Straight through hole, female



MRH-20FD+

MRH-50FD+

Components

	Insulator A
	Insulator B
	Contact
	Locking piece

Note: These connectors are compatible with the MR series of connectors.

Mating connectors: MRH-( )MD+, MRH-( )MA+


Others | Wire wrapping | Crimping | Soldering | IDC | Press-in | SMT | Through hole

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type male connector for PCB
MRH-( )MD+

Rectangular connector
For PCB
Straight Through hole


RoHS





Configuration of product Part No.


MRH-( ) MD+


1. Series name
2. No. of contacts: 20 or 50
3. Type of contact: Straight through hole, male












MRH-20MD+



MRH-50MD+

Components

1	Insulator
2	Contact
3	Locking piece

Note: These connectors are compatible with the MR series of connectors.

Mating connectors: MRH-( )FD+, MRH-( )FA+

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Right-angle through hole type female connector for PCB
MRH-( )FA+


RoHS



l Configuration of product Part No.

MRH-( ) FA+

□ Series name
□ No. of contacts: 20 or 50
□ Type of contact: Right-angle through hole, female



l Components

□	Insulator A
□	Insulator B
□	Bracket
□	Contact (short)
□	Contact (middle)
□	Contact (long)
□	Locking piece
□	Tapping screw

Note: These connectors are compatible with the MR series of connectors.

Mating connectors: MRH-( )MD+, MRH-( )MA+

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Right-angle through hole type male connector for PCB
MRH-( )MA+

Rectangular connector
For PCB
Right-angle Through hole


RoHS



I Configuration of product Part No.

MRH-( ) MA+

□ Series name
□ No. of contacts: 20 or 50
□ Type of contact: Right-angle through hole, male



MRH-20MA+

MRH-50MA+

I Components

□	Insulator
□	Bracket
□	Contact (short)
□	Contact (middle)
□	Contact (long)
□	Locking piece
□	Tapping screw

Note: These connectors are compatible with the MR series of connectors.

Mating connectors with case: MRH-( )FD+, MRH-( )FA+

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type female connector with locking block for PCB
MRH-( )RFD+

RoHS


Rectangular connector
For PCB
Straight Through hole
With locking block





Configuration of product Part No.


MRH-( ) R FD+


1. Series name
2. No. of contacts: 20 or 50
3. Locking block
4. Type of contact: Straight through hole, female















MRH-20RFD+



MRH-50RFD+

Components

1	Insulator A
2	Insulator B
3	Contact
4	Locking piece
5	Locking block
6	Small-sized Phillips head screw

Note: These connectors are compatible with the MR series of connectors.

Mating connectors with case: MR-( )LM+, MR-( )LMW+, MRP-( )M01-( )L+


Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

HONDA TSUSHIN KOGYO CO., LTD.

Straight through hole type male connector with locking block for PCB
MRH-( )RMD+

RoHS


Rectangular connector
For PCB
Straight Through hole
With locking block





l Configuration of product Part No.


MRH-( ) R MD+


□ Series name
□ No. of contacts: 20 or 50
□ Locking block
□ Type of contact: Straight through hole, male












MRH-20RMD+



MRH-50RMD+

l Components

□	Insulator
□	Contact
□	Locking piece
□	Locking block
□	Small-sized Phillips head screw

Note: These connectors are compatible with the MR series of connectors.

Mating connectors with case: MR-( )LF+, MR-( )LFW+, MRP-( )F01-( )L+

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Right-angle through hole type female connector with locking block for PCB
MRH-( )RFA+

RoHS


Rectangular connector
For PCB
Right-angle Through hole
With locking block



I Configuration of product Part No.

MRH- ( ) R FA+

1. Series name
2. No. of contacts: 20 or 50
3. Locking block
4. Type of contact: Right-angle through hole, female



I Components

	Insulator A
	Insulator B
	Bracket
	Contact (short)
	Contact (middle)
	Contact (long)
	Locking piece
	Locking block
	Small-sized Phillips head screw

Note: These connectors are compatible with the MR series of connectors.

Mating connectors with case: MR-( )LM+, MR-( )LMW+, MRP-( )M01-( )L+

Others | Wire wrapping | Crimping | Soldering | IDC | Press-in | SMT | Through hole

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Rectangular connector
For PCB
Right-angle Through hole
With locking block

Right-angle through hole type male connector with locking block for PCB
MRH-( )RMA+


RoHS





Configuration of product Part No.


MRH-( ) R MA+


- Series name
- No. of contacts: 20 or 50
- Locking block
- Type of contact: Right-angle through hole, male












MRH-20RMA+



MRH-50RMA+

Components

1	Insulator
2	Bracket
3	Contact (short)
4	Contact (middle)
5	Contact (long)
6	Locking piece
7	Locking block
8	Small-sized Phillips head screw

Note: These connectors are compatible with the MR series of connectors.


Mating connectors with case: MR-( )LF+, MR-( )LFW+, MRP-( )F01-( )L+

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type female connector for PCB
MRF-96FD( )+


RoHS





● Configuration of product Part No.

MRF- 96 FD ( )+
① ② ③ ④

① Series name
② No. of contacts 6
③ Type of contact Straight through hole, female
④ Contact plating
None Silver plate
G Gold plate







● Components

①	Insulator
②	Contact
③	Locking piece

Mating connectors: MRF-□6MD( )+, MRF-□6ML( )+


Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

HONDA TSUSHIN KOGYO CO., LTD.

Right-angle through hole type female connector for PCB
MRF-96FL( )+

RoHS


Rectangular connector
For PCB
Right-angle through hole





● Configuration of product Part No.

MRF- 96 FL ( )+
① ② ③ ④

① Series name
② No. of contacts 96
③ Type of contact Right-angle through hole, female
④ Contact plating
None Silver plate
G Gold plate







● Components

①	Insulator
②	Contact (short)
③	Contact (middle)
④	Contact (longer)
⑤	Locking piece


Mating connectors: MRF-□6MD( )+, MRF-□6ML( )+

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Wire wrapping type female connector for PCB
MRF-96FDW( )


RoHS





● Configuration of product Part No.

MRF- 96 FDW ( )
① ② ③ ④

① Series name
② No. of contacts 96
③ Type of contact Wire wrapping, female
④ Contact plating
None Silver plate
G+ Gold plate







● Components

①	Insulator
②	Contact

Mating connectors: MRF-□6MD( )+, MRF-□6ML( )+

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

HONDA TSUSHIN KOGYO CO., LTD.

Right-angle through hole type male connector PCB
MRF-96ML( )+

RoHS


Rectangular connector
For PCB
Right-angle Through hole





● **Configuration of product Part No.**


MRF- 96 ML ( )+
① ② ③ ④

① Series name
② No. of contacts 96
③ Type of contact Right-angle through hole, male
④ Contact plating
None Silver plate
G Gold plate









● **Components**

①	Insulator
②	Contact (short)
③	Contact (middle)
④	Contact (long)
⑤	Locking piece


Mating connectors: MRF-□6FD( )+, MRF-□6FL( )+, MRF-□6FDW( )

Through hole | SMT | Press-in | IDC | Soldering | Crimping | Wire wrapping | Others

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Straight through hole type male connector for PCB
MRF-96MD( )+


RoHS



● Configuration of product Part No.

MRF- 96 MD ( )+
① ② ③ ④

① Series name
② No. of contacts 96
③ Type of contact Straight through hole, male
④ Contact plating
None Silver plate
G Gold plate



● Components

①	Insulator
②	Contact
③	Locking piece

Mating connectors: MRF-□6FD( )+, MRF-□6FL( )+, MRF-□6FDW( )

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP