

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

CCD Imaging Cameras	ST-237A	ST-5C	ST-6B	ST-7XE	ST-8XE	ST-9XE	ST-10XE	ST-1001E	ST-2000XM
Video Camera / Autoguider	STV	ST-4							
Industrial / Scientific	Industrial Cameras		Spectrograph						

MODEL ST-6B CCD IMAGING CAMERA

[Note: This page is for reference only. The ST-6B has been discontinued and replaced with the ST-9XE]

Camera Model	Pixel Size	Pixel Array	Detector Size	Download Time	Interface	Dark Current @ -30C	Read Noise	Full Well Capacity	Self-guiding
ST-9XE	20 x 20 u	512 x 512	10.2 x 10.2 mm	~1 sec	USB	~1e-	13e-	150,000	Yes
ST-6B	23 x 27 u	375 x 241	8.6 x 6.5 mm	~25 sec	Serial	~10e-	23e-	400,000	No

The Model ST-6B was a successful product from the moment it became available. Following its introduction, for a period of years, it was in wider use than any other cooled low light level CCD imaging camera in the world. It's popularity by both amateur and professional astronomers was clearly proven by the hundreds of discoveries that have been published based on observations and images with this instrument. Discoveries ranging from Near Earth Asteroids and Supernova monitoring to the study of Gamma Ray Burster error boxes and distant Globular Clusters.

The ST-6B is still in use throughout the world. However, for those interested in a relatively inexpensive large pixel array with high sensitivity, the ST-9E offers better performance. The ST-9E also includes SBIG's patented dual sensor self-guiding, a feature not available on the ST-6B. For these reasons, the ST-6B has been discontinued and replaced by the ST-9E.



ST-6B CCD IMAGING CAMERA



Saturn. Color image captured with a Model ST-6 CCD camera and color filter wheel. Taken through a C14 telescope at f/60 using eyepiece projection. *Courtesy Ed Grafton*

The Model ST-6B will reveal spiral structure in hundreds of galaxies with 1 to 5 minute exposures at the prime focus of an 8 inch f/10 telescope. Planetary nebulae become easy objects. Stellar photometry down to 18th magnitude can be easily accomplished. The imaging camera is used in conjunction with an IBM PC compatible or Macintosh computer which allows the images to be easily displayed and processed. The ST-6B uses a proprietary two stage thermoelectric cooler design. The CCD temperature is user selectable and regulated to 0.1 degree. A regulating thermistor on the CCD stabilizes the temperature for long periods allowing low dark current operation. As a result, the ST-6B is capable of one hour exposures that are typically sky background limited.



NGC 253. Twenty 30 second exposures were combined to create this ST-6 image taken through a C8 telescope operting at f/6.3. *Courtesy of Ed Grafton*

The ST-6B incorporates a unique feature called Automatic Track & Accumulate (TRACCUM), allowing automatic guiding of long integrated images. In the TRACCUM mode the ST-6B will take an exposure, determine the position of a preselected star, add the image to the image sum building in an internal memory buffer, correct the telescope's position and then start the cycle over again. In this mode up to 64 images can be co-added. The resulting exposure is almost as good as a single long exposure, dependent on the exposure used and the actual sky conditions. The great sensitivity of the CCD virtually guarantees that there will be a usable guide star within the field of view. This patented feature provides dramatic performance and makes long exposures easy.



NGC 4216. This color image was captured with an ST-6 camera and color filter wheel through a C14 telescope operating at f/7. *Courtesy Ed Grafton*

The ST-6B allows the user to pursue challenging photometric and astrometric tasks which previously required expensive photomultipliers, and precise microscopes with expensive translation stages. These functions, which are part of the CCDOPS operating software furnished with each imaging camera, include variable star photometry, precise asteroid monitoring, and even spectroscopy. The CCD does more than just capture images with great sensitivity; it enables accurate brightness data to be extracted, a third dimension to all images shown here, a dimension which is very difficult to obtain from film.

Model ST-6B CCD Specifications

CCD	**TI TC-241**
Pixel Array	**375 x 241 pixels, 8.6 x 6.5 mm**
Total Pixels	**91,000**
Pixel Size	**23 x 27 microns**
Full Well Capacity	**400,000e**
Dark Current	**10e^-/pixel/sec at -30° C**
Antiblooming	**Variable Rate**

Readout Specifications

Shutter	**Electronic + EM Dark Vane**
Exposure	**0.01 to 3600 seconds, 10ms resolution**

Correlated Double Sampling	**Yes**
A/D Converter	**16 bits**
A/D Gain	**6.7e^-/ADU**
Read Noise	**23e^- RMS**
Binning Modes	**1 x 1, 1.5 x 1, 1.5 x 2**
Pixel Digitization Rate	**8 KHz**
Full Frame Acquisition	**under 25 seconds**

Optical Specifications (8" f/10)

Field of View	**14.9 x 11.3 arcminutes**
Pixel Size	**2.4 x 2.8 arcseconds**
Limiting Magnitude	**Magnitude 14.5 in 1 second**
(for 3 arcsec FWHM stars)	**Magnitude 18 in 1 minute**

System Specifications

Cooling	**Two Stage Thermoelectric Active Fan, -55 from Ambient Minimum**
Temperature Regulation	**±0.1°C**
Power	**12 V AC/DC 4 amps, Transformer included**
Computer Interface	**Serial (RS-232, RS-422)**
Computer Compatibility	**PC - MS-DOS, Windows 95 or Macintosh**
Guiding	**Autoguiding and Track & Accumulate**

Physical Dimensions

Optical Head	**6 inches diameter x 3 inches deep 15 cm diameter x 7.5 deep 2.5 pounds/1.1 Kg**
CPU	**6 x 9 x 2.5 inches / 15 x 23 x 6.3 cm 2 pounds/0.9 Kg**

Mounting	**T-Thread, 1.25" and 2" nosepieces included**
Backfocus	**0.64 inches/0.6 cm**

Price

[DISCONTINUED]

Revised: September 11, 2002 03:44:19 PM.
Copyright © 1998 Santa Barbara Instrument Group, Inc. All rights reserved.
Please report any problems with this page directly to the Webmaster

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP