

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Keysight / Agilent 8154B* at our website: ***Click HERE***


With compliments
Helmut Singer Elektronik
www.helmut-singer.com

FIBER OPTIC TEST EQUIPMENT

LED Source / Laser Diode Source

Model 8154B opt.003 (850nm), opt.002 (1300nm), opt.003 (1550nm) / Model 8155A opt.002 (1300nm), opt.003 (1550nm)

- Stability ±0.003dB/12h
- External modulation up to 1MHz
- Customer-exchangeable connector adapters




HP 8154B, option 002, option 011

DESIGNED FOR HP-IB SYSTEMS

The HP 8154B is a high performance LED source, optional for 850nm, 1300nm and 1550nm. Whether the insertion loss of connectors, attenuation of cables or the splice loss of optical links needs to be evaluated, the HP 8154B provides the required power level stability of typically 0.003dB at constant ambient temperature over 12h.

- Stability ±0.005dB/12h
- External modulation up to 850MHz
- Customer-exchangeable connector adapters

NEW



HP 8155A, option 002, option 011

DESIGNED FOR HP-IB SYSTEMS

The HP 8155A is a narrow linewidth laser diode source, optional for 1300nm and 1550nm with excellent short- and longterm stability. It outputs CW or 270Hz chopped light. External modulation up to 850MHz is also possible, and allows signal performance tests on fast telecommunication links.

Both, the HP 8154B and the HP 8155A, offer customer-exchangeable connector adapters.

HP 8154B, 8155A Specifications

Optical Characteristics	LED 8154B			LD 8155A	
	option 001	option 002	option 003	option 002	option 003
Wavelength	850±30nm	1300±40nm	1550±40nm	1310±30nm	1560±40nm
Spectral Bandwidth	30–90nm	40–90nm	70–150nm	<3nm (RMS)	<3nm (RMS)
Optical Power	≥−17dBm	≥−20dBm	≥−23dBm	≥−4dBm	≥−4dBm
Stability/15min./const. temp	—	—	—	±0.003dB	±0.003dB
Stability/12h/const. temp.(typ.)	±0.005dB	±0.003dB	±0.003dB	±0.005dB	±0.005dB
Stability/12h/±2C	±0.02dB	±0.02dB	±0.03dB	±0.03dB	±0.03dB
Fiber Type	50/125um	50/125um	50/125um	9/125um	9/125um

Connector: Diamond® HMS-10/HP, FC/PC, DIN 47256, ST

Supplementary Performance Characteristics

Digital Input
Input levels: TTL (8154B), ±0.2V (8155A)
Max. input voltage: ±10V (8154B), ±2.5V (8155A)
Input impedance: 10 kOhm (8154B), 50 Ohm (8155A)
Input frequency: 0 to 1MHz (HP 8154B), DC, 1kHz to 850 MHz (HP 8155A)
Operating Modes
Output disable: LED, LD switched off
External modulation enable: Activates the digital input
Internal modulation enable: Activates internal 270Hz generator

General

Recalibration period: 1 year
Warm-up time: 45 minutes for ±0.02dB stability
Environmental
Storage Temperature: −40°C to +75°C
Operating Temperature: 0°C to +55°C
Humidity: <95% R.H. from 0°C to +40°C
Power: 100/120/220/240Vrms, ±10%, 48–400Hz, 35VA max. (8154B), 45VA max. (8155A)

After being switched off the instruments will come up with the output and digital input disabled.

Dimensions: 89mm(H) x 212.3mm(W) x 345mm(D) (3.5" x 8.36" x 13.6")
Weight: net 3.75kg (8.3lbs), shipping 7.8kg (17.2lbs) (HP 8154B)
net 4.5kg (9.9lbs), shipping 8.55kg (18.85lbs) (HP 8155A)

Ordering Information

HP 8154B LED Source
Opt 001: 850nm
Opt 002: 1300nm
Opt 003: 1550nm

HP 8155A LD Source
Opt 002: 1300nm
Opt 003: 1550nm


Opt 011[1]**:** Diamond® HMS-10/HP connector interface
Opt 012[1]**:** FC/PC connector interface
Opt 013[1]**:** DIN 47256 connector interface
Opt 014[1]**:** ST connector interface
Opt. 907: Front handle kit (HP P/N 5061-9688)
Opt. 908: Rack flange kit (HP P/N 5061-9672)
Opt. 916: Additional operating manual
P/N 5061-9701 Bail handle kit

[1] for both the HP 8154B and the HP 8155A, customer-exchangeable

For adapters, cables and other accessories see "Fiber Optic Test Accessories" on page 307

LED-/Laserquellen:

- Hohe Stabilität
- Austauschbare Anschlußadapter
- Externe Modulation bis zu 850 MHz (HP 8155A)



ENTWICKELT FÜR HP-IB SYSTEME

HP 8155A, Option 002

LED-Quelle HP 8154B, Laserquelle HP 8155A

Die Hochleistungs-LED-Quelle HP 8154B ist der ideale Stimulus für alle Messungen an Multimode-Fasern und -Komponenten. Sie bietet eine interne Modulation bei 270 Hz und kann extern bis zu 1 MHz moduliert werden.

HP 8155A ist eine Laserquelle mit hoher Stabilität und der Möglichkeit zur externen digitalen Modulation bis zu 850 MHz. Dadurch sind auch Signalleistungsmessungen an schnellen Telekommunikationsverbindungen möglich.

Technische Daten LED-Quelle HP 8154B

	Option 001	Option 002	Option 003
Wellenlänge	850 nm ± 30 nm	1300 nm ± 40 nm	1550 nm ± 40 nm
Fasertyp	50/125 µm	50/125 µm	50/125 µm
Ausgangsleistung	>–17 dBm	>–20 dBm	>–23 dBm
Stabilität (12 h)	± 0,03 dB	± 0,02 dB	± 0,02 dB

Technische Daten Laserquelle HP 8155A

	Option 002	Option 003
Wellenlänge	1300 nm ± 30 nm	1550 nm ± 40 nm
Fasertyp	9/125 µm	9/125 µm
Ausgangsleistung	>–4 dBm	>–4 dBm
Stabilität (12 h)	± 0,03 dB	± 0,03 dB

Bestellinformationen

LED-Quelle HP 8154B Grundgerät*
- **Option 001:** Wellenlänge 850 nm
- **Option 002:** Wellenlänge 1300 nm
- **Option 003:** Wellenlänge 1550 nm

Laserquelle HP 8155A Grundgerät
- **Option 002:** Wellenlänge 1300 nm
- **Option 003:** Wellenlänge 1550 nm

Gemeinsame Optionen für beide Geräte
- **Option 907:** 1 Satz Frontgriffe
- **Option 908:** Gestelleinbausatz
- **Option 914:** Zusätzlich ein Operating Manual und ein Sevice Manual
- **Option 916:** Zusätzliches Operating Manual

* Es wird ein Anschlußadapter (HP 81000xI) je Grundgerät benötigt (siehe rechte Spalte).

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP