

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PCISA-3716E2V

Product Description:
PCISA Socket-370 CPU Card with Dual 10/100Mbps Ethernet, VGA & Audio



Click to Enlarge



REAR VIEW
Click to Enlarge

Features

- Supports Intel® Socket 370 base CPU from Celeron™ to Pentium® III up to 133MHz FSB
- Dual 10/100Mbps Ethernet on board
- Built-in VGA function with share memory architecture
- Designed with SiS630E chipset; support 133MHz FSB and Ultra DMAA66 IDE interface
- PCISA golden edge with PCI & ISA (Not Support Bus Master ISA card) fully compatible with ICP IP & IPX series backplane

Specifications

- CPU : Socket 370 base support Celeron™ / Pentium® III up to 133MHz FSB
- System Memory : One 168-pin DIMM sockets up to 512MB SDRAM and NEC Virtual channel memory (VCM)
- System Chipset : SiS630E
- BIOS : Award PnP Flash BIOS
- Video Controller :
  --> Integrated in SiS630E Chipset
  --> BUS : AGP 66MHz
  --> V-RAM : Share with system memory up to 64MB RAM
  --> Resolution : 1600 x 1200 (16 bit colors)
  --> Connector : DB-15 for CRT display
- Super I/O :
  --> 2 x RS-232 ports(optional one port RS-422/485)
  --> 1 x Parallel port (support SPP/EPP/ECP mode)
  --> IrDA port
  --> Hardware monitoring system
- USB Ports : Tow ports meets USB ver.1 standard by pin-header
- Ethernet : Dual Ethernet with one integrated in SiS630E chipset and one Realtek 8139C

- Audio : Integrated in SiS630E chipset meets AC'97 standard with Two 6W Amplifier (option)
- IDE : One Ultra DMA66 interface with one 40-pin pin-header
- FDD : One port
- WatchDog Timer
- Supports ATX power control function
- Power Consumption : 6A @+5V, 170mA@+12V
  (Pentium® III 500MHz CPU and 512MB SDRAM)
- Operating temperature : 0 ~ 60°C (CPU needs cooler)
- Relative humidity : 5 ~ 95%, non-condensing
- Support Compact Flash Type II Socket

Ordering Information

PCISA-3716E2V	PCISA Socket-370 SBC with VGA, Audio & Dual Ethernet
PCISA-3716EV	PCISA Socket-370 SBC with VGA, Audio & Ethernet

Model	PCI 1	PCI 2	PCI 3	PCI 4
PCISA-3716E2V	NO	YES	YES	YES
PCISA-3716EV	YES	YES	YES	YES

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP