ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *IDEC NRAS2100-2-2.5-AA* at our website: ***Click HERE***

NRA Series

Features:

- Available in 4 different styles
- Excellent overload and short circuit protection
- Small size and high-efficiency
- Life expectancy of over 10,000 operations
- UL1077 recognized "Supplementary Protectors"
- VDE certified to EN60934

c UL us File No. E68029

VDE License #116381

NRAS



NRAN



NRAR



Rocker



Illuminated Rocker (with Neon lamp)

Specifications

Protection Method	Electromagnetic tripping
Internal Circuit	Series current trip
Number of Poles	NRAS and NRAN: 1, 2, 3 NRAR: 1
Rated Voltage	250V AC, 50/60Hz, 65V DC
Rated Tripping Currents	0.3A, 0.5A, 0.75A 1A, 2A, 3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A
Rated Interrupting Capacity	250V AC, 50/60Hz, 1,000A 65V DC, 1,000A
Auxiliary Contact	SPDT microswitch: 250V AC, 5A (resistive load), 50V DC, 1A (resistive load)
Alarm Contact	SPDT microswitch: 250V AC, 5A (resistive load), 50V DC, 1A (resistive load)
Reference Temperature	25°C
Operating Temperature	–40 to +85°C (avoid freezing)
Insulation Resistance	100MΩ (measured with 500V megger)
Dielectric Strength	Between main circuit terminals: 2,000V AC, 1 minute Between main circuit and auxiliary contact: 2,000V AC, 1 minute
Vibration Resistance	100N (approximately 10G) (10 to 100Hz)
Shock Resistance	1,000N (approximately 100G)
Life Expectancy	Minimum 10,000 cycles (at 6 operations per minute)
Termination	Main terminal: Quick-connect receptacle 0.250" (accepts M3.5 screw terminal adapter) Auxiliary contact, alarm contact: Quick-connect receptacle 0.080"
Illumination Voltage (NRAR illuminated units)	Neon: 120, 240V AC, 50/60Hz

Not suitable for branch circuit protection.

Part Numbering Guide

NRA series part numbers are composed of up to 8 part number codes. When ordering an NRA series part, select one code from each category.
Example: NRAR 1 1 11 -F - 30A -AA -1

NRAR	1	1	11	—	F	—	30A	—	AA	—	1
① Model	② Poles	③ Internal Circuit	④ Auxiliary and Alarm Contacts		⑤ Inertia Delay		⑥ Rated Current		⑦ Time Delay Curve		⑧ Pilot Light*

Part Number Codes: NRA Series

	Description	Part Number Code	Remarks
① **Model**	Lever (round cutout)	NRAS	
	Lever (rectangular cutout)	NRAN	
	Rocker	NRAR	
② **No. of Poles**	1-pole	1	NRAR available in 1-pole only. All multi-pole circuit breakers are simultaneous throw/simultaneous break. All levers are mechanically interlocked.
	2-pole	2	
	3-pole	3	
③ **Internal Circuit**	Series current trip	1	
④ **Auxiliary and Alarm Contacts**	Without	00	
	With auxiliary contact	11	Auxiliary contact switches change state with lever and/or overload condition
	With alarm contact	21	Alarm contact switches change state only with overload condition
⑤ **Inertia Delay**	Without inertia delay	Blank	
	With inertia delay	F	
⑥ **Rated Current**	Rated current (current trip)	0.3A, 0.5A, 0.75A, 1A, 2A, 3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A	All current ratings must be listed in amps (A). Example conversion: 300mA = 0.30A.
⑦ **Time Delay Curve**	AC curves	AA, BA,MA	For time delay curves, see page 888.
	DC curves	AD, MD	
⑧ **Pilot Light***	With neon light 120V AC (50/60Hz)	1	*Applicable to illuminated NRAR only.
	With neon light 240V AC (50/60Hz)	2	

1. For NRA series accessories, see page 886.
2. For NRA series time delay curves, see page 888.
3. For NRA series dimensions, see page 890.
4. Not suitable for branch circuit protection.
5. UL recognized, applicable standard: UL1077, "Supplementary Protectors."

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Information About Circuit Breakers


Time Delay Curve Descriptions

Time Delay Curve	NRA Application
AD, AA	Common curves used in molded-case circuit breakers.
BA	Response to overcurrent is quite fast. Suited for protection of semiconductor circuits with very little overload tolerance. If overcurrents are expected to flow, fuses may be required according to the circuit characteristics.
MD, MA	Suited for motor loads that draw high inrush currents lasting a considerable length of time.
With Inertia Delay (F)	Designed not to trip on 20 times the rated current (peak value) for a duration of 8ms. Suited for transformer and lamp loads that draw steep inrush currents.

Inertia Delay Description

Circuit breakers equipped with inertia delay do not respond to high inrush currents such as those produced by transformer, lamp, or motor loads, but perform specified interruption on rated overcurrents.

Specify inertia delay by inserting an "F" in the part number as shown in Part Number Guide on previous page.



1. Percent of Rated Current $= \frac{\text{Pulse Peak Current}}{\text{Protector Rated Current}} \times 100\%$

2. Based on sinusoidal or parabolic pulse profile.

Notes

Multi-Pole

Multi-pole types such as 2- or 3-pole should be assembled by IDEC.
Because of their characteristics, 1-pole breakers cannot be combined to provide multi-pole units.



Auxiliary and Alarm Contacts

Multi-pole units can incorporate auxiliary and alarm contacts.
Auxiliary and alarm contacts will not work with IDEC's DIN rail adapters.



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Accessories

Part Numbers: NRA Series Accessories

Description		Appearance	Part No.	Remarks
Color Caps (NRAS only)	Red		NR5R	 Colored caps fit onto NRAS circuit breakers for color coding circuits and improving the appearance of the panel.
	Blue		NR5S	
	Yellow		NR5Y	
	White		NR5H	
Screw Terminal Adapter (1 pair)			NRT	For use on main terminals only. Includes M3.5 clamp screw. For dimensions see page 892.


Part Numbers: NRA Mounting Accessories

Description	Appearance	For Model	Number of Poles	Part Number	Remarks
Panel Mount Flush Plate		NRAN NRAR	1-pole	NR31	Use of a flush plate makes snap-in mount possible for NRAN, and NRAR circuit breakers (tightening screws not necessary). Multiple units can mount in a single panel cut-out.
		NRAN	2-pole	NR32	
		NRAN	3-pole	NR33	
DIN Rail Plug-in Base		NRAS NRAN	1-pole	NR21	1. Furnished with a hold-down spring. 2. Applicable only for series trip units up to 20 amps. 3. Not applicable for NRAR lighted series. 4. Not for use with circuit breakers incorporating auxiliary or alarm contacts.
			2-pole	NR22	
			3-pole	NR23	
		NRAR	1-pole	NR211	
Surface Mount Plug-in Base		NRAS NRAN	1-pole	NUS1	
			2-pole	NUS2	
			3-pole	NUS3	
		NRAR	1-pole	NUS11	


For dimensions of NRA series accessories and panel cut-out layouts, see drawings starting on page 891.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Internal Circuits and Terminal Arrangements: NRAS and NRAN Series



Internal Circuits and Terminal Arrangements: NRAR Series



Pilot Lights (NRAR only)

	Lead Wire	
Pilot Light	**A**	**B**
Neon (120V AC)	White	White
Neon (240V AC)	Black	Black

Dashed lines represent NRAR illuminated rocker units. Lead wires for neon pilot light as shown above.


Time Delay Curves (numerical equivalent)


Overcurrent — Time Delay Characteristics in Seconds (at 25°C)


		Percent of Rated Current							
	Curve	**100%**	**125%**	**150%**	**200%**	**400%**	**600%**	**800%**	**1000%**
AC (50/60Hz)	**AA**	No trip	10 – 120	6 – 45	2.2 – 15	0.3 – 2	0.05 – 0.55	0.007 – 0.13	0.005 – 0.04
	BA	No trip	0.75 – 10	0.45 – 3.5	0.22 – 1.3	0.045 – 0.22	0.012 – 0.12	0.005 – 0.06	0.004 – 0.03
	MA	No trip	60 – 900	30 – 260	9 – 70	1.5 – 8	0.18 – 2.5	0.009 – 0.25	0.006 – 0.08
DC	**AD**	No trip	10 – 130	6 – 55	2.6 – 20	0.5 – 3.5	0.12 – 1.4	0.008 – 0.1	0.005 – 0.05
	MD	No trip	35 – 400	20 – 200	7 – 60	1.3 – 8	0.2 – 3	0.01 – 0.25	0.006 – 0.08

1. All values above are in seconds.
2. Data in this table is equivalent to information presented in the time delay curves shown on page 888.


Time Delay Curves – NRA Series








DC Time Delay Curves





Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Resistance and Impedance Characteristics

Coil Data

Rated Current	DC Resistance	AC Impedance (50/60Hz)
	Curves AD, MD	Curves AA, BA, MA
0.3A	9.67Ω	9.82Ω
0.5A	3.24Ω	3.36Ω
0.75A	1.45Ω	1.49Ω
1A	0.90Ω	0.92Ω
2A	0.21Ω	0.21Ω
3A	0.09Ω	0.092Ω
5A	0.036Ω	0.036Ω
7.5A	0.017Ω	0.018Ω
10A	0.012Ω	0.012Ω
15A	0.0066Ω	0.0068Ω
20A	0.0048Ω	0.0048Ω
25A	0.0043Ω	0.0043Ω
30A	0.0036Ω	0.0041Ω

Tolerance ±25% (up to 20A), ±50% (25A and over).


Voltage Drop Due to Resistance or Impedance

The internal resistance or impedance of a circuit breaker tends to be larger for a smaller rated current. Therefore, when circuit breakers with a small rated current are used, voltage drop should be taken into consideration. Internal resistance also varies with time delay curves, even at the same rated current. This should also be considered during installation.


Time Delay Curve and Ambient Temperature

Since NRA series circuit breakers employ an electromagnetic tripping system, the rated current (trip current) is not affected by the ambient temperature, but the time delay varies with the oil viscosity in the tube. Lower oil viscosity at higher temperatures results in shorter delay; whereas at lower temperatures, the delay will be prolonged. The time delay curves, shown starting on page 888, are at 25°C. Time delay curves can be corrected.


Impedance Correction Curve



Resistance Correction Curve




Temperature Correction Curves




Dimensions

NRAS


• 1-pole



• 2-pole




• 3-pole




NRAN


• 1-pole




• 2-pole



• 3-pole




NRAR




Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Panel Cut-Outs


NRAS Series



NRAR, NRAN




NR31, NR32, NR33 – Panel Mount Flush Plate



Panel cut-out when two or more units are mounted closely (n = number of units).
Note 1: 24.3n - 5
Note 2: 48.8n - 10
Note 3: 69.3n - 10

Installation Angle: Circuit breakers are designed to operate on a vertical surface. The mounting angle should not exceed a vertical plane by more than 10°.


Model	Maximum Mounting Distance A	Maximum Mounting Distance B	Dimensions (mm)
NRAS	3.02″ (77.5mm)	3.57″ (91.5mm)	Mounting to Panel Surface / Mounting to DIN Rail
NRAN	3.02″ (77.5mm)	3.57″ (91.5mm)	
NRAR	3.38″ (86.7mm)	3.93″ (100.7mm)	



Accessory Dimensions

NRT: Screw Terminal Adapter (for use with NRA Series)






1. For use on main terminals only.
2. Includes M3.5 clamp screw.

BNDN1000 Aluminum DIN Rail





	Length in Inches (mm)
A	1.4" (35mm)
B	1.14" (29mm)
C	0.78" (23mm)
D	1.2" (31mm)
E	0.41" (10.5mm)
F	0.11" (3mm)
G	2" (51mm)
H	0.47" (12mm)
K	0.16" (4mm)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP