

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

GenRad 1433 Series

The 1433 Decade Resistors are convenient resistance standards for checking the accuracy of resistance-measuring devices. They are primarily intended for precision-measurement applications where accuracy, stability, and low-zero-resistance are important. They are used as components in dc and audio frequency impedance bridges.



*Model **1433** Precision Decade Resistor*

Features:

- Resistance range from 1 mΩ to 111 MΩ
- High accuracy: 0.01% up to 10 MΩ
- Low temperature coefficient
- Good frequency characteristics
- Excellent stability
- Low zero resistance
- Rack mount option available

See also:

- Higher accuracy: **HARS-LX Series**
- Higher power: **HPRS Series**
- Higher resistance: **HRRS Series**
- Higher voltage: **HRRS-5kV** and **HRRS-10kV Series**
- RTD simulators: **RTD Series**
- Programmable models: **PRS Series**

SPECIFICATIONS

Resistance per step	Total decade resistance	Max current	Max voltage (per step)	Max power (per step)	Stability (±ppm/yr)	Long-term stability (±ppm/3 yrs)	Temperature coefficient (±ppm/°C)	Resistor type
1 mΩ	10 mΩ	8.0 A	5 mV	0.04 W	50	75	50	Resistance wire
10 mΩ	100 mΩ	4.0 A	40 mV	0.16 W	50	75	20	
100 mΩ	1 Ω	1.6 A	0.16 V	0.25 W	50	75	20	
1 Ω	10 Ω	0.8 A	0.8 V	0.6 W	20	25	20	Wirewound, non-inductive
10 Ω	100 Ω	0.25 A	2.5 V	0.6 W	20	25	15	
100 Ω	1 kΩ	80 mA	8 V	0.6 W	20	25	5	
1 kΩ	10 kΩ	23 mA	23 V	0.5 W	20	25	5	
10 kΩ	100 kΩ	7 mA	70 V	0.5 W	20	25	5	
100 kΩ	1 MΩ	2.3 mA*	230 V*	0.5 W*	20	25	5	
1 MΩ	10 MΩ	0.7 mA*	700 V*	0.5 W*	20	25	5	
10 MΩ	100 MΩ	0.1 mA*	1000 V*	0.1 W*	50	100	10	Metal oxide film

**Subject to maximum of 2000 V to case*

Accuracy:
≤1 MΩ decades: ±(0.01% + 2 mΩ)
10 MΩ decades: ±0.03%
after subtraction of zero resistance, at 23°C; traceable to SI

Zero resistance:
≤1 MΩ decades: <1 mΩ per decade at dc
10 MΩ decade: ≈3 mΩ at dc

Max voltage to case:
2000 V peak

Terminals:
Gold-plated, 5-way, tellurium-copper binding posts with low thermal emf and low resistance. Rear outputs are available as an option.

Terminals:
3 binding posts, labeled **HI**, **LO**, and **GND**

-K Option: Kelvin connection is available as an option with 5 binding posts, labeled **HI CURRENT**, **HI SENSE**, **LO SENSE**, **LO CURRENT**, and **GND**

Switch capacitance:
<1 pF between contacts

Environmental conditions:
Operating: 10°C to 40°C; < 80% RH
Storage: -40°C to 70°C

Typical Value of Zero Impedance:
<0.001 Ω/decade at 1 Hz
0.04 Ω/decade at 1 MHz
Proportional to square root of frequency above 100 kHz

Switches:
Continuous rotation
11 positions marked "0"-"10"
Multiple solid silver-alloy contacts

Supplied with unit:
Instruction manual
Calibration Certificate

IET LABS, INC. in the GenRad Tradition
Long Island, NY

www.ietlabs.com
TEL: (516) 334-5959 • EMAIL: info@ietlabs.com

MECHANICAL SPECIFICATIONS

Model	Dimensions	Weight
3 decade	31 cm W x 8.9 cm H x 10.2 cm D (12.2" x 3.5" x 4")	1.7 kg (3.8 lb)
4-5 decade	37.6 cm W x 8.9 cm H x 10.2 cm D (14.8" x 3.5" x 4")	2.0 kg (4.3 lb)
6-7 decades	43.9 cm W x 8.9 cm H x 10.2 cm D (17.3" x 3.5" x 4")	2.4 kg (5.3 lb)
8-9 decades	48.3 cm W x 17.8 cm H x 17.8 cm D (19" x 7" x 7")	3.5 kg (7.7 lb)
10-11 decades		3.7 kg (8.1 lb)

ORDERING INFORMATION

Model	Total resistance	Number of decades	Resolution	Historic GR model numbers
1433-01	1.11 Ω	3	0.001 Ω	
1433-00	111.1 Ω	4	0.01 Ω	1433-U
1433-02	1.111 kΩ	4	0.1 Ω	1433-K
1433-04	11.11 k Ω	4	1 Ω	1433-J
1433-06	111.1 k Ω	4	10 Ω	1433-L
1433-08	1.111 MΩ	4	100 Ω	1433-Q
1433-09	11.11 MΩ	4	1 kΩ	
1433-09A	111.1 MΩ	4	10 kΩ	
1433-10	1.1111 kΩ	5	0.01 Ω	1433-T
1433-12	11.111 kΩ	5	0.1 Ω	1433-N
1433-14	111.11 kΩ	5	1 Ω	1433-M
1433-16	1.1111 M Ω	5	10 Ω	1433-P
1433-18	11.111 MΩ	5	100 Ω	1433-Y
1433-18A	111.11 MΩ	5	1 kΩ	
1433-19	1.111 11 kΩ	6	0.001 Ω	
1433-20	11.1111 kΩ	6	0.01 Ω	1433-W
1433-22	111.111 kΩ	6	0.1 Ω	1433-X
1433-24	1.111 11 MΩ	6	1 Ω	1433-B
1433-26	11.1111 MΩ	6	10 Ω	1433-Z
1433-27	111.111 MΩ	6	100 Ω	

Model	Total resistance	Number of decades	Resolution	Historic GR model numbers
1433-28	11.111 11 kΩ	7	0.001 Ω	
1433-29	111.1111 k Ω	7	0.01 Ω	1433-F
1433-31	1.111 111 MΩ	7	0.1 Ω	1433-G
1433-33	11.111 11 MΩ	7	1 Ω	1433-H
1433-34	111.1111 MΩ	7	10 Ω	
1433-35	111.111 11 kΩ	8	0.001 Ω	
1433-36	1.111 111 1 MΩ	8	0.01 Ω	
1433-37	11.111 111 MΩ	8	0.1 Ω	
1433-38	111.111 11 MΩ	8	1 Ω	
1433-39	1.111 111 11 MΩ	9	0.001 Ω	
1433-39A	11.111 111 1 MΩ	9	0.01 Ω	
1433-39B	111.111 111 MΩ	9	0.1 Ω	
1433-40A	11.111 111 11 MΩ	10	0.001 Ω	
1433-40	111.111 111 1 MΩ	10	0.01 Ω	
1433-41	111.111 111 11 MΩ	11	0.001 Ω	

Options:

1433-50: Rack Mount Kit (4-dial)
1433-51: Rack Mount Kit (5-dial)
1433-52: Rack Mount Kit (6 and 7-dial)
1433-XX-RO: Rear output binding posts
1433-XX-K: Kelvin-type 4-terminal posts and GND

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

IET Labs:

1433-09 1433-35 1433-39 1433-33 1433-06 1433-37 1433-38 1433-34 1433-36 1433-31 1433-39A 1433-02 1433-40A 1433-16 1433-12 1433-18 1433-10 1433-14 1433-19 1433-18A 1433-10A 1433-08 1433-01 1433-20 1433-28 1433-24 1433-22 1433-26 1433-27 1433-39B 1433-04 1433-40 1433-09A 1433-00 1433-41 1433-24-C

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP