

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

RS-CS-LS Series

Economical, indispensable tools for a variety of uses in engineering, design, troubleshooting, or service.

These small, rugged substituters can satisfy most requirements.

Features:

- Direct reading — No fumbling with multiple slide or rotary switches
  The IET family of digital substituters uses convenient side-by-side thumbwheel switches. Simply dial in the desired values and use.
- Standard accuracies of 1%, 0.1%, and 0.05% available.
- Broad choice of standard and optional models.
  A full line of standard substituters satisfies most requirements.
- Direct readings eliminate potential mistakes that come from rotary or slide-switch boxes.
- For easy value readings, ranges are separated by color-coded switches and numbers.
- The units are small, rugged, and portable.
- Combination units, such as Resistance and Capacitance Substituter (RCS-500), are available.

Options:

- Shielded case with grounding post
- Panel mounting
- Protection fuse

See also:

- Decade box product guide
- LCR meter product guide



R-Box

RS Series: Digital Resistance Substituter

Available from 0.01 Ω to 299,999,999.9 Ω (RS-200 Shown)



C-Box

CS Series: Digital Capacitance Substituter

Available from 1 pF to 999.999 9 µF (CS-300 Shown)



L-Box

LS Series: Digital Inductance Substituter

Available from 1 µH to 99.999 99 H (LS-400 Shown)



RC-Box

RCS Series: Digital Resistance-Capacitance Substituter

Combines RS and CS units in one box (RCS-500 Shown)

RS-CS-LS Series

Standard Models

RS Series -- Standard Models

Model	RS-200	RS-201	RS-200W	RS-201W	RS-200-2W	RS-201W-2W	RS-RTD	RCS-500	RCS-502
Type	Resistance	Precision Resistance	Wide-Range Resistance	Wide-Range Precision Resistance	High-Power Resistance	High-Power Wide-Range Resistance	RTD Simulator	Resistance/ Capacitance	Precision Resistance/ Capacitance
Accuracy*	±(1% + 25 mΩ)	±(0.1% + 25 mΩ)	±(1% + 36 mΩ)	±(0.1% + 36 mΩ)**	±(1% + 25 mΩ)	±(0.1% + 36 mΩ)**	±(0.1% + 25 mΩ)	Combines RS-200 and CS-300	Combines RS-201 and CS-301
Decades	7		9		7	9	6		
Range	0 to 9,999,999 Ω		0 - 99,999,999.9 Ω		0 - 9,999,999 Ω	0 - 99,999,999.9 Ω	0-9,999.99 Ω		
Resolution	1 Ω		0.1 Ω		1 Ω	0.1 Ω	0.01 Ω		
Ratings***	0.5 W (rising to 2.5 W at step 9)				2 W (rising to 10 W at step 9)		0.5 W		
Residual	≤0.39 Ω (≤0.056 Ω/decade)		≤0.5 Ω (≤0.056 Ω/decade)		≤0.39 Ω	≤0.5 Ω	≤0.34 Ω		
Components	Metal-film resistors; Manganin wire ≤0.9 Ω								
Mechanical	A		B		A	B	A	C	

CS Series -- Standard Models

Model	CS-300	CS-301	CS-301L	CS-300H
Type	Capacitance	Precision Capacitance	Precision, Low Capacitance	High Capacitance
Accuracy*	**<10 µF:** ±(4% + 3 pF) **≥10 µF:** ±7%	**<10 µF:** ±(1% + 3 pF) **≥10 µF:** ±7%	±(1% + 3 pF)	**<10 µF:** ±(4% + 3 pF) **≥10 µF:** ±7%
Decades	6		7	
Range	0 to 99.999 9 µF		0 - 9.999 999 µF	0 - 999.999 9 µF
Resolution	100 pF		1 pF	100 pF
Ratings***	100 V (25 V for 10 - 100 µF)		100 V	100 V (25 V for 10 - 1000 µF)
Residual	≤42 pF (≤7 pF/decade)		≤49 pF (≤7 pF/decade)	
Components	1-900 pF: mica 0.001 - 0.9 µF: Polypropylene 1-9 µF: Polyester 10-900 µF: Tantalum			
Test Cond.	1 kHz; 1 Vrms; for ≥10 µF: 120 Hz, series model; 23°C			
Mechanical	B			

LS Series -- Standard Models

Model	LS-400A	LS-400	LS-400L
Type	Inductance	High Inductance	Low Inductance
Accuracy*	±(2% + 0.5 µH)		
Decades	3	4	6
Range	0 to 999 mH	0 - 9.999 H	0-999.999 mH
Resolution	1 mH	1 mH	1 µH
Frequency Response	See **http://www.ietlabs.com/ls-series-inductance-decade-box.html**		
Residual	≤0.17 Ω; ≤1 µH (≤0.056 Ω/decade)	≤0.23 Ω; ≤1 µH (≤0.056 Ω/decade)	≤0.34 Ω; ≤1.5 µH (≤0.056 Ω/decade)
Components	Toroidal Inductors		
Test Cond.	1 kHz, 0.1 Vrms; series model; 23°C		
Mechanical	B		C

***Accuracy:**
After subtraction of residual impedance
Traceable to SI

****Accuracy for RS-201W & RS-201W-2W:**
<10 MΩ: as shown above
≥10 MΩ: 0.2%

*****Rating:**
Subject to switch maximum dielectric strength of 750 Vdc peak or 550 Vrms, switching

Switches:
10-position thumbwheel switches
make-before-break

Maximum switch voltage:
750 Vdc peak or 550 Vrms, switching

Mechanical:
A: 8.1 x 7.9 x 5.6 cm; 184 g (3.2" x 3.1" x 2.2"; 6.5 oz)
B: 12.1 x 7.9 x 5.6 cm; 235 g (4.7" x 3.1" x 2.2"; 8.3 oz)
C: 18.8 x 8.4 x 6.4 cm; 410 g (7.4" x 3.3" x 2.5"; 14 oz)

Optional Models

RS - F - 4 - 0.1 - WC - __ (Example: 0.1Ω -999.9 Ω, 1% Resistance Substituter in a standard case)

Type of Substituter	Tolerance	No. of Decades	Resolution	Packaging/Options	Rating
RS: Resistance	**A:** 0.05%	1 to 10	0.01Ω to 100 MΩ	**WC:** Standard	*blank*: Standard
CS: Capacitance	**B:** 0.1%		1 pF to 100 µF	**PM:** Panel Mount w/out case	1W
LS: Inductance	**C:** 0.5%		1 µH to 10 H	**SC:** Shielded Case	2W
	F: 1%			**FP:** Supplied with 2A fuse (residual increases by 0.06 Ω)	*Other*: Consult IET Labs
	G: 2%			*Other*: Consult IET Labs	
	H: 4%				

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP