ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *IKA C 5000* at our website: *Click HERE*

Data Sheet



C 5000 control package 2/10

The IKA® calorimeter C 5000 control is the only calorimeter in the world that offers a free selection of 3 working methods:
Thus it is possible to perform determinations of gross calorific values of liquid and solid samples in adiabatic (approx. 14 - 18 min), isoperibolic (approx. 22 min) and dynamic (reduced time: approx. 10 min) mode. A high level of automation in addition to an extensive range of accessories leave nothing more to wish for.
- Automatic water handling system includes tempering, filling and emptying of calorimeter inner vessel
- Automatic oxygen filling and degassing of the decomposition vessel
- Automatic decomposition vessel identification
- Validation according to DIN 51900,ISO 1928, ASTM D240, ASTM D4809, ASTM D5865, ASTM D1989, ASTM D5468, ASTM E711
- Interface connections for each of the following: scale, printer, monitor and sample rack C 5020
- User-friendly software C 5040 CalWin for controlling the calorimeter and administration of measuring data (accessory)
- LIMS integration is possible
- Cooling water supply via thermostat f.e IKA KV 600 (accessory) or firmly installed water connection, (temperature range 10 - 19°C)
- Special halogen resistent vessel C 5012 for quantitative decomposition of halogens and sulfur (accessory)
- The decomposition vessel can be changed over to use combustible crucibles C 14 (accessory C 5010.4 is needed)
- The C 5000 control can be expanded to the duocontrol system with two measurement cells at any time C 5000 - Standard consumables for calibrations and initial operation included with delivery

Accessories: C 16 Parafilm, C 17 Paraffin, C 5010 Decomposition vessel, standard, C 5012 Decomposition vessel, halogen resistent, KV 600 cooling water supply (230 V), C 5020 Sample rack, C 5030 Venting station, C 5010.4 Attachment for combustible crucible C14, C 5010.5 Crucible holder, big, C 29 Pressure gauge, oxygen, C 21 Pelleting press, C 5040 CalWin, C 5041 CalWin plus, C 5041.10 Connection cable, C 5003.1 Aqua Pro stabilizing agent, C 710.4 Cotton thread, cut to length, C 5010.3 Ignition wire, spare, C 5012.3 Ignition wire, platinum, C 4 Quartz dish, C 5 Set of VA combustion crucibles, C 6 Quartz crucible, big, C 9 Gelatine capsules, C 10 Acetobutyrate capsules, C 12 Combustion bags 40 x 35 mm, C 12 A Combustion bags 70 x 35 mm, C 14 Combustible crucible, C 15 Paraffin strips, C 43

Technical Data	
Measuring range max. [J]	40000
Measuring mode adiabatic 22°C	yes
Measuring mode dynamic 22°C	yes
Measuring mode isoperibol 22°C	yes
Measuring mode adiabatic 25°C	yes
Measuring mode dynamic 25°C	yes
Measuring mode isoperibol 25°C	yes
Measuring mode dynamic 30°C	no
Measuring mode isoperibol 30°C	no
Measuring mode double dry (ISO 1928)	no
Measuring time adiabatic approx. [min]	15
Measuring time dynamic approx. [min]	10
Measuring time isoperibol approx. [min]	22
Reproducibility adiabatic (1g benzoic acid NBS39i) [%RSD]	0.05
Reproducibility dynamic (1g benzoic acid NBS39i) [%RSD]	0.1
Reproducibility isoperibol (1g benzoic acid NBS39i) [%RSD]	0.05
Working temperature max. [°C]	25
Temperature measurement resolution [K]	0.0001
Cooling medium temperature min. [°C]	10
Cooling medium temperature max. [°C]	19
Cooling medium permissible operating pressure [bar]	9
Cooling medium	tap water
Type of cooling	flow
Flow rate min. [l/h]	18
Flow rate max. [l/h]	42
Oxygen operating pressure max. [bar]	40
Interface scale	RS232
Interface printer	Centronix
Interface PC	RS232
Interface test rack	yes
Interface ext. monitor	no
Interface ext. keyboard	no
Oxygen filling	yes
Degasification	yes
Decomposition detection	yes
Decomposition vessel C 5010	yes
Analysis according to DIN 51900 (1977/84)	yes

© IKA® Werke Staufen/Germany 2008 www.ika.net
Subject to technical changes

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP