ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *IKA HKD T 06 D* at our website: ***Click HERE***

Data Sheet
Mixing / Kneaders



HKD-T 06 D IKA High-performance laboratory kneader

For processing non-flowable, highly viscous media. Uniform mixing is based on intensive processing by means of wide-bladed kneading elements. The kneading medium is moved within the trough both horizontally and vertically. Additional media quantities may be added during the kneading operation.
- The double-walled kneading chamber allows cooling or heating of the product
- The product temperature may be measured directly behind the kneading blades
- Trough can easily be removed
- Kneading blades can easily be removed
- Short kneading time
- The narrow gap between the kneading blades and trough wall ensures efficient wipe-off
- Standard version equipped for vacuum operation
- Trough cover with inspection glass and safety screen
- Optional with torque measuring

Accessories: HKD 06.2 Plunger, VC 2 IKAVAC® Vacuum controller, HKD 06.10 Kneading blade, DTM 12 IKATRON® Digital temperature measuring instrument, CC3-308B vpc

Technical Data	
Blade shape	duplex
Usable volume min. [ml]	100
Usable volume max. [ml]	300
Attainable vacuum [mbar]	50
Trough for heating up to max. [°C]	210
Temperature sensor power input	yes
Material in contact with medium	stainless steel 1.4581
Motor rating input [W]	320
Motor rating output [W]	180
Motor protection	thermostat relay
Nominal torque [Nm]	48
Speed max. (front kneading blade) [1/min]	35
Speed max. (back kneading blade) [1/min]	17.5
Safety cutout	yes
Dimensions (W x H x D) [mm]	660 x 380 x 250
Weight [kg]	27
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 54
Analog output	yes
Voltage [V]	220 - 240
Frequency [Hz]	50/60
Power input [W]	320
Ident. No.	**1911800**

© IKA® Werke Staufen/Germany 2008 www.ika.net
Subject to technical changes
Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP