

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

**Artisan Technology Group**
(217) 352-9330 | sales@artisantg.com | artisantg.com

**Full-service, independent repair center**
with experienced engineers and technicians on staff.

**We buy your excess, underutilized, and idle equipment**
along with credit for buybacks and trade-ins.

**Custom engineering**
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

**Expert team | Trust guarantee | 100% satisfaction**

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

**Visit our website - *Click HERE***

# Data Sheet
Mixing / Shakers



## HS 260 basic

Compact, flat shaker with ideal swivel motion, for a maximum shaking weight of 7.5 kg.
- Electronic adjustment of speed and timer
- LED display for speed and time adjustment
- Wide range of attachment combinations makes it possible to use almost all shapes and sizes of vessels
- Attachments are not included in delivery, please order separately

Accessories: AS 260.2 Fixing clip attachment, H 11 Mains cable UK plug, H 11 Mains cable USA plug, H 11 Mains cable Euro plug, AS 260.5 Seperating funnel attachment, AS 260.1 Universal attachment, H 11 Mains cable CH plug, AS 260.3 Dish attachment, AS 2.5 Fixing clips, AS 2.4 Fixing clips, AS 2.3 Fixing clips, AS 2.2 Fixing clips, AS 2.1 Fixing clips

| **Technical Data** | |
|---|---|
| Type of movement | reciprocating |
| Orbital diameter [mm] | 20 |
| Permissible shaking weight (incl. attachment) [kg] | 7.5 |
| Motor rating input [W] | 45 |
| Motor rating output [W] | 10 |
| Permissible ON time [%] | 100 |
| Speed min (adjustable) [1/min] | 20 |
| Speed range [1/min] | 0 - 300 |
| Speed display | LED line |
| Timer | yes |
| Timer display | LED line |
| Time setting range [min] | 5 - 50 |
| Operating mode | timer and continuous operation |
| Shaking table lock | no |
| Dimensions (W x H x D) [mm] | 360 x 100 x 420 |
| Weight [kg] | 8.5 |
| Permissible ambient temperature [°C] | 5 - 50 |
| Permissible relative moisture [%] | 80 |
| Protection class according to DIN EN 60529 | IP 21 |
| RS 232 interface | no |
| Analog output | no |
| Voltage [V] | 220 - 240 / 100 - 120 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 45 |
| **Ident. No.** | **3066600** |

© IKA® Werke Staufen/Germany 2008 www.ika.net
Subject to technical changes

**Artisan Technology Group** is an independent supplier of quality pre-owned equipment

## Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

## Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP