ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *IKA HS 260* at our website: *Click HERE*

Data Sheet
Mixing / Shakers



HS 501 digital

Low profile laboratory shaker with a pleasant design, large mounting surface and load capacity of up to 15 kg.
- Infinitely variable speed control of 0 - 300 rpm
- Digital display
- Orbital diameter 30 mm
- Ideal for all lying vessels, e.g. separating funnels
- Guaranteed continuous operation (endless) even under extreme loads
- Includes timer
- Attachments are not included in delivery, please order separately

Accessories: AS 501.5 Dish attachment, H 11 Mains cable UK plug, H 11 Mains cable USA plug, H 11 Mains cable Euro plug, AS 501.4 Fixing clip support, AS 501.2 Seperating funnel attachment, AS 501.3 Seperating funnel attachment, H 11 Mains cable CH plug, AS 501.1 Universal attachment, AS 501.6 Seperating funnel attachment, AS 2.5 Fixing clips, AS 2.4 Fixing clips, AS 2.3 Fixing clips, AS 2.2 Fixing clips, AS 2.1 Fixing clips

Technical Data	
Type of movement	reciprocating
Orbital diameter [mm]	30
Permissible shaking weight (incl. attachment) [kg]	15
Motor rating input [W]	70
Motor rating output [W]	19
Permissible ON time [%]	100
Speed range [1/min]	0 - 300
Speed display	LED
Timer	yes
Timer display	scale
Time setting range [min]	1 - 56
Operating mode	timer and continuous operation
Shaking table lock	no
Dimensions (W x H x D) [mm]	505 x 120 x 585
Weight [kg]	26
Permissible ambient temperature [°C]	5 - 50
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
RS 232 interface	no
Analog output	no
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	74
Ident. No.	**2527000**

© IKA® Werke Staufen/Germany 2008 www.ika.net
Subject to technical changes
Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP