ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *IKA KMO 2* at our website: *Click HERE*

Data Sheet

Mixing / Magnetic Stirrers



KMO 2 basic IKAMAG®

Small, powerful magnetic stirrer without heating.
- Strong magnetic field
- Motor with optoelectronic speed control
- Infinitely variable speed from 0 - 1,100 rpm
- Stainless steel casing facilitates cleaning and sterilization
- Includes M 10 thread for H 16 V support rod

Accessories: H 38 Holding rod, H 16.1 Extension, H 16 V Support rod, H 44 Boss head clamp, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 15 Magnetic stirring bar, IKAFLON® 20 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 40 Magnetic stirring bar, IKAFLON® 50 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, TRIKA® 40 Magnetic stirring bar, RS 1 Set of magnetic stirring bars, RSE Stirring bar remover

Technical Data	
Number of stirring positions	1
Stirring quantity max. per stirring position (H2O) [l]	5
Stirring quantity max. (H2O) [l]	5
Motor rating input [W]	14
Motor rating output [W]	4
Speed range [1/min]	0 - 1100
Stirring bar length max. [mm]	50
Set-up plate material	stainless steel 1.4301
Set-up plate dimensions [mm]	140 x 120
Dimensions (W x H x D) [mm]	140 x 75 x 200
Weight [kg]	1.4
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	20
Ident. No.	**2812000**

© IKA® Werke Staufen/Germany 2008 www.ika.net
Subject to technical changes

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP