ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *IKA KS 260* at our website: *Click HERE*

Data Sheet
Mixing / Shakers



KS 130 basic

Small, quiet shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 2 kg.
- Electronic adjustment of speed and timer
- LED display for speed and time adjustment
- Wide range of attachment combinations makes it possible to use almost all shapes and sizes of vessels
- Attachments are not included, please order separately

Accessories: AS 130.2 Fixing clip attachment, H 11 Mains cable UK plug, H 11 Mains cable USA plug, H 11 Mains cable Euro plug, AS 130.4 Test tube support, AS 130.1 Universal attachment, H 11 Mains cable CH plug, AS 130.3 Dish attachment, AS 2.5 Fixing clips, AS 2.4 Fixing clips, AS 2.3 Fixing clips, AS 2.2 Fixing clips, AS 2.1 Fixing clips

Technical Data	
Type of movement	orbital
Orbital diameter [mm]	4
Permissible shaking weight (incl. attachment) [kg]	2.0
Motor rating input [W]	45
Motor rating output [W]	10
Permissible ON time [%]	100
Speed min (adjustable) [1/min]	80
Speed range [1/min]	0 - 800
Speed display	LED line
Timer	yes
Timer display	LED line
Time setting range [min]	5 - 50
Operating mode	timer and continuous operation
Shaking table lock	no
Dimensions (W x H x D) [mm]	270 x 98 x 316
Weight [kg]	8.8
Permissible ambient temperature [°C]	5 - 50
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
RS 232 interface	no
Analog output	no
Voltage [V]	220 - 240 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	45
Ident. No.	**2980000**

© IKA® Werke Staufen/Germany 2008 www.ika.net
Subject to technical changes
Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP