ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Ingersoll Rand 93504-1* at our website: *Click HERE*

Downstream Fluid Regulators

Model Number	Base Housing	Seat	Regulated Pressure Range PSI (bar)	Working Pressure W/Gauge PSI(bar)	Maximum Inlet Pressure PSI (bar)	Gauge Pressure Range PSI (bar)
3/8" ports, standard flow to 3 GPM (11.4 liters)						
Gauge Included.						
651780-A1A-B	C/S	T/C	400-1,250 (28-86)	–	3,000 (207)	–
651780-A1B-B	C/S	T/C	1,000-3,000 (69-207)	–	6,000 (414)	–
651780-A3A-B	S/S	T/C	400-1,250 (28-86)	–	3,000 (207)	–
651780-A3B-B	S/S	T/C	1,000-3,000 (69-207)	–	6,000 (414)	–
3/8" ports, high-flow to 6 GPM (22.7 liters)						
Gauge Included.						
651790-B1D-B	Z/A	T/C	30-200 (2-14)	600 (41.4)	1250 (86)	0-300 (0-20)
651790-B1E-B	Z/A	T/C	100-800 (7-55)	1,250 (86.2)	1250 (86)	0-1,000 (0-69)
651790-B3D-B	S/S	T/C	30-200 (2-14)	600 (41.4)	1250 (86)	0-300 (0-20)
651790-B3E-B	S/S	T/C	100-800 (7-55)	1,250 (86.2)	1250 (86)	0-1,000 (0-69)
Gauge Not Included.						
651780-B1A-B	C/S	T/C	400-1,250 (28-86	–	3,000 (207)	–
651780-B1B-B	C/S	T/C	1,000-3,000 (69-207)	–	6,000 (414)	–
651780-B3A-B	S/S	T/C	400-1,250 (28-86)	–	3,000 (207)	–
651780-B3B-B	S/S	T/C	1,000-3,000 (69-207)	–	6,000 (414)	–
3/4" ports, mastic-flow to 20 GPM (75.7 liters)**						
Gauge Not Included.						
651780-C1C-B	C/S	T/C	2,000-3,000 (138-345)	–	6,000 (414)	–
651780-C3B-B	S/S	T/C	750-2,500 (52-172)	–	6,000 (414)	–
3/8" ports, remote models, flow to 6 GPM (22.7 liters)						
Gauge Not Included.						
****651790-B4R-B**	S/S	3/S	30-200 (2-14)	50 (34)	–	–
651780-B1R-B	C/S	T/C	400-5,000 (14-345)	–	6,000 (414)	-
651780-B3R-B	S/S	T/C	400-5,000 (14-345)	–	6,000 (414)	-

** Flow rates tested in 30 wt. oil.

Model Number	Base Housing	Seat	Regulated Pressure Range PSI (bar)	Working Pressure W/Gauge PSI(bar)	Maximum Inlet Pressure PSI (bar)	Gauge Pressure Range PSI (bar)
3/4" ports, remote models, mastic-flow to 20 GPM (75.7 liters)**						
Gauge Not Included.						
651780-C1R-B	C/S	T/C	750-5,000 (52-345)	–	6,000 (414)	–
651780-C3R-B	S/S	T/C	750-5,000 (52-345)	–	6,000 (414)	–

** Flow rates tested in 55 CPS material.



3/8" Ports Model



3/4" Ports Model



High Pressure Remote Model

Material Codes

Code	Description
3/S	300 Series Stainless Steel
4/S	400 Series Stainless Steel
C/S	Carbon Steel

Code	Description
T/C	Tungsten Carbide
S/S	Stainless Steel
Z/A	Zinc Aluminum
Z	Zinc

Adapters

For mounting gauges on high pressure fluid regulators

Model	Port Size	Type
92968	3/8"	Dual Outlet Ports
92969	3/8"	Single Outlet Ports

Gauges

Model	Material	Max. Gauge Press. PSI (Bar):	Thread Size:
29975	Brass or Aluminum	160 (11)	1/8" (M)
29882	Brass or Aluminum	60 (4)	1/8" (M)
29883	Brass or Aluminum	160 (11)	1/8" (M)
29916	Stainless Steel	0-3000 (0-204)	1/8" (M)
100090	Brass	60 (4)	1/4" (M)
65107	Stainless Steel	0-100 (0-7)	1/4" (M)
100067	Brass or Aluminum	160 (11)	1/4" (M)
100083	Brass or Aluminum	300 (21)	1/4" (M)
93504-1	Stainless Steel	0-1000 (0-70)	1/4" (M)
93505-1	Brass or Aluminum	0-3000 (0-204)	3/8" (M)
93506-1	Stainless Steel	0-3000 (0-204)	3/8" (M)
93507-1	Brass or Aluminum	0-5000 (0-340)	3/8" (M)

Get in the ZONE (IR) ARO

Automatic Extrusion Guns

Model Number	Description	Pumps Used With		Port Size In. NPT		Working Pressure PSI (Bar)
651511	**Flow Gun -** Requires 4-way air valve to open and close. Adjusting screw varies stroke length. Secures to 1/2" diameter rod by allen screw. Aluminum body with tungsten carbide seats. Order 66541-XX Extrusion Nozzle Kit separately.	5000 (345)	3/8 NPT (F) (2)	.250 (6) & 11/16-16 (M)	(2) 1/8 F	50 (3.4) at 2000 PSI (138 bar) fluid pressure
651513-11-B	**Flow Gun -** Has air open, spring return cylinder. Requires 3-way air valve to open. Adjusting screw varies stroke length. Secures to 1/2" diameter rod by allen screw. 316 stainless steel with tungsten carbide seat. Order 66541-XX Extrusion Nozzle Kit separately.	5000 (345)	1/4 NPS (M)	.093 (2.3) & 11/16-16 (M)	1/8 (F)	50 (3.4) at 2000 PSI (138 bar) fluid pressure
651536-1	**Snuff-Back Gun -** High flow automatic dispensing gun is designed to handle high-viscosity materials. Requires a 4-way air valve to open and close.	5000 (345)	3/8 NPT (F) (2)	1/4 NPT (F)	(2) 1/8 NPT (F)	
651537-1	**Flow Gun -** Similar to 651511 except with carbon steel body and has ball seat located at material inlet and of valve seat assembly.	5000 (345)	3/8 NPT (F)	3/8 18 (M)	(2) 1/8 NPT (F)	50 (3.4) at 2000 PSI (138 bar) fluid pressure



651511



651513

Extrusion Gun Nozzle Kits

Model Number	Orifice Diameter	Model Number	Orifice Diameter	Model Number	Orifice Diameter
66541-XX	**Extrusion Nozzle Kit -** Used on manual or automatic extrusion guns. Hardened steel assembly includes nozzle and cap. 11/16-16 UN(F).				
66541-3	.031	**66541-9**	.093	**66541-17**	.172
66541-4	.046	**66541-12**	.125	**66541-18**	.187
66541-6	.063	**66541-15**	.156	**66541-25**	.250
				66541-37	.375



66541-XX

Material Filters

Model Number	Maximum Fluid Pressure PSI (Bar)	Filter Mesh	Filter Microns	Filter Inlet(s) Size (Qty) NPT	Filter Outlet(s) Size (Qty) NPT
1/4" fluid inlet/carbon steel construction					
651412 SAVE	5,000 (345)	70	200	1/4-F (2)	1/4-F (3) Bottom
1/2" fluid inlet/stainless steel construction (passivated)					
651422-40	6,000 (414)	40	375	1/2-F (2)	1/2-F (1)
651422-70	6,000 (414)	70	200	1/2-F (2)	1/2-F (1)
651422-100	6,000 (414)	100	149	1/2-F (2)	1/2-F (1)
1/2" fluid inlet/carbon steel construction (e-nickel plated)					
651420-40	6,000 (414)	40	375	1/2-F (2)	1/2-F (1)
651420-70	6,000 (414)	70	200	1/2-F (2)	1/2-F (1)
651420-100	6,000 (414)	100	149	1/2-F (2)	1/2-F (1)
651421-70	6,000 (414)	Dual Screens		1-8	3/4-F (1)
1" fluid inlet/carbon steel construction (e-nickel plated)					
651418-40-B	6,000 (414)	40	375	1-F (2)	3/8-F (3)
651418-70-B	6,000 (414)	70	200	1-F (2)	3/8-F (3)
651418-100-B	6,000 (414)	100	149	1-F (2)	3/8-F (3)



651418-XX-B



651412-



651420-XX-B

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP