

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Instek GAG-810* at our website: *Click HERE*

RF Generator / Audio Generator





GRG-450B (RF GENERATOR)

FEATURES

* Frequency Range from 100kHz ~ 150MHz (up ~ 450MHz on Harmonics)
* Int/Ext AM Modulation, 0 ~ 100%
* Frequency Monitor Output for EXT Frequency Counter

SPECIFICATIONS

MAIN OUTPUT	
Frequency	100kHz ~ 150MHz (up to 450MHz on harmonics)
Range	A 100 ~ 290kHz B 290 ~ 900kHz C 0.9 ~ 3.0MHz D 3.0 ~ 11MHz E 10 ~ 35MHz F 32 ~ 150MHz (96 ~ 450MHz, calibrated harmonics)
Accuracy	±5%
Level	100mVrms approx up to 35MHz
Level control	High/Low switchable and fine control
AMPLITUDE MODULATION	
Internal	Frequency: 1kHz Percentage: 30% max and adjuster
External	Frequency: 50Hz to 20kHz Sensitivity: less than 1Vrms
AUX OUTPUT	Audio Output Frequency: 1kHz Level: 1 Vrms MIN, fixed
FREQUENCY MONITOR	Frequency: Oscillation frequency Level: 50mVrms MIN
POWER SOURCE	AC 100/115/230V ±10% , 50/60Hz
ACCESSORIES	Instruction manual x 1, Power cord x 1, GTL-110 x 1
DIMENSIONS & WEIGHT	247(W) x 158(H) x 140(D)mm, Approx. 2.5kg

ORDERING INFORMATION

GRG-450B	150MHz RF Generator

GAG-809/810 (AUDIO GENERATOR)

FEATURES

* Frequency from 10Hz ~ 1MHz
* 0.02% Low Sine wave Distortion (GAG-810 Only)
* 6 Steps Output Attenuator
* EXT SYNC Function

SPECIFICATIONS

SINE WAVE CHARACTERISTIC	
Frequency Range	10Hz ~ 1MHz, 5 Ranges
Frequency Indicator	Dial Scale
Frequency Accuracy	±(3% + 1Hz)
Output Voltage	5 Vrms (600Ω load)
Frequency Response	10Hz ~ 1MHz±0.5dB(at 600Ω load) Reference Frequency (1kHz)
Distortion Factor	500Hz ~ 20kHz 0.02% or less (GAG-809 0.1%) 100Hz ~ 100kHz 0.05% or less (GAG-809 0.3%) (x 10 range for 100Hz, x 1k range for 100kHz) 50Hz ~ 200kHz 0.3% or less 20Hz ~ 500kHz 0.5% or less 10Hz ~ 1MHz 1.5% or less
SQUARE WAVE	
Output Voltage	10Vp-p or more (no load)
Overshoot	2% or less (at 1kHz, max output)
Rise & Fall Time	Less than 200nS
Duty Ratio	50%±5%
EXT. SYNCHRONIZATION	
Synchronizing Range	±1%/Vrms
Max. Allowable Input	15V (DC + AC peak)
Input Impedance	150k ohm
OUTPUT	
Output Impedance	600Ω
Output Attenuator	0, -10, -20, -30, -40, -50dB 6 ranges (accuracy±1dB at 600Ω load)
POWER SOURCE	AC 100/120/220/230V±10% , 50/60Hz
ACCESSORIES	Instruction Manual x 1, Power cord x 1, GTL-103 x 1
DIMENSIONS & WEIGHT	130(W) x 210(H)x292(D)mm , Approx 3 kg

ORDERING INFORMATION

GAG-809	1MHz Audio Generator
GAG-810	1MHz Audio Generator with 0.02% Low Sine Wave Distortion

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP