ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Instek GOM-802* at our website: ***Click HERE***

D.C. Milli-Ohm Meter



GOM-802

FEATURES

* 30000 Counts Display
* High Accuracy 0.05%
* Hi/Lo Comparator and Limit Percent Setting
* Measurement of REL, Actual and % Value
* Continuous or Triggered Measurement Mode
* Temperature Compensation and Measurement
* Four-Terminal Measurement Technique
* Auto-Recall Last Setting After Power OFF and ON Again
* Alarm Setting for PASS/FAIL
* Scan, Handler Interface (Standard)
* Manual or Autoranging
* RS-232C+GPIB (Option)

SPECIFICATIONS

DISPLAY	30,000 counts
RESISTANCE	
Ranges/Test Current (Fixed)	30mΩ/1A | 300mΩ/100mA | 3Ω/100mA 30Ω/10mA | 300Ω/1mA | 3kΩ/100μA 30kΩ/100μA | 300kΩ/10μA | 3MΩ/1μA
Accuracy	30mΩ : ± 0.1% reading + 6 digits 300mΩ : ± 0.05% reading + 6 digits 3Ω : ±0.05% reading + 3 digits 30Ω ~ 3MΩ : ±0.05% reading + 2 digits
Resolution	1μΩ , 10μΩ , 100μΩ , 1mΩ , 10mΩ , 100mΩ , 1Ω , 10Ω , 100Ω
TEMPERATURE	
Ranges	-50° C ~ 100° C
Accuracy	-10° C ~ 40° C : 0.3% + 0.5° C other : 0.3% + 1.0 °C
Resolution	0.1° C
FUNCTION	Hi/Lo, Go/No-Go, Manual Trigger, Actural, %, Diode, Temp, TC for Transformer
MEASURING RATE	7 measuring / sec at 30,000 counts, 30 measuring / sec at 3,000 counts
MEMORY	20 sets
INTERFACE	
Standard	Handler / Scan (same connector)
Option	RS-232C+GPIB
POWER SOURCE	AC 100/120/220/230V ± 10%
ACCESSORIES	Instruction manual x 1 Power cord x 1 GTL-108A x 1
DIMENSIONS & WEIGHT	251(W) x 91(H) x 291(D)mm, Approx. 3kg

ORDERING INFORMATION

GOM-802 High Precision Programmable DC Milli-Ohm Meter

Option

Opt.1 RS-232C + GPIB Interface

Opt.2 PT-100 Platinum Temperature Probe



GOM-801G

FEATURES

* Measures from 20mΩ ~ 20kΩ in 7 Ranges
* 1A High Test Current
* High Resolution 10μΩ
* Hi/Lo Comparator Indicator
* 3 1/2 Digits 0.5" LED Display

SPECIFICATIONS

TEST RANGE	20, 200mΩ, 2, 20, 200Ω, 2k, 20kΩ, 7 Ranges
TEST CURRENT	DC 10μA ~ 1A
ACCURACY	Measuring 20mΩ ± (0.2% rdg + 6 digits) 200mΩ ~ 20kΩ ± (0.2% rdg + 4 digits) Setting ± (0.2% + 6 digits)
RESOLUTION	0.01, 0.1, 1, 10, 100mΩ , 1, 10Ω
COMPARATOR	HI, LO setable
DISPLAY	3 1/2 digits 0.5" LED display HI, GO, LO indicator
POWER SOURCE	AC 115V/230V ±10% , 50/60Hz
ACCESSORIES	Instruction manual x 1 Power Cord x 1 Test Lead GTL-108A x 1
DIMENSIONS & WEIGHT	230(W) x 95(H)x280(D)mm, Approx. 2 kg

ORDERING INFORMATION

GOM-801G High Precision Programmable DC Milli-Ohm Meter

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP