

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*



GPT-705A/715A & GPI-725A/735A

Patent No : 074646



GPI-745A

CE | RS-232 | GPIB | SCAN | Remote I/O | Real-Panel Output | PC Software

Patent No:074646

The GPT/GPI-700A Series is a universal Safety Tester, compliant to all major safety standards such as UL, CSA, JIS, and BS. The operation interface has been carefully designed making it user-friendly and fully automatic, to ensure safety and to produce reliable test results. The advanced and versatile GPT/GPI-700A Series can be used in production lines, workshops, laboratories, and test sites.
Users can select from 5 models according to the testing requirement - starting from the simple 705A for AC Withstanding, through middle range GPI-725A for AC Withstanding + Insulation Resistance, up to the most advanced GPI-745A for AC Withstanding + DC Withstanding + Insulation Resistance + Ground Bond. Each model has remote control terminal and programming function which deliver fast and reliable test results.


FEATURES

* 200VA AC Test Capacity
* AC/DC Withstanding Voltage Test & Insulation Resistance Test
* True RMS Cut-Off Current Measurement
* Arc Detection
* Zero Crossing Turn-On Operation Switch
* Linear Amplifier with Feedback Control to Provider High Regulated Voltage Output
* Controllable Ramp-Up Time
* Output Voltage and Current Limit Could be set Without HV Output
* Output Voltage Adjustable During Test Period
* 9 pins Remote Control for START, RESET, and Test Result Output
* Automatic FAIL Indicator of Alarm Lamp and Buzzer
* Scanner Box for Automatic Test (Option)
* 42A Ground Bond Test (GPI-745A only)

SPECIFICATIONS

AC HI-POT	
Voltage Range	0.100kV ~ 5.000kV
Voltage Resolution	5V/step
Voltage Regulation (Line and Load)	1% + 5 V
Voltage Accuracy	± (1% rdg ±10V)
Max. Current Sourcing	30mA ~ 40mA (above 500V, maximum test time:180sec.) 0.10mA ~ 29.99mA (above 500V, continuous test) 0.10mA ~ 10mA (below 500V, continuous test)
Current Limit	0.10 ~ 40mA, 0.02mA/step
Current Accuracy	± (1% rdg ± 80μA)
DC HI-POT (GPT-715A/GPI-735A/GPI-745A)	
Voltage Range	0.100kV ~ 6.000kV
Voltage Resolution-Output	5V/step
Voltage Regulation (Line and Load)	1% + 5 V
Voltage Accuracy	± (1% rdg ±10V) (above 500V)
Max. Current Sourcing	0.10mA ~ 10.00mA (above 500V, continuous test) 0.10mA ~ 2mA (below 500V, continuous test)
Current Limit	0.10mA ~ 10mA, 0.01mA/step
Current Accuracy	±(1% rdg ± 50μA)
INSULATION RESISTANCE (GPI-725A/GPI-735A/GPI-745A)	
DC Voltage	50V/100V/500V/1000V
Resistance Range	1~9900MΩ(500V, 1000V); 1~2000MΩ (50V, 100V)
Resistance Accuracy (50V/100V)	1MΩ~50MΩ : ± (5% rdg ±1count) 51MΩ~200MΩ : ± (10% rdg ±1count) 201MΩ~2000MΩ : ± (20% rdg ±1count)
Resistance Accuracy (500V/1000V)	1MΩ~500MΩ : ± (5% rdg ±1count) 501MΩ~2000MΩ : ± (10% rdg ±1count) 2001MΩ~9500MΩ : ± (20% rdg ±1count)
GROUND BOND (GPI-745A)	
Voltage Range	Max. 8V (DC)
Current Range	3~42A
Current Resolution	0.02A
Current Accuracy	± 1% of reading ±0.2A (3A~8A); ± 1% of reading ± 50mA (9A~42A)
Ground Bond Resistance Test	0~600mΩ
Resistance Resolution	0.1mΩ
Resistance Accuracy	± 1% of reading ±3mΩ
Test Method	Four terminal test mode
CONTINUITY CHECK (GPT-705A/715A & GPI-725A/735A)	
Output Current Range	0.1A (DC)
Compliance Voltage Range	10%
Resolution	0.1Ω @ 1Ω
RAMP TIME & TEST TIME	
AC Hi-Pot Ramp/Test Time	000.0 ~ 999.9 seconds
DC Hi-Pot Ramp/Test Time	000.0 ~ 999.9 seconds
Insulation Resistance Test Time	001.0 ~ 999.9 seconds
Ground Bond Test Time	000.0 ~ 999.9 seconds
Continuity Check Test Time	000.0 ~ 999.9 seconds
ARC DETECT	
Detect Current	40 level (1 ~ 40mA)
MEMORY	
	Groups : 10, steps per group : 16
INTERFACE	
Remote I/O	Standard
RS-232C	Standard
Scan	Standard
GPIB	Option
Real Panel Output	Standard (only GPI-745A)
POWER SOURCE	
AC100V/120V/220V/230V ±10% , 50/60Hz	
DIMENSIONS & WEIGHT	
330(W) x 149(H) x 446(D) mm, Approx. 14kg	

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com



GPI-735A

Rear Panel



ORDERING INFORMATION

GPI-745A	AC 200VA AC/DC Withstanding Voltage/Insulation/Ground Bound Electrical Safety Tester
GPI-735A	AC 200VA AC/DC Withstanding Voltage / Insulation Electrical Safety Tester
GPI-725A	AC 200VA AC Withstanding Voltage / Insulation Electrical Safety Tester
GPT-715A	AC 200VA AC/DC Withstanding Voltage Electrical Safety Tester
GPT-705A	AC 200VA AC Withstanding Voltage Electrical Safety Tester

ACCESSORIES :
User manual x 1 , Power cord x 1
GHT-105A x 1 for GPT-705A/GPT-715A/GPI-725A/GPI-735A ; GHT-105A x 1, GTL-115A x 1 for GPI-745A

Option

Opt.01 GPIB Interface (Factory Installed)
Opt.04 HSB-001-1 Scanner Box, 8CH HV and 8CH GB
Opt.05 HSB-001-2 Scanner Box, 16CH HV

Option Accessories

GHT-107A	Clip High Voltage Probe
GHT-108	High Voltage Wiring Cable for HSB-001-1
GHT-109	Ground Bond Wiring Cable or HSB-001-1
GHT-110	Communication Cable for HSB-001-1/HSB-001-2
GHT-113	High Voltage Test Pistol
GRA-402	Rack Adapter Panel (19",4U)
GRA-406	Rack Adapter Panel (19",3U) for HSB-001-1/HSB-001-2
GTL-232	RS232C Cable, 9-pin Female to 9-pin, null Modem for Computer

NOTE : GPT/GPI-7 x 5A Series can control only one scanner box.

SELECTION GUIDE


MODEL \ FUNCTION	AC	DC	IR	GB
GPT-705A	✓			
GPT-715A	✓	✓		
GPI-725A	✓		✓	
GPI-735A	✓	✓	✓	
GPI-745A	✓	✓	✓	✓


SCANNER BOX

HSB-001-1
8CH HV + 8CH GB
For: GPT/GPI-700A Series

HSB-001-2
16CH HV
For: GPT/GPI-700A Series

Can be installed into rack by adding two option handles.

(Rear Panel)

(Front Panel)

GHT-108
High Voltage Wiring Cable
For : HSB-001-1



GHT-109
Ground Bond Wiring Cable
For : HSB-001-1



GRA-406 Rack Adapter Panel
For : HSB-001-1, HSB-001-2
Rack Mounting (19",3U)



GHT-113
HIGH VOLTAGE TEST PISTOL

* Housing of unbreakable plastic
* Operation voltage 10kVDC/8kVAC max.
* Connecting via highly flexible safety cable
* Power supply line approx. 2m
* Wear-resistant tungsten test probe tip
* Teflon sleeve for resistance to burning

For : GPT/GPI-800A Series, GPT/GPI-700A Series



GHT-107A Clip High Voltage Probe

For : GPT/GPI-800A Series, GPT/GPI-700A Series



Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP