

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Interface Advanced Force Measurement CX-0220* at our website: ***Click HERE***

Precision mV/V Load Cell Simulator

- **Most accurate load cell simulator**
- **Special low thermal emf construction**
- **Each unit individually calibrated, aged and recalibrated**
- **Strong, rugged design**
- **Instrument substitution testing**



CX-0610



CX-0440

Models CX-0202, CX-0610, CX-0440, CS-0330, and CX-0220 are used for setting up and checking the Gold Standard™ System Hardware. CX-0440, CX-0330, and CX-0220 are single-step mV/V transfer standards providing precision outputs of ±4, ±3, and ±2 mV/V respectively. CX-0610 is a multi-step unit that allows the user to go from -6 mV/V to +6 mV/V in 1 mV/V steps.

Model CX-0404 is specifically designed for instrument substitution testing as per ASTM E74.

Specification	CX-0404 Multi-Step Model	CX-0610 Multi-Step Model	CX-0440 Single-Step Model	CX-0330 Single-Step Model	CX-0220 Single-Step Model
Output at zero setting	< 0.5 µV	< 0.5 µV	< 1.0 µV	< 1.0 µV	< 1.0 µV
Output settings–mV/V	0, ±0.04, ±0.08, ±0.2, ±0.4, ±0.8, ±1.2, ±1.6, ±2.0, ±2.4, ±3.2, ±4.0, ±4.4	-6, -5, -4, -3, -2, -1, +1, +2, +3, +4, +5, +6	-4, +4	-3, +3	-2, +2
Output accuracy at any non-zero setting, normalized to actual zero setting output:					
Relative to nominal value	0.01% to 0.05% of setting	0.01% of setting	0.01% of setting	0.01% of setting	0.01% of setting
Relative to value provided in unit-specific calibration chart	0.0015% of setting for one year	0.0015% of setting for one year	0.0025% of setting for one year	0.0025% of setting for one year	0.0025% of setting for one year
Temperature coefficient of normalized output	< 5 ppm/°C of setting	< 5 ppm/°C of setting	< 5 ppm/°C of setting	< 5 ppm/°C of setting	< 5 ppm/°C of setting
Input and output resistance:					
At zero setting	350 ohms ±0.005%	350 ohms ±0.005%	350 ohms ±0.005%	350 ohms ±0.005%	350 ohms ±0.005%
At output setting (value decreases with increasing setting, either polarity)	> 347.5 ohms	> 347.5 ohms	> 348.5 ohms	> 348.5 ohms	> 348.5 ohms

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP