ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *VIAVI Solutions / JDSU MTA 300* at our website: *Click HERE*



MTA Series

The JDS Uniphase Attenuator Shelf holds up to eight attenuators and one control cassette in a low profile 19 inch (48.26 cm) rack-mounting shelf. It is ideal for controlling the optical launch conditions of DWDM system test beds and offers the lowest cost per channel for DWDM applications. It is optimized for the 1550 nm window but can be used over the 1200-1700 nm range with resolution of 0.05 dB nominal and accuracy better than ± 0.1 dB.

The system is designed to provide standard 60 dB attenuation range with good resolution for power equalization applications such as eight-channel DWDM systems. The inherent linear design and low polarization sensitivity allow the attenuators to be inserted directly at the output of an array of laser sources to stabilize or adjust optical power for each channel. Each attenuator cassette is available with a retractable connector plate to facilitate connector cleaning and maintenance and a beam block to simulate broken fiber conditions.

The shelves can be stacked to provide higher channel testing capacities, such as 16, 32, and 40 channels.

Each attenuator is controlled from the front panel keypad or by the GPIB remote interface. The commands are SCPI compatible, and LabVIEW drivers simplify remote control. The individual attenuators are etalon-free for low distortion and feature low polarization dependent loss (PDL) and return loss.

Key Features & Benefits

Holds up to eight programmable attenuator cassettes in one shelf

0.05 dB resolution

Low polarization sensitivity

One attenuator per channel

Remote control

Beam blocking switch

CE and cULus compliant

Applications

Adjust detectors in DWDM systems to their optimal dynamic range

Develop and test power equalization between eight-channel DWDM systems

Reduce or test excessive channel signal-to-noise ratios after optical amplification

Factory testing of multichannel transmission equipment

General test systems requiring multiple attenuators

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Technical Specifications

PARAMETER		SPECIFICATION
MTA300 ATTENUATOR CASSETTE		
Operating wavelength range		1200-1700 nm
Fiber type		9/125 µm
Attenuation	range	> 60 dB
	resolution	0.05 dB nominal
	repeatability[1]	± 0.005 dB typical, ± 0.02 dB maximum
	change rate	< 6 s, 0-60 dB
	accuracy	± 0.05 dB typical, ± 0.1 dB maximum
Insertion loss[2, 3]		2.2 dB typical, ≤ 2.5 dB maximum
Return loss[2, 3]		> 60 dB typical, > 57 dB maximum
Maximum optical input power		200 mW
Recalibration period (recommended)		2 years
Polarization dependent loss		≤ 0.05 dB typical, ≤ 0.10 dB maximum
Polarization dependent loss at 1545-1565 nm		≤ 0.03 dB typical, ≤ 0.05 dB maximum
Beam block isolation		> 90 dB
Beam block speed		< 20 ms
MTA150 CONTROL CASSETTE		
Local control		front panel keypad and LCD display
Remote control		GPIB
Command set		SCPI compatible
MTA100 AC POWERED RACK-MOUNT SHELF		
Input voltage		100-240 V AC, 50-60 Hz
Power consumption		80 VA maximum
Dimensions W x H x D		48.3 x 8.9 x 49.7 cm
19 inch rack mounting		2U high, standard 19 inch (48.26 cm) width
Weight		approximately 16 kg
Operating temperature		0 to 40 °C
Storage temperature		- 40 to 60 °C
Humidity		maximum 95 % up to 40 °C decreasing at 5 % per °C from 40 to 60 °C

1. At constant temperature, wavelength, and polarization state after half hour warm-up.
2. Measured at 23 °C with a laser source.
3. Including two SC/APC connectors.

Sample Order: MTAS7+1001SU1

MTAS7+1 ☐ ☐ ☐ ☐ ☐ ☐

code	rack-mount shelf
0	No
1	Yes

code	control cassette
0	No
1	Yes

code	cassettes
0	No
1	Yes

code	connector type
FP	FC/HPC
FA	FC/APC
SC	SC/HPC
SU	SC/APC
SP	ST/HPC
NC	No connector

code	port type (on front)
1	Bulkheads
3	Pigtails
N	Not applicable

Ordering Information

Indicate your requirements by selecting one option from each configuration table. Print the corresponding codes in the available boxes to form your part number.

LabVIEW is a registered trademark of National Instruments Corporation.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP