ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *VIAVI Solutions / JDSU PS3650* at our website: ***Click HERE***

Polarization Dependent Loss Multimeter

The JDS Uniphase Polarization Dependent Loss Multimeter is the fastest and most accurate multimeter available. It measures polarization dependent loss (PDL) of single-mode fiberoptic components using either an internal laser or an external source. The multimeter measures the loss of a device under test for four independent input polarization states. The PDL and the average loss over all polarization states are calculated using the Mueller matrix, internationally standardized under IEC (613)00-3-12.

The multimeter easily and rapidly changes from measuring PDL and insertion loss (IL) to measuring return loss (RL) or power. The PDL and IL are measured and displayed simultaneously in less than two seconds.

The multimeters have a sophisticated optical design that compensates for changes in optical power at the internal reference detector. The design ensures accurate loss measurements regardless of drift in the source power or the coupling efficiency of the input light through the polarization state controller. The integrated PDL standard source is particularly convenient for verifying the meter's calibration. An external tunable laser or two fixed laser sources can be selected for various wavelength measurements. The multimeter is ideal for PDL-sensitive components, such as isolators, DWDMs, fiber Bragg gratings (FBGs), optical circulators, switches, attenuators, couplers, and other devices for which high test accuracy and optimum production speed are crucial.

Two models are available: a single internal laser source model and a dual internal laser source model. The internal lasers available for the single internal laser source are: 980, 1310, 1480, 1550, 1625, or 1650 nm. The dual internal laser source is available with 1310/1550, 1550/1625, 1550/1650, 1480/1550 nm. Other accessories, such as detector adapters and hybrid jumpers, are also available.



Key Features & Benefits

Uses the Mueller method

Rapidly changes from PDL and IL to RL measurements

Measurements take only a few seconds

Displays IL and PDL simultaneously

External tunable source capability

GPIB and RS232 remote control

Integrated PDL standard source

Complies to CE requirements plus UL3101-1 and CAN/CSA-C22.2 No. 1010.1

Applications

Passive component qualifications

Optical attenuator specifications

Optical switch specifications

Safety Information

Complies to FDA 21CFR 1040.10 for Class I Lasers

CLASS 1
LASER PRODUCT

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Specifications

PARAMETER	PS30 x 0 AND PS36 x 0 MODELS		PS3 x 20 MODELS
Built-in laser type Fabry-Perot	1310,1480,1550,1625,1650 ± 10nm		980 ± 10nm
Fiber type	9/125 µm SM		5/125 µm Flexcor[4] 1060
IEC 61300-3-12	Polarization dependence of attenuation of a single-mode fiberoptic component: matrix calculation method		
PDL AND AVERAGE LOSS MEASUREMENTS			
Resolution	0.01, 0.001, or 0.0001 dB		
Optimization	1550 nm	1310 nm	980 nm
Absolute accuracy PDL 960-1060 nm (maximum)			± (0.005 dB + 5 % of PDL) dB
(typical)			± (0.002 dB + 1 % PDL) dB
PDL 1455-1665 nm (maximum)	± (0.005 dB + 5 % of PDL) dB	± (0.010 dB + 5 % of PDL) dB	
(typical)	± (0.002 dB + 1 % of PDL) dB	± (0.004 dB + 2 % of PDL) dB	
PDL 1250-1350 nm (maximum)	± (0.010 dB + 5 % of PDL) dB	± (0.005 dB + 5 % of PDL) dB	
(typical)	± (0.004 dB + 2 % of PDL) dB	± (0.002 dB + 1 % of PDL) dB	
L_{av} (insertion loss)	± (0.05 dB + 2 % of L_{av}) dB		
power	± 0.25 dB at - 10 dBm		
Repeatability PDL	± (0.001+ 5 % of PDL) dB		
L_{av} accuracy	± (0.001+ 2 % of L_{av}) dB		
Dynamic range[1] PDL range[2]	0-5 dB		
L_{av} (insertion loss) (InGaAs 3 mm)	> 60 dB		
GENERAL			
Input voltage	100-240 V AC, 50-60 Hz		
Power consumption	80 VA maximum		
Rack-mounting 19-inch (48.26 cm)	2 U high, half-rack width		
Dimensions W x H x D	21.2 x 8.9 x 35.5 cm		
Weight	4 kg		
Operating temperature	0 to 40°C		
Storage temperature	- 40 to 60 °C		
Humidity	maximum 95 % up to 40 °C decreasing 5 % per °C from 40 to 60 °C		
(FOR MULTIMETERS WITH RETURN LOSS OPTIONS ONLY) - PS36x0			
Resolution	1, 0.1, or 0.01 dB (For multimeters with return loss options only)		
Accuracy	± 1.0 dB		
Repeatability	± 0.7 dB		
RL range for - 15 dBm output power[3]	> 60 dB		

1. A measurement taken with output power less than - 25 dBm for the internal source and - 30 dBm (dynamic range for - 10 dBm at external input with the input fiber to the multimeter optimized for the most power) for an external source present at the multimeter's front panel detector can reduce resolution and/or accuracy.
2. Higher PDLs can be measured with reduced accuracy.
3. Output power is about 3 dB higher in RL mode than in power mode. Therefore, full RL range is obtained when the measured output power in power mode is - 18 dBm.
4. Flexcor is a trademark of Corning Incorporated.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Ordering Information

Sample Order: PS3650+25

PS3 ☐ ☐ 0+2 ☐

code	optical return loss
0	Without
6	With

code	light source wavelength (nm)
0	Without
2	980
3	1310
4	1480
5	1550
6	1625
7	1310/1550
8	1650
A	1550/1625
B	1550/1650
C	1480/1550

code	optimized wavelength (nm)
2	980[1]
3	1310
5	1550[2]

Indicate your requirements by selecting one option from each configuration table. Print the corresponding codes in the available boxes to form your part number.

1. *Only for models with a 980 nm internal source.*
2. *Standard.*

The multimeter includes: two FC/APC connectors (one at the OUT port and another at the IN port); an FC detector adapter and detector cap for the front panel detector; one FC/APC-FC/PC test jumpers and, for the RL option, a calibrated jumper; an AC power cord; and a 19-inch rack-mount kit. The GPIB and RS232 interfaces are standard.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

meters

All statements, technical information and recommendations related to the products herein are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its application. JDS Uniphase reserves the right to change at any time without notice the design, specifications, function, fit or form of its products described herein, including withdrawal at any time of a product offered for sale herein. JDS Uniphase makes no representations that the products herein are free from any intellectual property claims of others. Please contact JDS Uniphase for more information. JDS Uniphase, the JDS Uniphase logo and the JDS Uniphase Instrumentation logo are trademarks of JDS Uniphase Corporation. Other trademarks are the property of their respective holders. 2003 © JDS Uniphase Corporation. All rights reserved.
Printed in Canada.
10109642 Rev. 001 02/03

INSTRUMENTATION GROUP
E-MAIL: instruments@jdsu.com
WEB: www.jdsu.com/instrumentation

JDS Uniphase
Instrumentation

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP