ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *VIAVI Solutions / JDSU WD5555CBD-ALI2* at our website: *Click HERE*

Band Multi-Channel Modules



Key Features

- Cost effective
- Low insertion loss
- Extended temperature range
- High isolation
- Bi-directional operation
- Exceed Telcordia GR-1221 standards
- Exceptional reliability and environmental stability

Applications

- Access/enterprise networks
- Metro networks
- Transport systems


JDSU band multi-channel modules are manufactured using laser welding technology to exceed Telcordia GR-1221 requirements. These devices demonstrate low loss, temperature insensitivity, and reliable performance in any system application. They are available in east/west and multiplexer/demultiplexer configurations.

JDSU band multi-channel modules enable networks for bi-directional and unidirectional communication of coarse wavelengths within the C band. Their wide passbands and efficient filter technology provide a low-cost wavelength management solution suitable for Access and Metro markets.


Easily customizable, JDSU band multi-channel modules can be configured from a standard list of packaging and connector options.

2

Mux/Demux Configuration



East/West Configuration



Specifications

Parameter		Specification
Wavelength range		C Band 1528 nm to 1565 nm
Passband width		1533±3.5 nm, 1541±1.5 nm, 1549±1.5 nm, 1557±3.5 nm
Insertion loss[1] (any channel)	Maximum	2.0 dB
Insertion loss[1] (end to end)	Maximum	4.0 dB
Isolation[2] (adjacent channel)	Minimum	35 dB
Directivity	Minimum	45 dB
Return loss	Minimum	45 dB
Polarization dependent loss	Maximum	0.25 dB
Polarization mode dispersion	Maximum	0.1 ps
Optical power handling	Maximum	1 W
Operating temperature range		-5 to 75 °C
Storage temperature range		-40 to 85 °C
Package dimensions (W x D x H)		
CS cassette		6.86” x 5.07” x 1.38”
LGX cassette		6.36” x 5.10” x 1.15”

1. Losses include one connector.
2. Isolation values stated are for demultiplexers or the receive side of the East/West modules only.

3

Ordering Information

For more information on this or other products and their availability, please contact your local JDSU account manager or JDSU directly at 1-800-498-JDSU (5378) in North America and +800-5378-JDSU worldwide or via e-mail at customer.service@jdsu.com.

Sample: FWM-4E33SLGB2

FWM-4 □ 33S □□ B □

Code	Device
D	4 Channel Demux
M	4 Channel Mux
E	4 Channel East
W	4 Channel West

Code	Cassette
CS	CS cassette
LG	LGX cassette

Code	Bulkhead Connector[1]
2	FC/SPC
4	SC/SPC
8	ST/SPC

1. Other connectors available upon request.

Telcordia is a registered trademark of Telcordia Technologies Incorporated.

All statements, technical information and recommendations related to the products herein are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its application. JDSU reserves the right to change at any time without notice the design, specifications, function, fit or form of its products described herein, including withdrawal at any time of a product offered for sale herein. JDSU makes no representations that the products herein are free from any intellectual property claims of others. Please contact JDSU for more information. JDSU and the JDSU logo are trademarks of JDS Uniphase Corporation. Other trademarks are the property of their respective holders. ©2005 JDS Uniphase Corporation. All rights reserved. 10143029 Rev. 001 10/05

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP