ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

**Artisan Technology Group**
(217) 352-9330 | sales@artisantg.com | artisantg.com

**Full-service, independent repair center**
with experienced engineers and technicians on staff.

**We buy your excess, underutilized, and idle equipment**
along with credit for buybacks and trade-ins.

**Custom engineering**
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

**Expert team | Trust guarantee | 100% satisfaction**

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Juniper Networks NS-5GT-001* at our website: *Click HERE*

# Juniper Networks **NetScreen-5GT Series**







The Juniper Networks NetScreen-5GT Series is a family of three feature-rich, enterprise-class network security solutions. They are ideally suited for securing remote offices, retail outlets and broadband telecommuter environments, where IT staff support is minimal and ease of configuration and management is crucial. The NetScreen-5GT Series integrates key security applications, routing protocols and resiliency features to provide IT managers a cost effective appliance that is easy to deploy and manage. All NetScreen-5GT Series offerings described below come standard with the following features:

- Security: Use the Stateful and Deep Inspection firewall, DoS protection and embedded antivirus to stop network and application level attacks and defend against the propagation of worms and viruses. Prevent users from transmitting private or corporate data, via Phishing and Spyware attacks, with integrated or re-direct web filtering options.
- Network integration: Support for key routing protocols, such as BGP, OSPF, RIPv1/2 and ECMP along with NAT, Route and Transparent Layer 2 operation helps facilitate network integration.
- Resiliency: Dial-backup or dual Ethernet ports, along with route-based VPNs provide redundancy when network connectivity is business critical. Dual WAN ports can also be used to share traffic load.
- Port Flexibility: Almost every network deployment scenario can be accommodated without a hardware upgrade through five configurable Ethernet interfaces. Administrators can enable switching, dual WAN ports, a dedicated DMZ or any combination thereof through a set of six predefined interface layouts called Port Modes.

### Juniper Networks NetScreen-5GT Ethernet

Juniper Networks NetScreen-5GT Ethernet solution is ideal for environments that need hardwired connectivity backed by robust network, application and payload level security. The NetScreen-5GT Ethernet is available with five Ethernet interfaces that can be deployed in a wide variety of configurations.

### Juniper Networks NetScreen-5GT ADSL

The Juniper Networks NetScreen-5GT ADSL adds ADSL connectivity to existing Ethernet connectivity, eliminating the need for an external ADSL modem. It provides a cost effective security and ADSL routing platform, with the same key security applications, routing protocols and resiliency features found in the Ethernet-based platforms, to help ensure network resources are not compromised.

### Juniper Networks NetScreen-5GT Wireless

The Juniper Networks NetScreen-5GT with Wireless brings enterprise-level security applications, routing protocols and resiliency features to help organizations deploy 802.11b/g networks in a secure manner. The NetScreen- 5GT Wireless offers administrators up to four configurable Wireless Security Zones (patent-pending), each with a unique SSID that can be used to provision appropriate levels of security for different types of users. To help ensure wireless security, privacy and interoperability, the NetScreen-5GT Wireless supports a broad set of wireless authentication and privacy mechanisms. The NetScreen-5GT Wireless includes standard Ethernet connectivity with ADSL as a hardware option.

| | 5GT 10 user or plus | 5GT ADSL 10 user or plus | 5GT Wireless 10 user or plus |
|---|---|---|---|
| ScreenOS version support | ScreenOS 5.3 | | |
| Firewall performance[1] | 75 Mbps | | |
| 3DES VPN performance | 20 Mbps | | |
| Deep Inspection (DI) performance | 75 Mbps | | |
| Concurrent sessions | 2000 | | |
| New sessions/second | 2000 | | |
| Policies | 100 | | |
| Interfaces | 5 10/100 Base-T, 1 Modem, and 1 Console | 5 10/100 Base-T + ADSL, 1 Modem, and 1 Console | 5 10/100 ports, 1 Wireless port with up to 4 SSIDs, 1 Modem, and 1 Console, 1 ADSL port (optional), |
| **Mode of Operation** | **5GT 10 user or plus** | **5GT ADSL 10 user or plus** | **5GT Wireless 10 user or plus** |
| Layer 2 mode (transparent mode)[2] | Yes | Yes | Yes (except with ADSL) |
| Layer 3 mode (route and/or NAT mode) | Yes | Yes | Yes |
| NAT (Network Address Translation) | Yes | Yes | Yes |
| PAT (Port Address Translation) | Yes | Yes | Yes |
| Configurable port modes | Yes | Yes | Yes |
| Dual Untrust | Yes | Yes | Yes |
| Dial back up | Yes | Yes | Yes |
| Policy-based NAT | Yes | Yes | Yes |
| Mapped IP | 300 | 300 | 300 |
| Virtual IP | 4 | 4 | 4 |
| MIP/VIP Grouping | Yes | Yes | Yes |
| Users supported | 10 or Unrestricted | | |
| IPSec passthru in NAT mode | Yes | Yes | Yes |

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

| Firewall | 5GT 10 user or plus | 5GT ADSL 10 user or plus | 5GT Wireless 10 user or plus |
|---|---|---|---|
| Number of network attacks detected | 31 | 31 | 31 |
| Network attack detection | Yes | Yes | Yes |
| DoS and DDoS protections | Yes | Yes | Yes |
| TCP reassembly for fragmented packet protection | Yes | Yes | Yes |
| Malformed packet protections | Yes | Yes | Yes |
| Deep Inspection (DI) firewall[3] | Yes | Yes | Yes |
| Protocol anomaly detection | Yes | Yes | Yes |
| Stateful protocol signatures | Yes | Yes | Yes |
| Deep Inspection (DI) signature packs (see table on page 4) | Yes | Yes | Yes |
| Content Inspection | Yes | Yes | Yes |
| Malicious Web filtering | Up to 48 URLs | | |
| External Web Filtering (Websense) | Yes | Yes | Yes |
| External Web Filtering (SurfControl) | Yes | Yes | Yes |
| Brute force attack mitigation | Yes | Yes | Yes |
| Syn cookie protection | Yes | Yes | Yes |
| DI attack pattern obfuscation | Yes | Yes | Yes |
| Zone-based IP spoofing | Yes | Yes | Yes |
| Integrated Web filtering | Yes | Yes | Yes |
| **VPN** | | | |
| Concurrent VPN tunnels | Up to 10 | | |
| Tunnel interfaces | Up to 10 | | |
| DES (56 bit), 3DES (168-bit) and AES encryption | Yes | Yes | Yes |
| MD-5 and SHA-1 authentication | Yes | Yes | Yes |
| Manual Key, IKE, PKI (X.509) | Yes | Yes | Yes |
| Perfect forward secrecy (DH Groups) | 1, 2, 5 | 1, 2, 5 | 1, 2, 5 |
| Prevent replay attack | Yes | Yes | Yes |
| Remote access VPN | Yes | Yes | Yes |
| L2TP within IPSec | Yes | Yes | Yes |
| Dead Peer Detection | Yes | Yes | Yes |
| IPSec NAT traversal | Yes | Yes | Yes |
| Redundant VPN gateways | Yes | Yes | Yes |
| VPN tunnel monitor | Yes | Yes | Yes |
| **Antivirus/Anti-Spam[4]** | | | |
| Embedded Scan Engine | Yes | Yes | Yes |
| Antivirus signatures | > 80,000 | > 80,000 | > 80,000 |
| Protocols | POP3, SMTP, HTTP, IMAP, FTP | POP3, SMTP, HTTP, IMAP, FTP | POP3, SMTP, HTTP, IMAP FTP |
| HTTP Webmail only | Yes | Yes | Yes |
| Automated Pattern file updates | Yes | Yes | Yes |
| Maximum AV Users[5] | 10 or 25 depending on user license | | |
| Embedded Anti-Spam | Yes | Yes | Yes |
| Anti phishing[8] | Yes | Yes | Yes |
| Spyware / Adware / Keylogger Protection | Yes | Yes | Yes |
| **Firewall and VPN User Authentication** | | | |
| Built-in (internal) database - user limit | up to 100 | up to 100 | up to 100 |
| 3rd Party user authentication | RADIUS, RSA, SecurID, and LDAP | | |
| XAUTH VPN authentication | Yes | Yes | Yes |
| Web-based authentication | Yes | Yes | Yes |

| Logging/Monitoring | 5GT 10 user or plus | 5GT ADSL 10 user or plus | 5GT Wireless 10 user or plus |
|---|---|---|---|
| Syslog (multiple servers) | External, up to 4 servers | | |
| E-mail (2 addresses) | Yes | Yes | Yes |
| NetIQ WebTrends | External | External | External |
| SNMP (v1, v2) | Yes | Yes | Yes |
| Standard and custom MIB | Yes | Yes | Yes |
| Traceroute | Yes | Yes | Yes |
| At session start and end | Yes | Yes | Yes |
| **Virtualization** | | | |
| Virtual routers (VRs) | 3 | 3 | 3 |
| 802.1Q VLan Tagging | Yes | Yes | Yes |
| **Routing** | | | |
| OSPF/BGP/RIPv1/v2 dynamic routing | 3 instances each | | |
| Static routes | 1024 | 1024 | 1024 |
| Source Based Routing, Source Interface Based Routing | Yes | Yes | Yes |
| Equal cost multi-path routing | Yes | Yes | Yes |
| IGMP groups | 2400 | 2400 | 2400 |
| **High Availability (HA)** | | | |
| HA Lite | Yes - with Extended License Key | | |
| Dial Backup[6] | Yes | Yes | Yes |
| Dual Untrust | Yes | Yes | Yes |
| **VoIP** | | | |
| H.323 ALG | Yes | Yes | Yes |
| SIP ALG | Yes | Yes | Yes |
| MGCP ALG | Yes | Yes | Yes |
| NAT for H.323/SIP | Yes/Yes | Yes/Yes | Yes/Yes |
| **IP Address Assignment** | | | |
| Static | Yes | Yes | Yes |
| DHCP/PPPoE/PPPOA client | Yes/Yes/No | Yes/Yes/Yes | Yes/Yes/Yes (w/ADSL) |
| Internal DHCP server | Yes | Yes | Yes |
| DHCP relay | Yes | Yes | Yes |
| **PKI Support** | | | |
| PKI certificate requests (PKCS 7 and PKCS 10) | Yes | Yes | Yes |
| Automated certificate enrollment (SCEP) | Yes | Yes | Yes |
| Online Certificate Status Protocol (OCSP) | Yes | Yes | Yes |
| Self Signed Certificates | Yes | Yes | Yes |
| Certificate Authorities Supported | Verisign, Entrust, Microsoft, RSA Keon, iPlanet (Netscape), DOD PKI, Baltimore | | |
| **RADIUS Accounting** | | | |
| RADIUS Start/Stop | Yes | Yes | Yes |
| **System Management** | | | |
| WebUI (HTTP and HTTPS) | Yes | Yes | Yes |
| Command Line Interface (console) | Yes | Yes | Yes |
| Command Line Interface (telnet) | Yes | Yes | Yes |
| Command Line Interface (SSH) | Yes, v1.5 and v2.0 compatible | | |
| NetScreen-Security Manager | Yes | Yes | Yes |
| All management via VPN tunnel on any interface | Yes | Yes | Yes |
| Rapid deployment | Yes | Yes | Yes |

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

| Administration | 5GT 10 user or plus | 5GT ADSL 10 user or plus | 5GT Wireless 10 user or plus |
|---|---|---|---|
| Local administrators database | 20 | 20 | 20 |
| External administrator database | RADIUS/LDAP/SecurID | | |
| Restricted administrative networks | 6 | 6 | 6 |
| Root Admin, Admin, and Read Only use | Yes | Yes | Yes |
| Software upgrades | TFTP/WebUI/SCP/NSM | | |
| Configuration Roll-back | Yes | Yes | Yes |
| **Traffic Management** | | | |
| Guaranteed bandwidth | Yes | Yes | Yes |
| Maximum bandwidth | Yes | Yes | Yes |
| Ingress Traffic Policing | Yes | Yes | Yes |
| Priority-bandwidth utilization | Yes | Yes | Yes |
| DiffServ stamp | Yes | Yes | Yes |
| **ADSL Support** | | | |
| ADSL over POTS | N/A | Yes | Yes (optional) |
| ADSL over ISDN | N/A | Yes | Yes (optional) |
| ADSL DMT issue 2 | N/A | Yes | Yes (optional) |
| ADSL G lite Yes No | N/A | Yes | Yes (optional) |
| Dying Gasp Support | N/A | Yes | Yes (optional) |
| Deutsche Telecom Support | N/A | Yes | Yes (optional) |
| **ADSL Layer 2 and encapsulations** | | | |
| PPPoE/PPPoA | N/A | Yes | Yes (optional) |
| 2684/1483 (Bridge and Routed Mode) | N/A | Yes | Yes (optional) |
| ATM AAL5/ATM PVCs | N/A | Yes/10 | Yes/10 (optional) |
| **Wireless Radio** | | | |
| Transmit Power | N/A | N/A | Up to 200 mW |
| Wireless Standards supported | N/A | N/A | 802.11b/g |
| Access Point Survey | N/A | N/A | Yes |
| Maximum Configured SSIDs | N/A | N/A | 8 |
| Maximum Active SSIDs | N/A | N/A | 4 |
| **Wireless Security** | | | |
| Wireless Privacy | N/A | N/A | WPA (AES or TKIP), IPSec VPN, WEP |
| Wireless Authentication | N/A | N/A | PSK, EAP-PEAP, EAP-TLS, EAP-TTLS over 802.1x |
| Additional Dial-up VPN Tunnels | N/A | N/A | 20 for 10-user and Plus, 40 for Extended |
| MAC Access Controls | N/A | N/A | Permit or Deny |
| Client Isolation | N/A | N/A | Yes |
| **Antennae options** | | | |
| Diversity Antenna | N/A | N/A | Included |
| Directional Antenna | N/A | N/A | Optional |
| Omni-directional Antenna | N/A | N/A | Optional |

| Dimensions and Power | 5GT 10 user or plus | 5GT ADSL 10 user or plus | 5GT Wireless 10 user or plus |
|---|---|---|---|
| Dimensions (H/W/L) | 1/8.25/5 inches | 1/8.25/7.25 inches | 1/8.25/7.25 inches |
| Power Supply (DC) | No | No | No |
| Weight | 1.5 lbs | 2 lbs. | 2.5 lbs. |
| Rack mountable | Yes, w/separate kit | | |
| Power Supply (AC) | 9-12VDC 12W | 12VDC 18W | |
| **Environment** | | | |
| Operational temperature | 23° to 122° F, -5° to 50° C | | |
| Non-operational temperature: | -4° to 158° F, -20° to 70° C | | |
| Humidity | 10 to 90% non-condensing | | |
| MTBF (Telecordia standard) | 32.2 Years | 26.7 Years | 23.9 Years |
| **Certifications** | | | |
| Safety Certifications | UL, CUL, CB, TUV | | |
| EMC Certifications | FCC class B, CE class B, C-Tick, VCCI class B | | |
| Common Criteria EAL4 Certification | Yes | No | No |
| FIPS 140-2, Level 2 Certification | Yes | No | No |
| ICSA Firewall and VPN | Yes | Yes | Yes |
| WI-Fi Alliance 802.11 Certification | No | No | Yes |
| WI-Fi Alliance Enterprise Certification | No | No | Yes |

(1) Performance and capacity provided are the measured maximums under ideal testing conditions. May vary by deployment and features enabled.
(2) The following features are not supported in layer 2 (transparent mode): NAT, PAT, policy based NAT, virtual IP, mapped IP, OSPF, BGP, RIPv2, and IP address assignment. Layer 2 mode is only supported in Trust/Untrust port mode.
(3) Updates to Deep Inspection signatures requires signature service which is available for additional purchase
(4) Requires additional purchase of antivirus signature and antispam detection subscriptions.
(5) Recommended number of users
(6) Tested with 3COM 5686 56K modem and ZyXel omni.net LCD ISDN modem
(7) Can be done through "site blocking" via URL filtering - whether integrated or redirect, and "inbound email blocking" via anti-spam and/or Juniper-Kaspersky embedded AV for those platforms which support it.
(8) Juniper-Kaspersky engine only.

## License Options

The NetScreen-5GT Series is available in licensing options to support different numbers of users.

| Licensing Options | Description |
|---|---|
| 10 user Product license | Limits capacity to 10 concurrent users |
| Plus Product license | Increases capacity to an unlimited number of users |
| Extended Product license | Increases sessions and VPN tunnel capacities to 4000 and 25 respectively. Adds a DMZ zone and HA lite (no session synchronization) |

## Port Modes

Port Modes provide configuration flexibility to the interface options on each of the NetScreen-5GT Series platforms. The tables below depict the different Port Mode and Tunnel zone options. A tunnel zone is an extra zone for terminating tunnel interfaces.

### NetScreen-5GT Ethernet Port Mode Options

Interfaces 5 10/100 ports, 1 Modem and 1 Console, Current ScreenOS version 5.1

| Port Mode | Availability | Trusted Wired Security Zones | Tunnel Zones |
|---|---|---|---|
| Trust-Untrust | All Licenses | 1 | 1 |
| Dual-Untrust | All Licenses | 1 | 1 |
| Home-Work | All Licenses | 2* | 1 |
| Trust\Untrust\DMZ | Extended Only | 2 | 1 |
| DMZ\Dual Untrust | Extended Only | 2 | 1 |
| Combined | All Licenses | 2* | 1 |
| Dual-Untrust-DMZ | Extended Only | 2 | 1 |
| Dual-DMZ | Extended Only | 2 | 1 |

* Home Zone Cannot Access Work Zone in Home-Work and Combined Port Modes.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

### NetScreen-5GT ADSL and NetScreen-5GT WIreless/ADSL Port Mode Options

Interfaces 5 10/100 ports, 1 ADSL port 1 Modem and 1 Console, Current ScreenOS version 5.3

| | Availability | Trusted Wired and Wireless** Zones | Tunnel Zones | Additional Wireless Security Zones** |
|---|---|---|---|---|
| Trust-Untrust | All Licenses | 1 | 1 | 1 |
| Home-Work | All Licenses | 2* | 1 | 1 |
| Extended | Extended Only | 2 | 1 | 2 |

*Home Zone Cannot Access Work Zone in Home-Work and Combined Port Modes.
** Wireless security product only

### NetScreen-5GT Wireless Port Mode Options

5 10/100 ports, 1 Wireless radio, 1 Modem, and 1 Console, 1 ADSL port (optional), Current ScreenOS version 5.3

| | Availability | Trusted Wired and Wireless** Zones | Tunnel Zones | Additional Wireless Security Zones** |
|---|---|---|---|---|
| Trust-Untrust | All Licenses | 1 | 1 | 1 |
| Dual-Untrust** | All Licenses | 1 | 1 | 1 |
| Home-Work | All Licenses | 2* | 1 | 1 |
| Combined** | All Licenses | 2* | 1 | 1 |
| Extended | Extended Only | 2 | 1 | 2 |

*Home Zone Cannot Access Work Zone in Home-Work and Combined Port Modes.
** These Port modes are not available in the ADSL version of the NetScreen-5GT ADSL

| Product | Part Number |
|---|---|
| **Juniper Networks-5GT Ethernet** | |
| **Juniper Networks NetScreen-5GT 10 User** | |
| NetScreen-5GT US power supply | NS-5GT-001 |
| NetScreen-5GT UK power supply | NS-5GT-003 |
| NetScreen-5GT Europe power supply | NS-5GT-005 |
| NetScreen-5GT Japan power supply | NS-5GT-007-nn |
| **NetScreen-5GT ADSL** | |
| **Juniper Networks NetScreen-5GT ADSL 10 User*** | |
| NetScreen-5GT ADSL US power supply | NS-5GT-011-x |
| NetScreen-5GT ADSL UK power supply | NS-5GT-013-x |
| NetScreen-5GT ADSL Europe power supply | NS-5GT-015-A |

| Product | Part Number |
|---|---|
| **NetScreen-5GT Wireless** | |
| **Juniper Networks NetScreen-5GT Wireless 10 User** | |
| NetScreen-5GT Wireless US Only - US power supply | NS-5GT-021 |
| NetScreen-5GT Wireless World* - UK power supply | NS-5GT-023 |
| NetScreen-5GT Wireless World*- Europe power supply | NS-5GT-025 |
| NetScreen-5GT Wireless Japan Only* - Japan power supply | NS-5GT-027-nn |
| NetScreen-5GT Wireless World* - US power supply | NS-5GT-028 |
| **NetScreen-5GT Wireless ADSL** | |
| **Juniper Networks NetScreen-5GT Wireless ADSL 10 User** | |
| NetScreen-5GT Wireless ADSL US Only - US power supply | NS-5GT-031-x |
| NetScreen-5GT Wireless ADSL World* - UK power supply | NS-5GT-033-x |
| NetScreen-5GT Wireless ADSL World* - Europe power supply | NS-5GT-035-x |
| NetScreen-5GT Wireless ADSL World* - US power supply | NS-5GT-038-x |
| **NetScreen-5GT Upgrades** Anti-Virus, Deep Inspection, Web Filtering, and Anti-Spam can be purchased via subscription licenses. | |
| NetScreen-5GT Upgrade from 10-User to NetScreen-5GT Plus (Unrestricted user) | NS-5GT-PLU |
| NetScreen-5GT Upgrade from 10-User to NetScreen-5GT Extended | NS-5GT-ETU |
| NetScreen-5GT Upgrade from Plus to Extended | NS-5GT-EPU |
| **Accessories** | |
| Rack mount kit for 2 NetScreen-5GTs | NS-5GT-RMK |

* World units may not be purchased in Japan or the US due to regulatory restrictions.
To order ADSL Annex A or Annex B units, replace the –x at the end of the sku with an A or B.
Please check ISP and DSLAM compatibility for the ADSL connections at www.juniper.net/products/integrated/5GT-ADSL/

### Deep Inspection (DI) Signature Packs

This feature enhancement allows ScreenOS to support targeted DI signature pack optimized for your specific network deployment. You can now select the DI signature pack that improves threat prevention for your network environment to ensure detection accuracy and coverage.

| Protection Type* | Deployment Type | Defense type | Attack Type |
|---|---|---|---|
| Base | Branch Offices Small/Medium Businesses | Client/Server and worm protection | Selected set of critical signatures |
| Client | Remote/Branch Offices | Perimeter defense, compliance for hosts (desktops, etc) | Attacks in the server-to-client direction |
| Server | Small/Medium Businesses | Perimeter defense, compliance for server infrastructure | Attacks in the client-to-server direction |
| Worm Mitigation | Remote/Branch Offices of Large Enterprises | Most comprehen-sive defense against worm attacks | Worms, Trojans, back-door attacks |

Juniper NETWORKS

CORPORATE HEADQUARTERS AND SALES HEADQUARTERS FOR NORTH AND SOUTH AMERICA
Juniper Networks, Inc.
1194 North Mathilda Avenue
Sunnyvale, CA 94089 USA
Phone: 888-JUNIPER (888-586-4737) or 408-745-2000
Fax: 408-745-2100
www.juniper.net

EAST COAST OFFICE
Juniper Networks, Inc.
10 Technology Park Drive
Westford, MA 01886-3146 USA
Phone: 978-589-5800
Fax: 978-589-0800

ASIA PACIFIC REGIONAL SALES HEADQUARTERS
Juniper Networks (Hong Kong) Ltd.
Suite 2507-11, Asia Pacific Finance Tower
Citibank Plaza, 3 Garden Road
Central, Hong Kong
Phone: 852-2332-3636
Fax: 852-2574-7803

EUROPE, MIDDLE EAST, AFRICA REGIONAL SALES HEADQUARTERS
Juniper Networks (UK) Limited
Juniper House
Guildford Road
Leatherhead
Surrey, KT22 9JH, U. K.
Phone: 44(0)-1372-385500
Fax: 44(0)-1372-385501

Copyright 2006, Juniper Networks, Inc. All rights reserved. Juniper Networks and the Juniper Networks logo are registered trademarks of Juniper Networks, Inc. in the United States and other countries. All other trademarks, service marks, registered trademarks, or registered service marks in this document are the property of Juniper Networks or their respective owners. All specifications are subject to change without notice. Juniper Networks assumes no responsibility for any inaccuracies in this document or for any obligation to update information in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

110034-005 Apr 2006

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

**Artisan Technology Group** is an independent supplier of quality pre-owned equipment

## Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

## Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP