



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

SPECIFICATIONS

PART NUMBER
485 SPECS

RANGE	RESOLUTION	ACCURACY (1 YEAR) 18°-28°C ±(%rdg + counts)†	ANALOG RISE TIME (10-90%)	NORMAL MODE REJECTION RATIO (50 or 60Hz)	MAXIMUM CONTINUOUS INPUT‡
2 nA	0.1 pA	0.4 + 4	60ms	70dB	350Vdc
20 nA	1 pA	0.4 + 1	60ms	70dB	350Vdc
200 nA	10 pA	0.2 + 1	6ms	65dB	350Vdc
2 µA	100 pA	0.15 + 1	3ms	65dB	350Vdc
20 µA	1 nA	0.1 + 1	3ms	65dB	50Vdc
200 µA	10 nA	0.1 + 1	1ms	65dB	50Vdc
2mA	100 nA	0.1 + 1	1ms	55dB	50Vdc

† When properly zeroed.
‡ With no limiting resistance: 1000Vdc with external 100kΩ series resistance.

INPUT VOLTAGE BURDEN: Less than 200µV.
RANGING: Manual or autoranging.
AUTORANGING TIME: Average 250ms per range.
SETTLING TIME AT DISPLAY: Less than 1 second to within 2 counts on fixed range.
CONVERSION PERIOD: 300ms.
TEMPERATURE COEFFICIENT (0°-18°C & 28°-50°C): ±(0.1 × applicable accuracy specification) per °C.
MAXIMUM COMMON MODE VOLTAGE: 30V rms, DC to 80Hz sine wave.
ANALOG OUTPUT:
 Output Voltage: +1V = -10000 counts, except +100mV = -10000 counts on 2nA range.
 Output Resistance: 1000Ω.
REL: Pushbutton allows zeroing of on range readings. Allows relative readings to be made with respect to baseline value. Front panel annunciator indicates REL mode.
DATA STORE and MIN/MAX: 100 reading storage capacity; records data at one of six selectable rates from 3 readings/second to 1 reading/hour, or by manual triggering. Also detects and stores maximum and minimum readings continuously while in the data store mode.
LOG: Displays logarithm (base 10) of the absolute value of the measured current (examples: -3.000 = ±1mA; -6.301 = ±0.5µA).

IEEE-488 BUS IMPLEMENTATION (Option 4853)

MULTILINE COMMANDS: DCL, SDC, GET, GTL, UNT, UNL, SPE, SPD.
UNILINE COMMANDS: IFC, REN EOI, SRQ, ATN.
INTERFACE FUNCTIONS: SH1, AH1, T5, TEO, L4, LEO, SR1, RL2, PP0, DC1, DT1, C0, E1.
PROGRAMMABLE PARAMETERS: Zero Check, Range, REL, LOG, Trigger, Calibration, EOI, SRQ, Status, Output Format, Terminator.

GENERAL

DISPLAY: 4 1/2 digit LCD, 0.5" height; polarity, range and status indication.
OVERRANGE INDICATION: "OL" displayed.
CONNECTORS:
 Input: BNC.
 Analog Output: Banana Jacks.
OPERATING ENVIRONMENT: 0-50°C, less than 70% R.H. up to 35°C; linearly derate 3% R.H./°C up to 50°C.
STORAGE ENVIRONMENT: -25° to +60°C
POWER: 105-125V or 210-250V (switch selected), 90-110V available, 50-60Hz, 12 VA.
DIMENSIONS, WEIGHT: 85mm high × 235mm wide × 275mm deep. (3 1/4" × 9 1/4" × 10 3/4").
 Net Weight: 1.8kg (4 lbs.)

ACCESSORIES AVAILABLE:

- Model 1010: Single Rack Mounting Kit
- Model 1017: Dual Rack Mounting Kit
- Model 1684: Hard Shell Carrying Case
- Model 1758: Rechargeable Battery Pack
- Model 4801: Low Noise Input Cable (4ft.), BNC to BNC
- Model 4803: Low Noise Cable Kit
- Model 4853: IEEE-488 Interface
- Model 7008-3: IEEE-488 Digital Cable (3ft.)
- Model 7008-6: IEEE-488 Digital Cable (6 ft.)
- Model 8673: IEEE-488 Interface for IBM PC

LTR	REVISIONS	APP.	DATE	DRN. MH	DATE
A	01-15884		6-88	CKD. Tuna	DATE 01/88
				APP.	DATE

KEITHLEY Keithley Instruments Inc.
Cleveland, Ohio 44139

MODEL 485
SPECIFICATIONS

PART NUMBER
485 SPECS



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com