ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Keithley 617* at our website: *Click HERE*

PURCHASED ITEM

PART NUMBER SPEC-617

MODEL 617 SPECIFICATIONS

VOLTS

RANGE	RESOLUTION	ACCURACY (1 Yr.)* 18°–28°C ±(%rdg + counts)	TEMPERATURE COEFFICIENT 0°–18°C & 28°–50°C ±(%rdg + counts)/°C
200 mV	10 µV	0.05 + 4	0.004 + 3
2 V	100 µV	0.05 + 1	0.004 + 0.3
20 V	1 mV	0.05 + 1	0.005 + 0.1
200 V	10 mV	0.07 + 1	0.007 + 0.1

*When properly zeroed.

NMRR: >80dB on 200mV, 60dB on 2V and 20V, 55dB on 200V range, at 50Hz or 60Hz ±0.1%.

CMRR: >120dB at DC, 50Hz or 60Hz.

INPUT IMPEDANCE: >200TΩ in parallel with 20pF (<2pF guarded).

AMPS

RANGE	RESOLUTION	ACCURACY (1 Yr.)* 18°–28°C ±(%rdg + counts)	TEMPERATURE COEFFICIENT 0°–18°C & 28°–50°C ±(%rdg + counts)/°C
2 pA	100 aA	1.6 + 66	0.15 + 8
20 pA	1 fA	1.6 + 7	0.15 + 1
200 pA	10 fA	1.6 + 1	0.15 + 0.1
2 nA	100 fA	0.25 + 5	0.015 + 3
20 nA	1 pA	0.25 + 1	0.015 + 0.3
200 nA	10 pA	0.25 + 1	0.015 + 0.1
2 µA	100 pA	0.15 + 4	0.005 + 3
20 µA	1 nA	0.15 + 1	0.005 + 0.3
200 µA	10 nA	0.15 + 1	0.006 + 0.1
2 mA	100 nA	0.15 + 4	0.005 + 3
20 mA	1 µA	0.15 + 1	0.005 + 0.3

*When properly zeroed using recommended warm-up procedure.

INPUT BIAS CURRENT: <5fA (5×10^{-15}A) at 23°C

INPUT VOLTAGE BURDEN: <1mV except 3mV on 20mA range.

PREAMP SETTLING TIME (to 10% of final value): 2.5s on pA ranges, 15ms on nA ranges, 5ms on µA and mA ranges.

NMRR: >95dB on pA, 60dB on nA, µA, and mA ranges at 50Hz or 60Hz ±0.1%.

COULOMBS

RANGE	RESOLUTION	ACCURACY (1 Yr.)* 18°–28°C ±(%rdg + counts)	TEMPERATURE COEFFICIENT 0°–18°C & 28°–50°C ±(%rdg + counts)/°C
200 pC	10 fC	0.4 + 4	0.02 + 3
2 nC	100 fC	0.4 + 1	0.02 + 0.3
20 nC	1 pC	0.4 + 1	0.02 + 0.1

*When properly zeroed.

INPUT BIAS CURRENT: <5fA (5×10^{-15}A) at 23°C.

OHMS

RANGE	RESOLUTION	ACCURACY (1 Yr.)* 18°–28°C ±(%rdg+counts)	TEMPERATURE COEFFICIENT 0°–18°C & 28°–50°C ±(%rdg+counts)/°C	TEST CURRENT ±1.5%
2 kΩ	100 mΩ	0.20 + 4	0.01 + 3	100 µA
20 kΩ	1 Ω	0.15 + 1	0.01 + 0.3	100 µA
200 kΩ	10 Ω	0.25 + 1	0.01 + 0.3	10 µA
2 MΩ	100 Ω	0.25 + 1	0.02 + 0.3	1 µA
20 MΩ	1 kΩ	0.25 + 1	0.02 + 0.3	100 nA
200 MΩ	10 kΩ	0.30 + 1	0.02 + 0.3	10 nA
2 GΩ	100 kΩ	1.5 + 1	0.04 + 0.3	1 nA
20 GΩ	1 MΩ	1.5 + 1	0.04 + 0.1	1 nA
200 GΩ	10 MΩ	1.5 + 1	0.04 + 0.1	1 nA

*When properly zeroed.

MAXIMUM OPEN CIRCUIT VOLTAGE: 300V DC.

PREAMP SETTLING TIME (To 0.1% of final value with <100pF input capacitance): 2kΩ through 20MΩ: 15ms; 200MΩ: 150ms. (To 1% of final value with Input Guard on and <1pF of unguarded input capacitance): 2GΩ: 10ms; 20GΩ: 100ms; 200GΩ: 1 s.

V/I MODE: Used with V source; displays resistance (5×10^4 to 10^{14}Ω) calculated from measured current. V/I Ohms accuracy equal to accuracy of V source plus accuracy of selected Amps range.

VOLTAGE SOURCE

OUTPUT: –102V to +102V in 50mV steps.

ACCURACY (1 Yr., 18°–28°C): ±(0.2% + 50mV).

TEMPERATURE COEFFICIENT: ±(0.005% + 1mV)/°C

MAXIMUM OUTPUT CURRENT: ±2mA; active current limit at <4mA with annunciation.

SETTLING TIME: <3ms to rated accuracy.

NOISE: <(1ppm of output voltage + 200µV) p-p from 0.1Hz to 10Hz.

IEEE-488 BUS IMPLEMENTATION

MULTILINE COMMANDS: DCL, LLO, SDC, GET, GTL, UNT, UNL, SPE, SPD.

UNILINE COMMANDS: IFC, REN, EOI, SRQ, ATN.

INTERFACE FUNCTIONS: SH1, AH1, T5, TE0, L4, LE0, SR1, RL0, PP0, DC1, DT1, C0, E1.

PROGRAMMABLE PARAMETERS: Function, Range, Zero Check, Zero Correct, Zero Suppress, EOI, Trigger, Terminator, 100-Reading Storage and Retrieval, Calibration, V Source Output, Display Format, SRQ, Status (including V Source I-Limit), Output Format.

ADDRESS MODES: TALK ONLY and ADDRESSABLE.

TRIGGER TO READING DONE: 350ms typical.

GENERAL

DISPLAY: 4½-digit numeric LEDs with appropriate decimal point and polarity indication; signed two-digit alphanumeric exponent.

OVERRANGE INDICATION: Display reads "OL".

RANGING: Automatic or manual.

CONVERSION TIME: 330ms.

DATA STORE and MIN/MAX: 100-reading store capacity; records data at one of six selectable rates from every reading to 1 reading/hour, or by manual triggering. Also detects and stores maximum and minimum readings continuously while in the Data Store mode.

PROGRAMS: Provide front panel access to IEEE address, choice of engineering units or scientific notation, and digital calibration.

MAXIMUM INPUT: 250V peak, DC to 60Hz sine wave; 10s per minute maximum on mA ranges.

MAXIMUM COMMON MODE VOLTAGE (DC to 60Hz sine wave): Electrometer, 500V peak; V Source, 100V peak.

ISOLATION (Input LO to chassis): Typically 10^{14}Ω in parallel with 500pF.

INPUT CONNECTOR: Two lug triaxial on rear panel.

OUTPUT CONNECTORS: 5-way binding posts on rear panel for V source, preamp, and analog outputs. Rear panel BNC for External Trigger and Meter Complete.

2V ANALOG OUTPUT: 2V for full range input. Inverting in Volts and Ohms modes. Output impedance 10kΩ.

PREAMP OUTPUT: Provides a guard output for Volts and Ohms measurements. Can be used as an inverting output or with external feedback in Amps and Coulombs modes. Output Impedance: 100Ω.

GAIN ERROR AT PREAMP OUTPUT: Typically 5ppm.

SMALL SIGNAL BANDWIDTH AT PREAMP OUTPUT: Typically –3dB at 100kHz.

EXTERNAL TRIGGER: TTL compatible External Trigger and Electrometer Complete.

V, Ω GUARD SWITCH: OFF position: Inner shield of triax is Input LO, input capacitance is ≤20pF. ON position: Inner shield of triax is Guard (follows input HI). Input capacitance is ≤2pF. Use Analog Output COM for Input LO connection.

ENVIRONMENT: Operating: 0°–50°C; relative humidity 70% non-condensing, up to 35°C. Storage: –25° to +65°C.

SHIELDING: Double shielded.

WARM-UP: 2 hours to rated accuracy (see manual for recommended procedure).

POWER: 105–125V or 210–250V (internal switch selected), 90–110V available; 50–60Hz, 25VA.

DIMENSIONS, WEIGHT: 127mm high × 216mm wide × 359mm deep (5 in. × 8.5 in. × 14.125 in.). Net weight 3.6kg (8 lbs.).

ACCESSORY SUPPLIED: Model 6011 Triaxial Input Cable.

ORIGINAL IF RED

LTR	REVISIONS	APP.	DATE
A	RELEASED 10223	MS	9-27-84
B	REVISED 10332	MS	11-26-84
C	REVISED 10384	MS	12-26-84
D	REVISED 11396	MS	5-14-85
E	17107 REV. PREAMP SETTLING TIME	A	4-13-90

DRN. MZ DATE 9-27-84
CKD. B DATE 9-27-84
APP. DATE

KEITHLEY Keithley Instruments Inc. Cleveland, Ohio 44139

SPECIFICATIONS

PART NUMBER SPEC-617

BRUNING 40-21 62198

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP