ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Keopsys KPS-BT-C-18-LN-FA* at our website: ***Click HERE***

C-Band Benchtop Fiber Amplifiers

KPS-BT-C and KPS-BT2-C Series

The KPS-BT-C and KPS-BT2-C fiber amplifiers operate in the C-band wavelength region from 1529 to 1565nm. Several output saturation powers with different optical configurations are available. High output powers **up to 37dBm** are efficiently achieved thanks to Keopsys *VSP®* (V-groove Side Pumping) technology.

These turnkey microprocessor controlled bench-top versions manage alarms and status indicators and maintain constant pump current or output power. Integrated GPIB interface enables easy control, diagnostic and data acquisition. It also offers automatic power control (APC) and automatic current control (ACC) for any input signal power variation within the specified input signal power range.

Features

- Saturated output power **from 10 to 37 dBm**
- Wide Bandwidth
- Turnkey devices
- Input and Output photodiodes
- Isolated input and output ports
- Microprocessor control of operating parameters and alarms
- Automatic power control (APC)
- Automatic current control (ACC)
- GPIB remote control
- Tabletop or rack-mountable unit

KPS-BT2-C Series



VSP Technology

KPS-BT-C Series



Applications

- C-Band data transmission
- Free space transmission
- Power booster for tunable laser sources
- Pre-amplifier and in-line amplifier
- Telcordia component testing
- Non linear effect study

KEY OPTICAL SYSTEMS
eopsys
Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

High Power Preamplified Booster

KPS-BT-C-HPFA and KPS-BT2-C-HPFA Series

With integrated preamplifier, these two stages High Power Fiber Amplifiers ensure low noise figure combined with high output powers delivered by the booster stage. Our *VSP*® (V-groove side pumping) technology provide high efficiency and high output saturation power up to 37dBm in very compact and cost effective designs.

Features

- Saturated output power from 21 to 37dBm
- Bandwidth 1535-1565nm
- Preamplified Booster
- Low noise figure
- Input and output monitor photodiodes
- GPIB interface

SPECIFICATIONS (at 25°C)

OPTICAL		NOTES
Optical Bandwidth	1535nm - 1565nm	
Saturated Output Power	21 23 25 27 30 33 37dBm	at Pin= -3dBm
Optical Input Power	From -15dBm to 0dBm	
Noise Figure	<5.0 <5.0 <5.0 <5.5 <6.0 <7.0 < 8.0dB	at Pin= -10dBm @1550nm
Small Signal Gain	>35 >35 >35 >40 >40 >40 >45dB	at Pin= -30dBm @1550nm
Gain Variation	< 1.5dB	at Pin= -3dBm
Polarization Dependent Gain	< 0.5dB	
Polarization Mode Dispersion	< 1ps	Low PMD (<0.5ps) option available
Optical Isolation	> 30dB	
Return Loss	< -40dB	

ORDERING INFORMATION		
Part Numbering for tabletop unit	KPS-BT-C-xx-PB-yy	xx : Output power in dBm (1)
Part Numbering for rack-mountable unit	KPS-BT2-C-xx-PB-yy	yy : FA for FC/APC, SA for SC/APC FC for FC/SPC, SC for SC/SPC (2)

(1) 33dBm and 37dBm output power on BT2 version only
(2) SPC connectors up to 23dBm only

High Power Booster

KPS-BT-C-HPFB and KPS-BT2-C-HPFB Series

These economical, single stage, high power boosters are the ideal choice to amplify input signals around 0dBm. Through the use of our *VSP*® technology, they provide very high saturated output power.

Features

- Saturated output power from 18 to 30 dBm
- Banwidth : 1535-1565 nm
- Booster only
- Input and output monitor photodiodes
- GPIB interface

SPECIFICATIONS (at 25°C)

OPTICAL		NOTES
Optical Bandwidth	1535nm - 1565nm	
Saturated Output Power	18 21 23 25 27 30dBm	at Pin= 0dBm
Optical Input Power	From -3dBm to +3dBm	
Noise Figure	<7.0 <7.0 <8.0 <8.0 <8.5 <9.0dB	at Pin= -3dBm @1550nm
Small Signal Gain	>30 >30 >35 >35 >40 >40dB	at Pin= -30dBm @1550nm
Gain Variation	< 1.5dB	at Pin= 0dBm
Polarization Dependent Gain	< 0.5dB	
Polarization Mode Dispersion	< 1ps	Low PMD (<0.5ps) option available
Optical Isolation	> 30dB	
Return Loss	< -40dB	

ORDERING INFORMATION		
Part Numbering for tabletop unit	KPS-BT-C-xx-BO-yy	xx : Output power in dBm
Part Numbering for rack-mountable unit	KPS-BT2-C-xx-BO-yy	yy : FA for FC/APC, SA for SC/APC FC for FC/SPC, SC for SC/SPC (2)

(2) SPC connectors up to 23dBm only

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Standard Fiber Amplifier

KPS-BT-C-SFA and KPS-BT2-C-SFA Series

The Standard Fiber Amplifier series offer cost effective solutions for applications requiring preamplifiers, in line amplifiers or moderate power boosters. They cover the entire C-band range and provide low gain variation in single channel applications.

Features

- Saturated output power from 10 to 18dBm
- Wide bandwidth
- Wide dynamic range
- GPIB interface

SPECIFICATIONS (at 25°C)

OPTICAL		NOTES
Optical Bandwidth	1529nm - 1562nm	
Saturated Output Power	10 13 15 18dBm	at Pin= 0dBm
Optical Input Power	From -15dBm to 0dBm	
Noise Figure	< 5dB	at Pin= -3dBm @1550nm
Small Signal Gain	>20 >20 >30 >30dB	at Pin= -30dBm @1550nm
Gain Variation	< 1.5dB	at Pin= 0dBm
Polarization Dependent Gain	< 0.5dB	
Polarization Mode Dispersion	< 1ps	Low PMD (<0.5ps) option available
Optical Isolation	> 30dB	
Return Loss	< -40dB	

ORDERING INFORMATION		
Part Numbering for tabletop unit	KPS-BT-C-xx-Sd-yy	xx : Output power in dBm
Part Numbering for rack-mountable unit	KPS-BT2-C-xx-Sd-yy	yy : FA for FC/APC, SA for SC/APC FC for FC/SPC, SC for SC/SPC

GENERAL SPECIFICATIONS

TABLETOP BENCHTOP



ELECTRICAL		NOTES
AC Voltage	85-264V	47 to 63Hz
Power Consumption	Between 30W to 100W	Depending on Output Power

GENERAL	
Operating Case Temperature	+18°C / +35°C
Storage Temperature	-20°C / +55°C
Size	160mm x 260mm x 380mm
Fiber Type	SMF-28
Standard Connector	FC/APC

RACK MOUNTABLE BENCHTOP



ELECTRICAL		NOTES
AC Voltage	85-264V	47 to 63Hz
Power Consumption	Between 30W to 100W	Depending on Output Power

GENERAL	
Operating Case Temperature	+15°C / +35°C
Storage Temperature	-20°C / +55°C
Size	88mm x 427mm x 386mm
Fiber Type	SMF-28
Standard Connector	FC/APC

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Keopsys

KEY OPTICAL SYSTEMS



Your Keopsys Sales Contact:









Keopsys undertakes a continuous and intensive product development program to ensure that its products perform to the highest technical standards. As a result, the specifications in this document are subject to change without notice.

All products comply with IEC 60825-1 and FDA (21 CFR Subchapter J) laser safety standards.

Keopsys reserves the right to make changes to the products, pictures or information countained herein without notice.

KEOPSYS, SA
21 rue Louis de Broglie
22300 Lannion
FRANCE
Tel: + 33 2 96 05 08 00
Fax: + 33 2 96 05 08 01

KEOPSYS, Inc
96 Route 173 West, Suite 3
Hampton, NJ 08827-4004
USA
Tel: (908) 238-0898
Fax: (908) 238-9178

sales@keopsys.com
www.keopsys.com

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP