ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Kepco RAX 15-6.6K* at our website: ***Click HERE***



DIN-RAIL MOUNTABLE

The Family of RAX Models

FEATURES

- "Power-OK" LED.
- Remote on/off: TTL compatible signal applied to the optically isolated "RC" terminals; reduces surge stress on input circuit when used instead of switching the mains a-c.
- Active soft-start circuit: Limits a-c turn-on surge.
- Remote error sensing: Compensates for voltage drops up to 0.4V per wire (0.25V in 3.3V and 5V models).
- Remote voltage control: Provision is made for an external resistor to trim the output voltage setting.
- Adjustable voltage: Internal trimmer accessible through the case allows manual adjustment of the voltage setting.
- Overvoltage protection: Power is shut off if output voltage is forced beyond the set limit.

This KEPCO product is backed by a firm 5-YEAR WARRANTY

Kepco's RAX are general purpose, single output, industrial grade modules in four sizes from 50-300 watts. Enclosed construction with barrier strip input/output provides protection for mounting in industrial environments. RAX meet EN60950, UL 1950 and are certified to the MIL STD 810D environment.

RAX are rugged, single-output power modules that can be individually installed or may be combined into a custom power assembly for multi-output requirements. Please see pages 131-135 for details on Kepco's Power Assembly Program.

KEPCO POWER ASSEMBLY PROGRAM

AN ISO 9001 COMPANY
KEPCO®
THE POWER SUPPLIER™
SINCE 1946

KEPCO, INC. • 131-38 Sanford Avenue • Flushing, NY 11352 USA • Tel: (718) 461-7000 • Fax: (718) 767-1102
Email: hq@kepcopower.com • www.kepcopower.com/rax.htm

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



Model RAX 12-4.2K
50W



Model RAX 24-4.2K
100W



Model RAX 28-6.2K
175W



Model RAX 28-10K
300W

RAX MODEL TABLE

MODEL	OUTPUT VOLTAGE VOLTS Factory set(1)	OUTPUT VOLTAGE VOLTS Adjustment range	OVP SETTING VOLTS Nom. Input, 25°C	OUTPUT CURRENT AMPS 50°C	OUTPUT CURRENT AMPS 60°C	OUTPUT CURRENT AMPS 71°C	CURRENT LIMIT AMPS 25°C Rectangular Fixed	RIPPLE mV Source p-p typ	RIPPLE mV Source p-p max	RIPPLE mV Switching p-p typ	RIPPLE mV Switching p-p max	NOISE (SPIKE) mV d-c to 50MHz p-p max	EFFICIENCY PERCENT max load typ
50 WATT MODELS													
RAX 3.3-10K	3.3	1.8~3.6	3.9~4.8	10.0	7.0	4.0	10.5~11.0	5	10	25	40	100	75%
RAX 5-10K	5	4.0~5.5	6.0~6.9	10.0	7.0	4.0	10.5~11.0	5	10	25	40	100	
RAX 12-4.2K	12	8.4~13.2	13.7~15.7	4.2	2.9	1.7	4.5~4.8	15	30	25	50	170	
RAX 15-3.4K	15	12.0~16.5	17.0~19.5	3.4	2.4	1.4	3.6~3.9	15	30	25	50	200	
RAX 24-2.1K	24	16.8~26.4	27.0~30.5	2.1	1.5	0.8	2.3~2.5	25	40	25	60	290	
RAX 28-1.8K	28	19.6~30.8	32.0~35.0	1.8	1.3	0.7	2.0~2.2	30	60	25	60	330	
RAX 48-1K	48	32.6~52.8	55.0~63.0	1.0	0.7	0.4	1.1~1.3	35	90	25	60	530	
100 WATT MODELS													
RAX 3.3-20K	3.3	1.8~3.6	3.9~4.8	20.0	14.0	8.0	22.0~24.0	5	10	25	40	100	78%
RAX 5-20K	5	4.0~5.5	6.0~6.9	20.0	14.0	8.0	22.0~24.0	5	10	25	40	100	
RAX 12-8.3K	12	8.4~13.2	13.7~15.7	8.3	5.8	3.3	9.1~10.0	15	30	25	50	170	
RAX 15-6.6K	15	12.0~16.5	17.0~19.5	6.6	4.6	2.6	7.3~8.0	15	30	25	50	200	
RAX 24-4.2K	24	16.8~26.4	27.0~30.5	4.2	2.9	1.7	4.7~5.1	25	40	25	60	290	
RAX 28-3.5K	28	19.6~30.8	32.0~35.0	3.5	2.5	1.4	4.0~4.2	30	60	25	60	330	
RAX 48-2K	48	32.6~52.8	55.0~63.0	2.0	1.4	0.8	2.3~2.5	35	90	25	60	530	
175 WATT MODELS													
RAX 3.3-35K	3.3	1.8~3.6	3.9~4.8	35.0	24.5	14.0	36.8~38.5	5	10	25	40	100	79%
RAX 5-35K	5	4.0~5.5	6.0~6.9	35.0	24.5	14.0	36.8~38.5	5	10	25	40	100	
RAX 12-14K	12	8.4~13.2	13.7~15.7	14.0	9.8	5.6	14.7~15.4	15	30	25	50	170	
RAX 15-11K	15	12.0~16.5	17.0~19.5	11.0	7.7	4.4	11.8~12.1	15	30	25	50	200	
RAX 24-7.2K	24	16.8~26.4	27.0~30.5	7.2	5.0	2.9	8.0~8.3	25	40	25	60	290	
RAX 28-6.2K	28	19.6~30.8	32.0~35.0	6.2	4.3	2.5	7.0~7.3	30	60	25	60	330	
RAX 48-3.6K	48	32.6~52.8	55.0~63.0	3.6	2.5	1.4	4.3~4.5	35	90	25	60	530	
300 WATT MODELS													
RAX 5-60K	5	4.0~5.5	6.0~6.9	60.0	42.0	24.0	65.0~70.0	5	10	25	40	100	77%
RAX 12-25K	12	8.4~13.2	13.7~15.7	25.0	17.5	10.0	28.0~30.0	15	30	25	50	170	
RAX 15-20K	15	12.0~16.5	17.0~19.5	20.0	14.0	8.0	22.0~24.0	15	30	25	50	200	
RAX 24-12K	24	16.8~26.4	27.0~30.5	12.0	8.4	4.8	13.2~14.4	25	40	25	60	290	
RAX 28-10K	28	19.6~30.8	32.0~35.0	10.0	7.5	4.3	12.0~15.0	30	60	25	60	330	
RAX 48-6K	48	32.6~52.8	55.0~63.0	6.0	4.2	2.4	6.8~7.4	35	90	25	60	530	

(1) Nominal input, maximum load, 25°C.

AN ISO 9001 COMPANY
KEPCO®
THE POWER SUPPLIER™
SINCE 1946

KEPCO, INC. • 131-38 Sanford Avenue • Flushing, NY 11352 USA • Tel: (718) 461-7000 • Fax: (718) 767-1102
Email: hq@kepcopower.com • www.kepcopower.com/rax.htm

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

RAX GENERAL SPECIFICATIONS

SPECIFICATION		RATING/DESCRIPTION	CONDITION
Temperature		0-71°C (see model table)	Operating
		-40 to +75°C	Storage
Humidity		95% RH	Non-condensing, operating & storage
Shock		20g, 3 axes (11msec ±5msec pulse duration	Non-operating 3 shocks each axis
Vibration		5-10Hz: 10mm amplitude, 3 axes	Non-operating 1 hour each axis
		10-55Hz: 2g, 3 axes	
Isolation	Output to case	500V d-c, 100MΩ	25°C, 65% RH
Withstand Voltage	Input to output	3.75KV a-c for 1 minute	25°C, 65% RH Y capacitor removed
	Input to case	2KV a-c for 1 minute	25°C, 65% RH
Safety		UL 1950, CSA 1402C, TÜV EN60950	
Type of Construction		PC card, enclosed	
Enclosure		Aluminum	
Cooling	50W, 100W, 175W	Convection	
	300W	Built-in fan	

RAX INPUT CHARACTERISTICS

SPECIFICATION		50 WATT MODELS	100 WATT MODELS	175 WATT MODELS	300 WATT MODELS	CONDITION
Voltage Range		90-132 or 180-264V a-c; 240-370V d-c(4)				Jumper selectable(1)
Brownout Voltage		80/160V a-c; 220V d-c(4)				115/230V a-c
Current	typ	1.2/0.6A	1.8/0.9A	3.4/1.7A	4.6/2.8A	Maximum load 25°C 115/230V a-c
	max	1.6/0.8A	2.5/1.3A	4.2/2.2A	6.0/3.6A	
Fuse Value		3.15A	5.0A	6.3A	10.0A	
Initial Turn-on Surge		17/34A	17/34A	17/34A	20/40A	115/230V a-c
Frequency		Nominal 50/60Hz; range 47-440Hz(2)				Single phase
EMI		FCC, Class A (conducted)				
Soft-start Circuit		Resistor and triac or thyristor				
Leakage Current		0.5mA				UL method, 115V a-c
		0.75mA				UL/VDE, 230V a-c
Startup Time		800msec max				Std.(3)
Holdup Time	typ	30msec				Std.(3)
	min	20msec				
Circuit Type		Forward converter				
Switching Frequency		~150KHz				Nom. input, rated load

(1) For d-c, set selector to "230".
(2) At 440Hz the leakage current exceeds the VDE/UL safety specification limits.
(3) Std. condition = nominal input, maximum load, 25°C.
(4) Safety approval is for a-c operation only.


FEATURES

- Undervoltage protection in 300W models: If output voltage falls below 70% of nominal for any reason (including overload) and stays there for more than 20 seconds, power is shut off.
- Rectangular current limiting so you can drive non-linear loads.
- Parallel operation: Units may be paralleled for increased current.
- Holding time: Output is sustained by internally stored energy for 30 milliseconds typically, 20 milliseconds minimum.
- Fan cooling in 300W models: A monitor circuit maintains optimum temperature.
- Built-in EMI filter attenuates conducted noise below the requirements of FCC, Class A.
- Safety: All models recognized by UL 1950, certified by CSA 1402C, approved by TÜV Rheinland to EN60950, and are certified to meet the MIL STD 810D environment.
- Connections: Input and output connections are via screw terminal barrier strip.

UL RECOGNIZED CSA CERTIFIED TÜV APPROVED

RAX are CE marked per the Low Voltage Directive (LVD), EN60950.

DERATING 50, 100, 175W MODELS
(Convection cooled)



AN ISO 9001 COMPANY
KEPCO®
THE POWER SUPPLIER™
SINCE 1946

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

DIMENSIONS (HxWxD)

50W inches — 4.3 x 1.8 x 7.5
mm — 110 x 45 x 190

100W inches — 4.3 x 2.6 x 7.9
mm — 110 x 65 x 200

175W inches — 4.3 x 3.9 x 8.7
mm — 110 x 100 x 220

300W inches — 4.3 x 5.1 x 8.7
mm — 110 x 130 x 220

NET WEIGHT

50W 1.80lbs, 0.8Kg

100W 2.90lbs, 1.3Kg

175W 3.96lbs, 1.8Kg


300W 5.50lbs, 2.5Kg

RAX OUTPUT CHARACTERISTICS

SPECIFICATION		RATING/DESCRIPTION	CONDITION
Source Effect	typ	0.8%	Minimum to maximum input
	max	1.5%	
Load Effect	typ	0.8%	10-100% load
	max	1.5%	
Temperature Effect	typ	1.0%	Nominal input, rated load, 0-50°C
	max	2.0%	
Combined Effect (source, load & temperature)	typ	2.0%	
	max	4.0%	
Time Effect (drift)	typ	0.1%	0.5-8.5 hr, maximum load, 25°C
	max	0.5%	
Recovery Characteristics	Excursion	<4.0%	Nominal input, 25°C; step load change from 50% to 100% of rated load
	Recovery within ±1%	1msec	

OUTLINE DIMENSIONAL DRAWINGS

Fractional dimensions in light face type are in inches, **dimensions in bold face type are in millimeters.**



DIMENSIONS

MODEL	A	max. B	max. C	D	E	F	G	H	max. I
50W MODELS	6.30 **160**	7.48 **190**	0.98 **25**	3.54 **90**	0.59 **15**	0.59 **15**	0.71 **18**	0.79 **20**	4.33 **110**
100W MODELS	6.69 **170**	7.87 **200**	1.0 **25**	3.54 **90**	0.98 **25**	0.79 **20**	0.71 **18**	—	4.33 **110**
175W MODELS	7.48 **190**	8.66 **220**	0.98 **25**	3.54 **90**	2.36 **60**	0.79 **20**	0.71 **18**	—	4.33 **110**
300W MODELS	7.48 **190**	8.66 **220**	1.02 **26**	3.54 **90**	3.54 **90**	0.79 **20**	0.71 **18**	—	4.33 **110**

Tolerances: 0.028" (0.7mm) between mounting holes, 0.04" (1.0mm) other dimensions.

Mounting:
50W: 8-32 tapped holes —
(4) bottom; (3) each side; maximum screw penetration 0.28" (7.0mm).
100W, 175W, 300W: 8-32 tapped holes —
(4) bottom; (4) each side; maximum screw penetration 0.28" (7.0mm).

AN ISO 9001 COMPANY
KEPCO®
THE POWER SUPPLIER™
SINCE 1946

KEPCO, INC. • 131-38 Sanford Avenue • Flushing, NY 11352 USA • Tel: (718) 461-7000 • Fax: (718) 767-1102
Email: hq@kepcopower.com • www.kepcopower.com/rax.htm

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP