ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Keyence KV-40T* at our website: *Click HERE*



KV-40DR

Base unit, DC type, 24 Inputs and 16 Relay Outputs


SPECIFICATIONS


Model			KV-40DR
Type			DC power supply type base unit
Input power supply voltage	Base unit		24 VDC (+ 10%, - 20%)
Allowable instantaneous outage time			Less than 2 ms
Internal current consumption (24 VDC conversion value)			180mA or less
	Expansion unit		KV-E4X 20mA or less KV-E8X 25mA or less KV-E16X 35mA or less KV-E4T 25mA or lessKV-E8T(P) 40mA or less KV-E16T 60mA or less KV-E4R 40mA or less KV-E8R 70mA or lessKV-E16TP 70mA or less KV-E4XT(P) 30mA or less KV-E4XR 45mA or less KV-E16R 110mA or less
	Other		Operator panel KV-D20: 60 mA or less KL link adapter KL-N10V: 35 mA or less Programming console KZ-P3: 65 mA or less
Environmentalresistance	Operating ambient temperature		0 to 50°C (no freezing), 0 to 45°C (KZ-P3)
	Operating ambient humidity		35 to 85% RH(no condensation)
	Storage ambient temperature		-20 to 70°C (no freezing)
Withstand voltage			1,500 VAC for 1 minute (between the power supply terminal and the I/O terminals and between all the external terminals and the case)
Noise resistance			1,500 Vp-p or more, pulse width: 1 µs, 50 ns (by way of a noise simulator), conforms to EN standards (EN 61000-4-2/-3/-4/-6)
Shock resistance			Conforms to JIS C 0041, 150 m/s^2 (15 G), operating time: 11 ms, 2 times in each of the 3 axial directions
Vibration resistance[*1]	Intermittent vibration	Frequency: 10 to 57 Hz	Amplitude: 0.075 mm
		Frequency: 57 to 150 Hz	Acceleration: 9.8 m/s^2
	Continuous vibration	Frequency: 10 to 57 Hz	Amplitude: 0.035 mm
		Frequency: 57 to 150 Hz	Acceleration: 4.9 m/s^2
Insulation resistance			50 MΩ or more (tested with a 500 VDC megger, between the power supply terminal and the input terminal and between all the external terminals and the case)
Operating environment			Minimal amount of dust and corrosive gas present
Weight	Base unit		approx 330g
	Expansion unit		KV-E4X: approx. 80 g, KV-E8X: approx. 100 g, KV-E16X: approx. 130 g, KV-E4T: approx. 80 g, KV-E8T (P): approx. 100 g, KV-E16T (P): approx. 130 g, KV-E4R: approx. 100 g, KV-E8R: approx. 130 g, KV-E16R: approx. 190 g, KV-E4XT (P): approx. 100 g, KV-E4XR: approx. 120 g
	Other		KZ-P3 approx 230g KV-D20 approx 160g KL-N10V approx 80g


[*1] Conforms to JIS B 3502, IEC61131-2
Number of sweeps: 10 times respectively in the X, Y, and Z directions, 80 minutes

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Dimensions







Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP