

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Keysight / Agilent C6282-61606* at our website: ***Click HERE***



➜ **Related Supplies, Accessories, & Products**

summary

Automated tape backup without corporate IT support. Non-technical staff can set up and use the Autoloader 1/9, even remotely. Its small dimensions and affordable cost make it ideal for small or medium-sized companies or a mid-range server or network.

features

- scalable: tape options for 720 GB to 1.8 TB capacity plus upgrades to super drives
- easy -to-use: illuminated front-panel display and menu-structured controls
- stress-free: an integrated barcode reader automatically keeps track of tapes
- sophisticated: monitoring and diagnostics with a Web browser using optical remote management card
- plug-and-play: with LVDS or HVDS SCSI options; remote management card supports Ethernet connections via 10/100Base-T

hp warranty

- 1-year
- parts only

what's in the box?

- LTO Media Cartridge
- LTO Cleaning Cartridge
- 68 pin SCSI Jumper Cable
- 68 pin SCSI Terminator
- 2 meter 68 pin SCSI Interface Cable
- Bar Code Label Pack
- User/Service Manual
- Install Welcome Mat
- ISV Software Flyer
- Media mousemat
- Infotab Kit

key specifications

Capacity	• Native ◦ 900 GB

	• Compressed ◦ 1.8 TB*
Compression Technique	LTO-DC (enhanced version of ALDC)
Logical Recording Format	Linear Tape Open/Ultrium
External I/O Ports	High voltage differential SCSI
Performance Characteristics	

Local Backup Rate	• Native
	  ◦ 54 GB/hr
	• Compressed
	  ◦ 108 GB/hr

Transfer Rate	• Sustained
	  ◦ 15 MB/s native
	• Data
	  ◦ 15 MB/s native
	  ◦ 30 MB/s compressed*

Error Rate	$1x10^{-17}$
Average Storage Data Access Time	71 sec
Average Storage Medium Load Time	25 sec
Average Storage Medium Unload Time	17 sec

Device Media	• Read
	  ◦ LTO Ultrium - 1
	• Write
	  ◦ LTO Ultrium - 1

Compatibility Characteristics	
Backup Options	• Network

	◦ CA ◦ Veritas ◦ HP ◦ Legato ◦ Tivoili TSM
Network Operating Systems	• Network Operating ◦ NT ◦ Netware ◦ HP-UX ◦ Solaris ◦ Windows 2000
Environmental Characteristics	
Temperature	• Operating ◦ 10 to 35 ° C ◦ 50 to 95 ° F • Non-operating ◦ -40 to 66 ° C ◦ -40 to 151 ° F
Humidity	• Recommended ◦ 20 to 80% RH non-condensing • Non-operating ◦ 10 to 90% RH non-condensing
Power Requirements	
Consumption	• 100 watts typical, 120 watts maximum
Supply	• Line voltage 100 - to 127 V AC, 200 - to 240 V AC, line frequency; 50 - to 60 Hz
Acoustic Power Emissions	Less than 6.5 B(A)
Product Certifications	• UL 1950 • cUL • CSA 950 • TUV IEC 950/IEC 60 825-1 (laser CLASS 1) • FCC Class "B" • CISPR 22 Class "B" • C-Tick • VCCI • BSMI Taiwan

Physical Characteristics	

Dimension (WxDxH)	• Inches
	  ◦ 9 x 26 x 9 in
	• Metric
	  ◦ 235 x 660 x 229 mm

Weight	• Pounds
	  ◦ 54.3 lbs
	• Metric
	  ◦ 24.7 kg

Package Weight	• Pounds
	  ◦ 54 lb standalone; 54 lb rackmount
	• Metric
	  ◦ 24.5 kg standalone; 24.5 kg rackmount

UPC Number	7 25184-63484 0 C7147AA ABA U.S. - English localization 7 25184-63495 6 C7147CB ABA U.S. - English localization 7 25184-63506 9 C7149AA ABA U.S. - English localization 7 25184-63517 5 C7149CB ABA U.S. - English localization 7 25184-63530 4 C7747AA ABA U.S. - English localization 7 25184-63541 0 C7747CB ABA U.S. - English localization 7 25184-63552 6 C7748AA ABA U.S. - English localization 7 25184-63563 2 C7748CB ABA U.S. - English localization

*Capacities and transfer rates assume 2:1 data compression. Actual compression may differ because compression varies with data type.

All brand and product names are trademarks of their respective companies. Technical information in this document is subject to change without notice.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP