



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

HS & HB MODELS

TSO'D 50/60 Hz AC Frequency Converter 500 to 1200VA

The HS and HB series are lightweight, AC frequency power converters. These models utilize the latest state of the art solid state circuitry to convert a 115/200 VAC, 3 phase, 400 Hz input to either a 115 VAC, 60 Hz or 230 VAC, 50 Hz sine wave output. Design features include a crystal controlled oscillator for output frequency stability and a pulse-width-modulated square to sine wave power conversion scheme for efficient & reliable operation.



The model HS and HB Series frequency changers are designed to power laptop computers, audio/video entertainment systems, portable electronics (stereo, MP3, CD, DVD, video games, etc.), microwave ovens, coffee makers and medical equipment in airborne, marine and ground mobile applications.

Specifications:	
Input Voltage:	115/200 VAC \pm 10 VAC, 3 phase
Input Frequency:	400 Hz \pm 100 Hz
Output Wave Form:	Sine
Output Phase:	Single
Harmonic Distortion:	0.5% (nominal)
Power Factor:	+0.8 to -0.8
Efficiency:	87%(nominal)
Response Time:	300 uSec (no load to full load)
Regulation:	1% Line, 1% Load, 2.5% Temp.
Overload Capacity:	110% of the rated output power for a period of 2 hours; 150% of the rated output current for a period of 5 minutes (minimum). When the operating temp. >55°C, the overload setting is internally limited to 135% \pm 10% of the rated output power.
Protection Circuits:	The converter will shutdown under the following conditions: <ul style="list-style-type: none"> • Input voltage > 135 VAC \pm 5 VAC • Input voltage < 95 VAC \pm 5 VAC • Internal, high ambient temperature. • Short circuit condition.
Remote ON-OFF:	Yes
Operating Temperature:	-55°C to 71°C (-65°F to +160°F)
Altitude:	55,000 Ft.
Environmental:	DO-160C env. cat. F3ZBB[LV]XXXXXXBXAXXXBXXX
Cooling:	Thermostatically controlled, brushless fan.
Compliance:	FAA TSO-C73

Model	Input Current (A/PH)	Output				Dimensions (See Figure 1)					Wt Lb (Kg) ±5%
		Voltage (VRMS) ±5%	Current (A) RMS	Frequency (Hz) ±.5 Hz	Power (VA)	LL Inch (MM)	LM Inch (MM)	L Inch (MM)	T Inch (MM)	M.H. Inch (MM)	
HS50	2.0	115	4.3	60	500	9.50 (241.30)	8.75 (222.25)	8.09 (205.49)	.06 (1.52)	.20 (5.08)	4.4 (2.00)
HS100	3.4	115	8.7	60	1000	12.00 (304.80)	11.25 (285.75)	10.60 (269.64)	.08 (2.03)	.28 (7.11)	7.5 (3.40)
HS120	4.5	115	10.4	60	1200	12.00 (304.80)	11.25 (285.75)	10.60 (269.64)	.08 (2.03)	.28 (7.11)	7.5 (3.40)
HB100	3.4	230	4.3	50	1000	12.00 (304.80)	11.25 (285.75)	10.60 (269.64)	.08 (2.03)	.28 (7.11)	7.5 (3.40)
HB120	4.5	230	5.2	50	1200	12.00 (304.80)	11.25 (285.75)	10.60 (269.64)	.08 (2.03)	.28 (7.11)	7.5 (3.40)

PINS	HS50	HS100/HS120	HB100/HB120
A	OUTPUT 116 VAC, 60 Hz	OUTPUT 116 VAC, 60Hz	OUTPUT 230 VAC, 50Hz
B	INPUT Ø A, 115/200 VAC	INPUT Ø A, 115/200 VAC	INPUT Ø A, 115/200 VAC
C	INPUT Ø B, 115/200 VAC	INPUT ØB, 115/200 VAC	INPUT ØB, 115/200 VAC
D	OUTPUT RETURN (NEUTRAL)	OUTPUT RETURN (NEUTRAL)	OUTPUT RETURN (NEUTRAL)
E	INPUT Ø C, 115/200 VAC	INPUT Ø C, 115/200 VAC	INPUT Ø C, 115/230 VAC
F	REMOTE ON-OFF	REMOTE ON-OFF	REMOTE ON-OFF
G	INPUT RETURN, CHASSIS GND	INPUT RETURN, CHASSIS GND	INPUT RETURN, CHASSIS GND
MATE	MS3106A18-9S OR EQUIV.	MS3106A18-9SW OR EQUIV.	MS3106A18-9SW OR EQUIV.

OUTLINE DIMENSIONS



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com