ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.


Find the *Kollmorgen / Pacific Scientific P21NRXS-LNS-NS-03* at our website: *Click HERE*

599-95 Step Mtrs Sel Gd.out 11/15/00 1:44 PM Page 39

POWERMAX II®



MODEL NUMBER CODE POWERMAX II® motors



The example model number above indicates a standard NEMA 23 frame motor with a one stack rotor. This motor is equipped with a standard NEMA mount, regular construction, receptacle and an A winding. It also has a standard rotor, a smooth single-ended shaft and no encoder or encoder mounting provisions.

HOW TO ORDER

Review the Motor Model Number Code to assure that all options are designated. Dimensions, connections and phasing diagrams start on page 49. Encoder mounting options are on page 53.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

599-95 Step Mtrs Sel Gd.out 11/15/00 1:44 PM Page 38

POWERMAX II®



POWERMAX II® sets the world performance standard for NEMA 23 step motors. At up to 253 oz-in. holding torque, you won't find a more powerful two inch stepper.

With POWERMAX II you also gain the cost advantages of design for manufacturability (DFM) and North America's most advanced step motor manufacturing line.

That makes POWERMAX II economical without sacrificing features - such as long life bearings, high temperature insulation and quality magnet materials.

Plus DFM means we can build POWERMAX II to your specifications, in the volumes you need, according to your JIT or other delivery schedule.

Standard

Standard POWERMAX II motors come in half, single and two stacks that provide holding torques from 42 to 253 oz-in.

Custom

POWERMAX II proves that an economical step motor doesn't have to limit your options. It's just the opposite, thanks to flexible manufacturing.

Whether you require a simple drive shaft flat or an integral lead screw, POWERMAX II motors are made to order.

FEATURES	BENEFITS
Two Year Warranty	High quality, dependable operation
New Polymer Encapsulated Stator	Exceptional thermal dissipation
New Polymer End Bell with Threaded Inserts	End bell runs cooler, provides greater flexibility in mounting encoder and brake options
Largest Available Shaft Diameter on a NEMA 23 Stepper	Withstands high radial and axial loads. Supports numerous shaft modifications.
Oversized 30mm Bearings	Increases bearing fatigue life (L_{10}), extends motor life, reduces downtime
Sigmax® Technology	Increases available torque
Optional Low Inertia Rotor	Produces the highest acceleration rate possible
Optional Solid Rotor	High low speed torque, fast settling, superior stiffness and damping
Precision Ground Rotor OD and Honed Stator ID for Concentric Air Gap in an Economical Motor Design	High quality performance in an economical motor design.
Exposed Laminations Aids Thermal Dissipation	Improved heat dissipation extends motor life, reduces downtime.
High Performance Gearheads	Increases torque range in a reliable, complete package



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

599-95 Step Mtrs Sel Gd.out 11/15/00 1:45 PM Page 44

POWERMAX II® MOTOR TECHNOLOGY


Pacific Scientific developed POWERMAX II® to be the best cost/performance value available in hybrid step motors.

That's why you'll find so many standard POWERMAX II models in the universal NEMA 23 frame size. With POWERMAX II, you can tailor motor torque, acceleration and inertia to every axis of your design. And you can do this economically too, using a single mounting configuration and the driver of your choice.

Does your application require that extra measure of performance? Then consider the POWERMAX II M Series, featuring the patented Sigmax® technology.*


Samarium cobalt magnets in M Series motors concentrate magnetic flux at desired points between the rotor and stator. Sigmax technology optimizes flux paths to increase torque production and current utilization over conventional hybrid designs.

P SERIES STANDARD HYBRID



Typical paths of flux transfer in an energized conventional hybrid step motor. Some flux leakage occurs in normal operation.

M SERIES ENHANCED HYBRID SIGMAX® TECHNOLOGY



Patented Sigmax® technology* redirects magnetic flux to inhibit leakage and optimize torque production.

* Sigmax® technology is covered by U.S. patents 4,712,028, 4,713,470, 4,763,034 and 4,827,164.

TECHNICAL OVERVIEW

Types	
POWERMAX II M Series	Hybrid step motors with rare earth magnets in the stator teeth
POWERMAX II P Series	Hybrid step motors
Rotor construction	
POWERMAX II M and P Series; with "L" rotor designates	Laminated (high speed efficiency)
POWERMAX II M and P Series; with "J" rotor designates	Low mass/low inertia (fast start/stop, high acceleration)
Windings	
A, B, C, D, E, F, G	Standard winding to match any application
Phases	2
Full steps per revolution	200
Full step angle	1.8°
Angular accuracy	
POWERMAX II M and M "J"	±1.5% of one step, no load, non-cumulative
POWERMAX II P and P "J"	±3% of one step, no load, non-cumulative
Operating temperature	-20 to 40°C
Insulation	NEMA Class B, 130°C
Insulation resistance	100 Megohms @500V dc and 25°C
Shaft load ratings	
Max. radial load (at center of std. shaft extension)	20 lb.
Max. axial load (on front shaft extension toward motor)	13 lb.
Bearing life	Since large bearings (30 mm) are used, life is typically about 4 times that of 22 mm or smaller bearings used on other NEMA Size 23 motors. POWERMAX II bearing fatigue life (L_{10}) exceeds 10,000 hours at any rotational speed up to 10,000 full steps/second if operated within the max. radial and axial loads specified above.
Encoder options	See page 53.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

599-95 Step Mtrs Sel Gd.out 11/15/00 1:45 PM Page 45

POWERMAX II® HYBRIDS

NEMA 23 FRAME (2.3")—Ratings and Characteristics

Review the Model Number Code on page 39 to assure that all options are designated. Dimensions, connections and phasing diagrams are on page 49. In addition to those below, motors with characteristics for specific performance requirements are offered. Contact factory for more details.

Rated Currents are in descending order	Motor Model Number	Connection △2 Parallel	Connection △2 Series	Connection △2 Unipolar	Holding Torque △3 (2 phases on) oz-in (Nm) ±10%	Rated Current/ Phase △4 (amps DC)	Phase Resistance (ohms) ±10%	Phase Inductance △5 (mH) Typical	Detent Torque oz-in (Nm)	Thermal Resistance △6 (°C/watt)	Rotor Inertia oz-in-S² (kgm² x 10⁻³)	Weight lbs (kg)
Torque range: 42-61 oz-in. .29-.43 Nm	P2HNXXH-LXX-XX-00	•			59 (0.42)	5.2	0.22	0.5	2.5 (0.018)	6.6	0.0010 (0.007)	1.0 (0.45)
	P2HNXXH-LXX-XX-00		•		59 (0.42)	2.6	0.90	1.9				
	P2HNXXH-LXX-XX-00			•	42 (0.29)	3.68	0.44	0.5				
STANDARD P2H Series 1/2 rotor stack	P2HNXXB-LXX-XX-00	•			59 (0.42)	2.6	0.76	1.9				
	P2HNXXB-LXX-XX-00		•		59 (0.42)	1.3	3.04	7.6				
	P2HNXXB-LXX-XX-00			•	42 (0.29)	1.84	1.52	1.9				
	P2HNXXC-LXX-XX-00	•			61 (0.43)	2.5	0.84	2.3				
	P2HNXXC-LXX-XX-00		•		61 (0.43)	1.25	3.36	9.2				
	P2HNXXC-LXX-XX-00			•	43 (0.30)	1.77	1.68	2.3				
	P2HNXXF-LXX-XX-00	•			60 (0.42)	1.61	1.92	5.1				
	P2HNXXF-LXX-XX-00		•		60 (0.42)	0.80	7.68	20.4				
	P2HNXXF-LXX-XX-00			•	42 (0.30)	1.10	3.84	5.1				

All ratings typical and at 25°C unless otherwise noted.

△1 An "X" in the Model Number Code indicates an undefined option. Colored letter indicates winding. See Model Number Code on page 39.

△2 See Model Number Code on page 39, optional leaded connectors on page 52 and connection information on page 52.

△3 With rated current applied. Windings at 130°C and motor unmounted and in still air at 40°C (without heat sink).

△4 Windings at 130°C and motor in still air at 40°C (without heat sink). Operation of these motors above rated current may cause demagnetization. Contact factory.

△5 Small signal inductance as measured with impedance bridge at 1kHz, 1 amp.

△6 Thermal resistance measured with motor hanging in still air (unmounted).

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

599-95 Step Mtrs Sel Gd.out 11/15/00 1:45 PM Page 46

POWERMAX II® HYBRIDS

NEMA 23 FRAME (2.3")—Ratings and Characteristics (Con't)

Review the Model Number Code, page 39, to assure that all options are designated. Dimensions, connections and phasing diagrams are on page 49. In addition to those below, motors with characteristics for specific performance requirements are offered. Contact factory for more details.

Rated Currents are in descending order	Motor Model Number △1	Connection △2 Parallel	Connection △2 Series	Connection △2 Unipolar	Holding Torque △3 (2 phases on) oz-in (Nm) ±10%	Rated Current/ Phase △4 (amps DC)	Phase Resistance (ohms) ±10%	Phase Inductance △5 (mH) Typical	Detent Torque oz-in (Nm)	Thermal Resistance △6 (°C/watt)	Rotor Inertia oz-in-S² (kgm² x 10^{-3})	Weight lbs (kg)
Torque range: 95-144 oz-in. .67-1.02 Nm	M21NXXA-LXX-XX-00	•			142 (1.00)	5.6	0.23	0.7	9.4 (0.066)	5.5	0.0017 (0.012)	1.5 (0.68)
	M21NXXA-LXX-XX-00		•		142 (1.00)	2.8	0.92	2.8				
	M21NXXA-LXX-XX-00			•	100 (0.71)	4.0	0.46	0.7				
SIGMAX® M21 Series 1 rotor stack	M21NXXB-LXX-XX-00	•			137 (0.97)	4.6	0.32	1.0				
	M21NXXB-LXX-XX-00		•		137 (0.97)	2.3	1.28	4.0				
	M21NXXB-LXX-XX-00			•	97 (0.68)	3.3	0.64	1.0				
	M21NXXC-LXX-XX-00	•			144 (1.02)	3.5	0.53	2.0				
	M21NXXC-LXX-XX-00		•		144 (1.02)	1.75	2.12	8.0				
	M21NXXC-LXX-XX-00			•	102 (0.72)	2.5	1.06	2.0				
	M21NXXD-LXX-XX-00	•			135 (0.95)	1.51	2.61	8.7				
	M21NXXD-LXX-XX-00		•		135 (0.95)	0.76	10.4	34.8				
	M21NXXD-LXX-XX-00			•	95 (0.67)	1.07	5.22	8.7				
Torque range: 77-116 oz-in. .54-.82 Nm	P21NXXA-LXX-XX-00	•			114 (0.81)	5.6	0.23	0.8	4 (0.028)	5.5	0.0017 (0.012)	1.5 (0.68)
	P21NXXA-LXX-XX-00		•		114 (0.81)	2.8	0.92	3.2				
	P21NXXA-LXX-XX-00			•	81 (0.57)	4.0	0.46	0.8				
STANDARD P21 Series 1 rotor stack	P21NXXB-LXX-XX-00	•			111 (0.79)	4.6	0.32	1.1				
	P21NXXB-LXX-XX-00		•		111 (0.79)	2.3	1.28	4.4				
	P21NXXB-LXX-XX-00			•	79 (0.55)	3.3	0.64	1.1				
	P21NXXC-LXX-XX-00	•			116 (0.82)	3.5	0.53	2.3				
	P21NXXC-LXX-XX-00		•		116 (0.82)	1.75	2.12	9.2				
	P21NXXC-LXX-XX-00			•	82 (0.58)	2.5	1.06	2.3				
	P21NXXD-LXX-XX-00	•			109 (0.77)	1.51	2.61	10.3				
	P21NXXD-LXX-XX-00		•		109 (0.77)	0.76	10.4	41.2				
	P21NXXD-LXX-XX-00			•	77 (0.54)	1.07	5.22	10.3				

All ratings typical and at 25°C unless otherwise noted.

△1 An "X" in the Model Number Code indicates an undefined option. Colored letter indicates winding. See Model Number Code on page 39.

△2 See Model Number Code on page 39, optional leaded connectors on page 52 and connection information on page 52.

△3 With rated current applied. Windings at 130°C and motor unmounted and in still air at 40°C (without heat sink).

△4 Windings at 130°C and motor in still air at 40°C (without heat sink). Operation of these motors above rated current may cause demagnetization. Contact factory.

△5 Small signal inductance as measured with impedance bridge at 1kHz, 1 amp.

△6 Thermal resistance measured with motor hanging in still air (unmounted).

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

599-95 Step Mtrs Sel Gd.out 11/15/00 1:45 PM Page 47

POWERMAX II® HYBRIDS

NEMA 23 FRAME (2.3")—Ratings and Characteristics (Con't.)

Review the Model Number Code, page 39, to assure that all options are designated. Dimensions, connections and phasing diagrams are on page 49. In addition to those below, motors with characteristics for specific performance requirements are offered. Contact factory for more details.

Rated Currents are in descending order	Motor Model Number △1	Connection △2 Parallel	Connection △2 Series	Connection △2 Unipolar	Holding Torque △3 (2 phases on) oz-in (Nm) ±10%	Rated Current/ Phase △4 (amps DC)	Phase Resistance (ohms) ±10%	Phase Inductance △5 (mH) Typical	Detent Torque oz-in (Nm)	Thermal Resistance △6 (°C/watt)	Rotor Inertia oz-in-S² (kgm² x 10^{-3})	Weight lbs (kg)
Torque range: 161-253 oz-in. 1.13-1.79 Nm	M22NNXA-LXX-XX-00	•			230 (1.62)	6.5	0.21	0.7	17 (0.12)	4.5	0.0036 (0.025)	2.5 (1.13)
	M22NNXA-LXX-XX-00		•		230 (1.62)	3.3	0.84	2.8				
	M22NNXA-LXX-XX-00			•	163 (1.15)	4.6	0.42	0.7				
SIGMAX® M22 Series 2 rotor stack	M22NNXB-LXX-XX-00	•			253 (1.79)	4.6	0.38	1.7				
	M22NNXB-LXX-XX-00		•		253 (1.79)	2.3	1.52	6.8				
	M22NNXB-LXX-XX-00			•	179 (1.26)	3.3	0.76	1.7				
	M22NNXC-LXX-XX-00	•			238 (1.68)	3.1	0.78	3.1				
	M22NNXC-LXX-XX-00		•		238 (1.68)	1.55	3.12	12.4				
	M22NNXC-LXX-XX-00			•	168 (1.19)	2.2	1.56	3.1				
	M22NNXD-LXX-XX-00	•			238 (1.68)	2.5	1.22	5.0				
	M22NNXD-LXX-XX-00		•		238 (1.68)	1.25	4.88	20.0				
	M22NNXD-LXX-XX-00			•	168 (1.19)	1.77	2.44	5.0				
	M22NNXE-LXX-XX-00	•			227 (1.60)	1.64	2.71	10.1				
	M22NNXE-LXX-XX-00		•		227 (1.60)	0.82	10.8	40.4				
	M22NNXE-LXX-XX-00			•	161 (1.13)	1.16	5.42	10.1				
Torque range: 138-214 oz-in. .97-1.51 Nm	P22NNXA-LXX-XX-00	•			197 (1.39)	6.5	0.21	0.8	7 (0.049)	4.5	0.0036 (0.025)	2.5 (1.13)
	P22NNXA-LXX-XX-00		•		197 (1.39)	3.3	0.84	3.2				
	P22NNXA-LXX-XX-00			•	139 (0.98)	4.6	0.42	0.8				
STANDARD P22 Series 2 rotor stack	P22NNXB-LXX-XX-00	•			214 (1.51)	4.6	0.38	2.1				
	P22NNXB-LXX-XX-00		•		214 (1.51)	2.3	1.52	8.4				
	P22NNXB-LXX-XX-00			•	151 (1.07)	3.3	0.76	2.1				
	P22NNXC-LXX-XX-00	•			203 (1.43)	3.1	0.78	3.9				
	P22NNXC-LXX-XX-00		•		203 (1.43)	1.55	3.12	15.6				
	P22NNXC-LXX-XX-00			•	144 (1.01)	2.2	1.56	3.9				
	P22NNXD-LXX-XX-00	•			203 (1.43)	2.5	1.22	6.2				
	P22NNXD-LXX-XX-00		•		203 (1.43)	1.25	4.88	24.8				
	P22NNXD-LXX-XX-00			•	144 (1.01)	1.77	2.44	6.2				
	P22NNXE-LXX-XX-00	•			195 (1.38)	1.64	2.7	12.6				
	P22NNXE-LXX-XX-00		•		195 (1.38)	0.82	10.8	50.4				
	P22NNXE-LXX-XX-00			•	138 (0.97)	1.16	5.4	12.6				

All ratings typical and at 25°C unless otherwise noted.

△1 An "X" in the Model Number Code indicates an undefined option. Colored letter indicates winding. See Model Number Code on page 39.

△2 See Model Number Code on page 39 optional leaded connectors on page 52 and connection information on page 52.

△3 With rated current applied. Windings at 130°C and motor unmounted and in still air at 40°C (without heat sink).

△4 Windings at 130°C and motor in still air at 40°C (without heat sink). Operation of these motors above rated current may cause demagnetization. Contact factory.

△5 Small signal inductance as measured with impedance bridge at 1kHz, 1 amp.

△6 Thermal resistance measured with motor hanging in still air (unmounted).

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


599-95 Step Mtrs Sel Gd.out 11/15/00 1:45 PM Page 48

POWERMAX II®

HYBRIDS WITH LOW INERTIA ROTORS

ROTOR INERTIA CHARACTERISTICS . . . POWERMAX II® motors

Single and double stack POWERMAX II® motors are available with both standard and low inertia rotors. Choose low inertia to produce the highest acceleration rates possible.



Low inertia rotor **Standard rotor**

ACCELERATION COMPARISON

	Model	Rotor Type	△1 Inertia oz-in-S² x 10⁻³/ kgm² x 10⁻³	Theoretical Normalized △2 Acceleration comparison
Single Stack	**P21NRXX-L**	Standard	1.68/0.010	1
	P21NRXX-J	Low inertia	1.30/0.008	1.27
	M21NRXX-L	Standard	1.68/0.010	1.23
	M21NRXX-J	Low inertia	1.30/0.008	1.59
Double Stack	**P22NRXX-L**	Standard	3.57/0.022	1
	P22NRXX-J	Low inertia	2.59/0.016	1.30
	M22NRXX-L	Standard	3.57/0.022	1.18
	M22NRXX-J	Low inertia	2.59/0.016	1.63

△1 Low inertia rotors not offered for half stack models

△2 Comparative values for normalized acceleration of unloaded motors. Base value is standard hybrid motor with standard rotor, indicated for single and double stack lengths.

Actual acceleration capability depends on load, velocity profile and driver power. Comparisons made with 90°C temperature rise using bipolar driver.

NEMA 23 FRAME (2.3")—Ratings and Characteristics

Review the Model Number Code, page 39, to assure that all options are designated. Dimensions, connections and phasing diagrams start on page 49. In addition to those below, all 1 and 2 stack "L" construction windings, page 59, and custom windings for specific performance requirements are available with low inertia rotors. Contact factory for more details.

	Motor Model Number △1	Connection △2 Parallel	Series	Unipolar	Holding Torque △3 (2 phases on) oz-in (Nm) ±10%	Rated Current/ Phase △4 (amps DC)	Phase Resistance (ohms) ±10%	Phase Inductance △5 (mH) Typical	Detent Torque oz-in (Nm)	Thermal Resistance △6 (°C/watt)	Rotor Inertia oz-in-S² (kgm² x 10⁻³)	Weight lbs (kg)
Torque range: 99-140 oz-in. .70-.99 Nm **SIGMAX® M21 Series 1 rotor stack**	M21NXX**A**-JXX-XX-00	•			**140** (0.99)	**5.6**	0.23	0.7	9.4 (0.066)	5.5	0.0013 (0.009)	1.5 (0.68)
	M21NXX**A**-JXX-XX-00		•		**140** (0.99)	**2.8**	0.92	2.8				
	M21NXX**A**-JXX-XX-00			•	**99** (0.70)	**4.0**	0.46	0.7				
Torque range: 79-111 oz-in. .55-.78 Nm **STANDARD P21Series 1 rotor stack**	P21NXX**A**-JXX-XX-00	•			**111** (0.78)	**5.6**	0.23	0.9	4 (0.028)			
	P21NXX**A**-JXX-XX-00		•		**111** (0.78)	**2.8**	0.92	3.6				
	P21NXX**A**-JXX-XX-00			•	**79** (0.55)	**4.0**	0.46	0.9				
Torque range: 178-252 oz-in. 1.26-1.78 Nm **SIGMAX® M22 Series 2 rotor stack**	M22NXX**B**-JXX-XX-00	•			**252** (1.78)	**4.6**	0.38	1.5	17 (0.12)	4.5	0.0026 (0.018)	2.5 (1.13)
	M22NXX**B**-JXX-XX-00		•		**252** (1.78)	**2.3**	1.52	6.0				
	M22NXX**B**-JXX-XX-00			•	**178** (1.26)	**3.3**	0.76	1.5				
Torque range: 142-201 oz-in. 1.00-1.42 Nm **STANDARD P22 Series 2 rotor stack**	P22NXX**B**-JXX-XX-00	•			**201** (1.42)	**4.6**	0.38	1.8	7 (0.049)			
	P22NXX**B**-JXX-XX-00		•		**201** (1.42)	**2.3**	1.52	7.2				
	P22NXX**B**-JXX-XX-00			•	**142** (1.00)	**3.3**	0.76	1.8				

All ratings typical and at 25°C unless otherwise noted.

△1 An "X" in the Model Number Code indicates an undefined option. Colored letter indicates winding. See Model Number Code on page 39.

△2 See Model Number Code on page 39, optional leaded connectors on page 52 and connection information on page 52.

△3 With rated current applied. Windings at 130°C and motor unmounted and in still air at 40°C (without heat sink).


△4 Windings at 130°C and motor in still air at 40°C (without heat sink). Operation of these motors above rated current may cause demagnetization. Contact factory

△5 Small signal inductance as measured with impedance bridge at 1kHz, 1 amp.

△6 Thermal resistance measured with motor hanging in still air (unmounted).

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


DIMENSIONS. . .(POWERMAX II® HYBRIDS) in. / mm (metric dim. for ref. only)



Motor Model	L Max.
P2H	1.60 / 40,7
P or M21	2.06 / 52,3
P or M22	3.10 / 78,7

STANDARD SHAFT OPTIONS


1. Shaft modifications also available. See page 39.
2. Optional flat available on front shaft as shown.



⚠1 Optional rear shaft extension available as shown. Same diameter as front shaft extension.


ENCODER OPTION

See page 53 for encoder/mounting specifications.



CONNECTION INFORMATION . . .Terminations and phase sequencing

NOTE: Phase sequencing direction of rotation as viewed from mounting end of motor.




DRIVER CONNECTION ⚠2


STEP	A	$\overline{A}$	B	$\overline{B}$
1	+	–	–	+
2	–	+	–	+
3	–	+	+	–
4	+	–	+	–
1	+	–	–	+

CCW ↓ ↑ CW

Bipolar full step



4-Lead connection (Bipolar)



6-Lead connection (Unipolar)

DRIVER CONNECTION ⚠1

STEP	A	B	C	D
1	GND	O	GND	O
2	O	GND	GND	O
3	O	GND	O	GND
4	GND	O	O	GND
1	GND	O	GND	O

CCW ↓ ↑ CW

Unipolar full step

⚠2 Notes:

0 = off or open
\+ = positive current flow
\- = negative current flow
GND = ground

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


599-95 Step Mtrs Sel Gd.out 11/15/00 1:45 PM Page 50

POWERMAX II® Flying Lead Motor Connection Informations

CONNECTION	LEAD COLOR	DRIVER CONNECTION
4-LEAD BIPOLAR	BLK	A
BIPOLAR	ORG	$\overline{A}$
SERIES	RED	B
	YEL	$\overline{B}$
	WHT/BLK & WHT/ORG	—
	WHT/RED & WHT/YE	—
	WHT/RED & WHT/YEL	—
4-LEAD BIPOLAR	BLK & WHT/ORG	$\overline{A}$
BIPOLAR	ORG & WHT/BLK	A
PARALLEL	RED & WHT/YEL	$\overline{B}$
	YEL & WHT/RED	B
6-LEAD UNIPOLAR	BLK	A
UNIPOLAR	ORG	B
	RED	C
	YEL	D
	WHT/BLK & WHT/ORG	+V
	WHT/RED & WHT/YEL	+V


CONNECTION INFORMATION . . .Terminations and phase sequencing

NOTE: Phase sequencing direction of rotation as viewed from mounting end of motor.



PHASE B

8 lead motor
(reference only)




6-Lead connection
(Unipolar)

DRIVER CONNECTION ⚠


STEP	A	B	C	D
1	GND	O	GND	O
2	O	GND	GND	O
3	O	GND	O	GND
4	GND	O	O	GND
1	GND	O	GND	O

CCW ↓ ↑ CW

Unipolar full step



SERIES



PARALLEL

4-Lead motor
(Bipolar)

DRIVER CONNECTION ⚠

STEP	A	$\overline{A}$	B	$\overline{B}$
1	+	–	–	+
2	–	+	–	+
3	–	+	+	–
4	+	–	+	–
1	+	–	–	+

CCW ↓ ↑ CW

Bipolar full step


Notes:

⚠ 0 = off or open
\+ = positive current flow
\- = negative current flow
GND = ground

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

599-95 Step Mtrs Sel Gd.out 11/15/00 1:45 PM Page 51

POWERMAX II® Flying Lead Motor



Motor Model	L Max.
P2H	1.60 / 40,7
P or M21	2.06 / 52,4
P or M22	3.10 / 78,8

NOTES:

⚠1 Flexible rubber boot may be bent as shown. Normal height 1.0 inch (25,4)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

599-95 Step Mtrs Sel Gd.out 11/15/00 1:45 PM Page 52


POWERMAX II® CONNECTION INFORMATION . . .

. . . Optional leaded connectors

Four different leaded connectors are available from Pacific Scientific. Order the "GW" part number as a separate item.

Part Number	Phase Connection	Pin No.	Connector/Leadwire Assembly Lead Colors	Driver Connection
GW0000F (8 Lead)	bipolar series	6	Black	$\overline{A}$
		1	Orange	A
		8	Red	$\overline{B}$
		3	Yellow	B
		2 & 5	Wht/Blk & Wht/Org	none
		4 & 7	Wht/Red & Wht/Yel	none
	bipolar parallel	6 & 5	Blk & Wht/Org	$\overline{A}$
		1 & 2	Org & Wht/Blk	A
		8 & 7	Red & Wht/Yel	$\overline{B}$
		3 & 4	Yel & Wht/Red	B
	unipolar	6	Black	A
		1	Orange	B
		8	Red	C
		3	Yellow	D
		2 & 5	Wht/Blk & Wht/Org	+ V
		4 & 7	Wht/Red & Wht/Yel	+ V
GW0000E (6 Lead)	unipolar	6	Black	A
		1	Orange	B
		8	Red	C
		3	Yellow	D
		2 & 5	Wht/Blk & Org	+ V
		4 & 7	Wht/Red & Yel	+ V
GW0000H (4 Lead)	bipolar parallel	6 & 5	Black	$\overline{A}$
		1 & 2	Orange	A
		8 & 7	Red	$\overline{B}$
		3 & 4	Yellow	B
GW0000L (4 Lead)	bipolar series	6	Black	$\overline{A}$
		1	Orange	A
		8	Red	$\overline{B}$
		3	Yellow	B

Typical leaded connector (4-lead shown)




. . . Optional mating connector only

A separate mating connector housing and strain relief cover are available from Pacific Scientific or AMP. The user attaches leads to the connector.

ITEM	PACIFIC SCIENTIFIC	AMP
STANDARD HOUSING	GP00012	641653-8
STANDARD COVER	GP00013	643077-8

Optional Ground Wire



NOTES:

1. GROUND LABEL PLACED IN FRONT OF GROUND SCREW.
2. GREEN/YELLOW SAFETY EARTH CONDUCTOR (18AWG).

See page 39 for ordering information.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


599-95 Step Mtrs Sel Gd.out 11/15/00 1:45 PM Page 53

ENCODER OPTIONS


NEMA 23 ENCODER OPTION

The standard encoder offered on the NEMA 23 motor is the Agilent Technologies HEDS 5600 series.

NON-LINE DRIVER ENCODER



ENCODER OUTPUT
FOR CW DIRECTION OF ROTATION WHEN VIEWED FROM MOTOR DRIVE SHAFT END. (COMPLEMENTS NOT SHOWN) MIN. EDGE SEPARATION 45°. INDEX GATED TO A AND B.




PIN	COLOR	FUNCTION
1	BLACK	GROUND
2	BLUE	Z
3	WHITE	A
4	RED	+5V
5	BROWN	B

PARAMETERS 2	NON-LINE DRIVER	
TYPE	INCREMENTAL	
ENCODER OPTION	HD	HJ
PULSES PER REVOLUTION	500	512
SUPPLY VOLTAGE	+5V ± 10% @ 85 mA MAX.	
OUTPUT FORMAT	DUAL CHANNEL QUADRATURE AND INDEX	
OUTPUT TYPE	SQUARE WAVE TTL COMPATIBLE	
FREQUENCY RESPONSE:		
DATA	100 kHz	
INDEX	100 kHz	
ROTOR INERTIA	5 x 10^{-7} lb-in-S^2	
WEIGHT	0.08 lb.	

ENCODER MOUNTING PROVISION ONLY = M1

FOR AGILENT TECHNOLOGIES HEDS 5600 SERIES OR SIMILAR.



SHAFT DIA. .2500 $^{+.0000}_{-.0005}$
SHAFT LENGTH .75 ± .06

NOTES:
1. Leads are terminated with Agilent Technologies HEDS-8903 connector.
2. TYPICAL @ 25° C

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP