ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Kontron VM6054-SA48* at our website: *Click HERE*

VM6054



6U VME SINGLE BOARD COMPUTER

- Intel® Quad-Core™ 3rd Generation Intel® Core™ i7, up to 16 GB SDRAM with ECC
- Intel® HD Graphics 4000, multiple Graphic Heads
- Comprehensive I/O Capabilities: 4 Ethernet 1000BASE-T, USB, Serial, SATA, Personality Module, PMC/XMC, Flexible I/O
- Long Term Supply
- Commercial and Rugged Versions

POSSIBILITIES START HERE kontron

6U VME HIGH PERFORMANCE 3rd GENERATION INTEL® CORE™ I7 COMPUTER

The VM6054 6U VME 2eSST Single Board Computer is built around Intel®'s state-of-the-art 3rd Generation Core™ i7 quad-core processor. The VM6054 provides exceptional I/O capabilities onboard and outstanding flexibility by providing support for PMC, XMC and storage mezzanines, personality modules. Accessory cards such as VME 6U dual PMC carrier and rear transition module complete the ecosystem. Existing users of PENTXM2, PENTXM4 and VM6050 will find with VM6054 the perfect replacement with the same front and rear interface making investment preservation with Kontron products an actual experience already spanning a decade.


EXTENSIVE I/O SUPPORT

The VM6054 base version provides four Gigabit Ethernet interfaces, two serial lines, up to 8 GPIOs, three USB links, two SATA interfaces, one 4x PCI-Express link and two onboard Mezzanine Sites, supporting PMC/XMC. An extended I/O selection is available by adding a flexible multi-purpose XMC I/O card from Kontron. More I/O cards can be seated on the V2PMC2, a Kontron 6U VME PCI-X/PMC carrier card that holds up to two single-width or one double-width PCI-X/PMC module.

HIGH VERSATILITY AND CUSTOMIZATION

The VM6054 offers many options to fulfill a large range of application requirements: onboard HDD and SSD, Flash Disk Module (FDM). Specific personality module interface available on top and bottom offers additional and customizable features like Digital Graphics, VGA, GPIOs, USB, High Definition Audio and more.

Example: VM6054 with personality module offering one VGA two Display Ports and 2 PMC/XMC.




LONG TERM SUPPLY AND SUPPORT

The VM6054 is part of the Kontron Extended Life Cycle product family which offers a 15-year life cycle organization on top of Intel® embedded product line silicon life cycle. And extended long term support achievement is render simple choosing among a set of catalog support packages.

LEGACY COMPATIBILITY

The VM6054 is front and rear I/O compatible with Kontron's line of x86 and PowerPC VME SBCs, supporting the same peripherals, Rear Transition Module and PMCs Carrier. The net effect of this fit form function compatibility is to allow our customers a simple line replacement policy of the SBC in deployed systems.

▶ VM6054 BLOCK DIAGRAM



ASSOCIATED PRODUCTS

EVALUATION SYSTEM



EZ1-VM6054

REAR TRANSITION MODULE




PBV36-P0-VM6-00

FLASH DISK MODULE




FDM-SATA

PMCs CARRIER




V2PMC2

PowerPC



VM6250


X86




PENTXM2, PENTXM4
VM6050, VM6052, VM6054

PINOUT COMPATIBILITY ACROSS PROCESSOR FAMILIES

MEZZANINE CARRIER



REAR TRANSITION MODULE



FRONT PANEL I/OS



FULL COMPATIBILITY WITH LEGACY PRODUCTS

▶ TECHNICAL INFORMATION

PROCESSOR		3rd Generation Intel® Core™ i7 processor (22 nm manufacturing process, code name Ivy Bridge) ▶ Quad Core 3612QE – SV 2,1 GHz/35W		
MEMORY	System Memory	Up to 16 GB dual channel DDR3 SDRAM, with ECC, soldered, running at 1600 MHz		
	Nand Flash	SATA NAND Flash Disk Modules (typically 16, 32 GB), soldered or on mezzanine socket (FDM-SATA option)		
	EEPROM	One serial 256 Kbit EEPROM dedicated to system data One serial 256 Kbit EEPROM dedicated to application data		
	Flash BIOS	FLASH BIOS, with recovery image and uEFI BIOS settings		
ONBOARD CONTROLLER & MONITORING	Platform Controller Hub	Hub Mobile Intel® QM77 Express Chipset		
	Real Time Clock	Integrated in QM77 with 256 Byte CMOS RAM		
	Watchdog	Software configurable dual-stage Watchdog timer with programmable timeout from 125 ms to 256s		
	VME, VME 2eSST	Kontron ALMA PCI VME Bridge		
	Health Management	Power On Built In Test, temperature and voltage sensors		
FRONT INTERFACES	Base version	1 or 2 x RS232/422/485, 2 x 1000BASE-T, 1 x USB 2.0, LEDS, 2 x PMC/XMC slots		
ONBOARD INTERFACES	VITA Mezzanines	PMC: one 64-bit 66 MHz / PCI-X 133 MHz , one 32-bit 66 MHz, VIO=3,3V XMC: one PCIe x8, one PCIe x4		
	Storage	One port for mounting an optional 2.5" media device like HDD and SSD (in lieu of one PMC/XMC) One port for Flash Disk Module		
	Personality Module	One port for mounting an optional Personality Module top or bottom		
BASELINE I/OS		*Front (Air-Cooled Version)*	*Rear*	*Onboard*
	USB 2.0	1	2 (P0)	
	PMC/XMC	-	-	2
	Serial 232/422/485 selectable	1 or 2 (RJ-12)	2 (P2)	
	SATA	-	2 (P0)	1 for HDD/SSD option 1 for Flash module option
	Ethernet	2x 10/100/1000BASE-T (RJ-45)	2x 10/100/1000BASE-T (P0)	-
	GPIO	-	up to 8	
	LED	4	-	-
	Reset	one reset button	one pin (P0)	-
OPTIONAL I/OS	Personality Module	Personality modules offer additional I/O services. One personality module may be mounted on SBC: ▶ Top mounting for one VME slot occupancy and 1 PMC/XMC slot available ▶ Bottom mounting for two VME slots occupancy and 2 PMC/XMC available		
LEGACY I/O CONFIGURATION		PENTXM2, PENTXM4, VM6050 I/O configuration may be identically reproduced allowing "Fit Form Function" board replacement effectiveness. VM6054 accepts same RTM and PMC/XMC Carrier board already used with PENTXM2, PENTXM4, VM6050.		
DIMENSIONS	(BASELINE)	VME 1 slot, 6U, 4HP, 0.8" slot pitch, P1 P2 P0 equipped, 5-row backplane connector		

▶ TECHNICAL INFORMATION

WEIGHT (BASELINE)		Standard Air Cooled Version: 550g approx. / Conduction Cooled Version: 800g approx.
SOFTWARE SUPPORT		AMI BIOS Aptio 0.27.023 / Linux Operating System Fedora 16 Board Support Package
POWER	Standard 5V only option	3.3V, 5V, +12V (-12V if required for mezzanine) VME64 compatible version: 3.3V not required No P0 connector fitted
COMPLIANCY		Designed to meet or exceed: ▶ Safety: UL94-V ▶ EN55082, EN55022 class A ▶ VITA 47 ▶ MIL-STD-810F ▶ RoHS, Reach

▶ ENVIRONMENTAL SPECIFICATION

	SA - STANDARD COMMERCIAL	WA - EXTENDED TEMPERATURE	RC - RUGGED CONDUCTION-COOLED
CONFORMAL COATING	Optional	Standard	Standard
AIRFLOW	2.3 m/s to 3.3 m/s	3.3 m/s	NA
TEMPERATURE	VITA 47-Class AC1 (design to meet)	VITA 47-Class AC1 (design to meet)	VITA 47-Class CC3 (design to meet)
Cooling Method	Convection	Convection	Conduction
Operating	0° to +55°C	-20° to +65°C	-40° to +71°C
Storage	-40° to +85°C	-45° to +100°C	-50° to +100°C
VIBRATION SINE (OPERATING)	20-500 Hz - 2g	20-500 Hz - 2g	22-2,000 Hz - 5g
RANDOM	VITA 47-Class V1 (design to meet)	VITA 47-Class V1 (design to meet)	VITA 47-Class V3
SHOCK (OPERATING)	20g/11 ms Half Sine	20g/11 ms Half Sine	40g/20 ms Half Sine
ALTITUDE (OPERATING)	-1,500 to 60,000 ft	-1,500 to 60,000 ft	-1,500 to 60,000 ft
RELATIVE HUMIDITY	90% without condensation	95% without condensation	95% without condensation

PRELIMINARY

▶ ORDERING INFORMATION

ARTICLE	ORDER CODE	DESCRIPTION
VM6054	VM6054-SA48-00110000	6U Single slot 4HP (0,8") VME SBC 2,1GHz Intel® quad-core Corei7 3612QE processor, 8 GB dual bank DDR3-SDRAM with ECC/ no soldered Flash, two PMC/XMC slots, Air-Cooled VITA 47 Class AC1 (0°C to +55°C)
VM6054	VM6054-SA48-02110000	6U Single slot 4HP (0,8") VME SBC 2,1GHz Intel® quad-core Corei7 3612QE processor, 8 GB dual bank DDR3-SDRAM with ECC/ no soldered Flash, one PMC/XMC slot, personality module providing 2 DP and 1 VGA on front, Air-Cooled VITA 47 Class AC1 (0°C to +55°C)
VM6054	VM6054-RC48-20110000	6U single slot 4 HP (0,8") VME SBC 2,1 GHz Intel® quad-core Core i7 3612QE processor, 8 GB dual bank DDR3-SDRAM with ECC / Soldered Flash 16 GB SATA SSD SLC, two PMC/XMC slots, standard VME, 3 GPIO on P0, Conduction Cooled VITA 47 Class CC3 (-40°C to +71°C).
ASSOCIATED PRODUCTS:		
REAR TRANSITION MODULES	PBV36-P0-VM6-00 PBV36-P0-VM6-00V	2x 10/100/1000BASE-T Ethernet, 1x USB, 1x SMB, 2x serial lines , 3x GPIOs, 2x SATA, 1x PCI Express 2x 10/100/1000BASE-T Ethernet, 1x USB, 1x SMB, 2x serial lines , 3x GPIOs, 2x SATA, 1x PCI Express with conformal coating
TURNKEY SYSTEM	EZ1-VM6054-00-L	Turnkey evaluation and development platform (Plug& Play), 1U 19" Chassis, power input 110/230VAC, air cooled, 2-slot 6U VME backplane, VM6054-SA48-301100 Single Board Computer, PBV36-P0-VM6-00, I/O cables kit Operating Software: Linux Fedora, Benchmark suite (CPU, memory, network...)
FLASH DISK MODULE	FDM-SATA-xGB-xxx	SATA Flash Module (various sizes available in respect with SA and RC environmental class)
MEDIA MOUNTING KIT	KIT-DISK25-SATA	2.5" SATA HDD/SSD onboard mounting kit (within 4 HP)
PMC CARRIER	V2PMC2-xx-xxx	6U VME PMC Carrier (various option available for air cooled and conduction cooled environment)

▶ CORPORATE OFFICES

EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany
Tel.: + 49 821 4086 0
Fax: + 49 821 4086 111
info@kontron.com

NORTH AMERICA

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: + 1 888 294 4558
Fax: + 1 858 677 0898
info@us.kontron.com

ASIA PACIFIC

1~2F, 10 Building, No. 8 Liangshuihe 2nd Street,
Economical & Technological Development Zone,
Beijing, 100176, P.R.China
Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn

Copyright © 2015 Kontron AG. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Kontron and the Kontron logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized. Specifications are subject to change without notice. VM6054 - 20160401-MB

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP