

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

TRILITHIC






Figure 1.

Trilithic's RA series rotary attenuators are recognized worldwide as the standard for durable, precise signal level control. The series is divided into both 50 and 75 ohm units with attenuation as high as 120 dB dynamic range (in 10 dB steps) on the RA-120; or as low as 1 dB range (in 0.1 dB steps) on the RA-53 and RA-73. A firm, snap action detent locks in the desired attenuation as indicated on the supplied control knob. Low VSWR and insertion loss is assured throughout the range of each unit with tightly controlled pad values and machining tolerances. A broad selection of standard connectors is offered for various applications and includes BNC as standard, plus N, SMA, TNC, or F types.

Specifications	RA-50*	RA-70*	RA-51*	RA-71*
Frequency Range	DC-2 GHz	DC-1 GHz	DC-2 GHz	DC-1 GHz
dB Value	0 to 10 by 1 dB	0 to 10 by 1 dB	0 to 70 by 10 dB	0 to 70 by 10 dB
Connectors	BNC, N, SMA, TNC	BNC, N, TNC, F	BNC, N, SMA, TNC	BNC, N, TNC, F
Impedance	50 Ohms	75 Ohms	50 Ohms	75 Ohms
VSWR	1.2:1 to 1 GHz 1.3:1 to 1.5 GHz 1.5:1 to 2 GHz	1.15:1 to 0.5 GHz 1.3:1 to 1 GHz	1.2:1 to 0.5 GHz 1.3:1 to 1 GHz 1.5:1 to 1.5 GHz	1.2:1 to 0.5 GHz 1.3:1 to 1 GHz
Accuracy	±0.1 dB to 0.03 GHz ±0.2 dB to 0.5 GHz ±0.25 dB to 1 GHz ±0.5 dB to 2 GHz	±0.1 dB to 0.03 GHz ±0.2 dB to 0.5 GHz ±0.3 dB to 1 GHz	±0.2 dB to 0.03 GHz ±0.5 dB to 0.5 GHz ±1 dB to 1 GHz ±1 dB or 2% to 1.5 GHz	±0.2 dB to 0.03 GHz ±0.5 dB to 0.5 GHz ±1 dB to 1 GHz
Insertion Loss	0.1 dB max. to 0.5 GHz 0.3 dB max. to 1 GHz 0.5 dB max. to 2 GHz	0.1 dB max. to 0.5 GHz 0.3 dB max. to 1 GHz 0.4 dB max. to 2 GHz	0.1 dB max. to 0.5 GHz 0.3 dB max. to 1 GHz 0.4 dB max. to 2 GHz	0.1 dB max. to 0.5 GHz 0.3 dB max. to 1 GHz
Temperature	-20° to +125°C	-20° to +125°C	-20° to +125°C	-20° to +125°C
Average Power	1 Watt (25°C)	1 Watt (25°C)	0.5 Watt (25°C)	0.5 Watt (25°C)
Peak Power	750 Watts, 3µSec. pulse	750 Watts, 3µSec. pulse	750 Watts, 3µSec. pulse	750 Watts, 3µSec. pulse
Rotation	30 degrees	30 degrees	45 degrees	45 degrees
Weight	10 ounces	10 ounces	12 ounces	12 ounces
Housing	Irridited Aluminum	Irridited Aluminum	Irridited Aluminum	Irridited Aluminum
Dimensions	See Figure 1	See Figure 1	See Figure 2	See Figure 2

Call Toll Free For More Information • 1-800-344-2412 (U.S.A. & Canada)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

All Models

Connector	X
BNC	2.59
F	2.50
N	2.81
SMA	2.18
TNC	2.59




Figure 2.

Specifications	RA-53*	RA-73*	RA-100*	RA-120*
Frequency Range	DC-1 GHz	DC-1 GHz	DC-1.2 GHz	0.01-0.5 GHz
dB Value	0 to 1 by 0.1 dB	0 to 1 by 0.1 dB	0 to 100 by 10 dB	0 to 120 by 10 dB
Connectors	BNC, N, SMA, TNC	BNC, N, TNC, F	BNC, N, SMA, TNC	BNC, N, SMA, TNC
Impedance	50 Ohms	75 Ohms	50 Ohms	50 Ohms
VSWR	1.1:1 to 0.5 GHz 1.2:1 to 1 GHz	1.1:1 to 0.5 GHz 1.2:1 to 1 GHz	1.1:1 to 0.5 GHz 1.2:1 to 1 GHz 1.4:1 to 1.2 GHz	1.1:1 to 0.5 GHz
Accuracy	±0.02 dB to 0.03 GHz ±0.03 dB to 0.5 GHz ±0.06 dB to 1 GHz	±0.02 dB to 0.03 GHz ±0.03 dB to 0.5 GHz ±0.06 dB to 1 GHz	±0.3 dB or 1% to 0.03 GHz ±0.3 dB or 2% to 0.5 GHz ±3% to 1 GHz ±4% to 1.2 GHz	±0.3 dB or 1% to 0.03 GHz ±0.3 dB or 2% to 0.5 GHz
Insertion Loss	0.6 dB max. to 0.5 GHz 0.8 dB max. to 1 GHz	0.6 dB max. to 0.5 GHz 0.8 dB max. to 1 GHz	0.1 dB max. to 0.5 GHz 0.3 dB max. to 1 GHz 0.4 dB max. to 1.2 GHz	0.1 dB max. to 0.5 GHz
Temperature	-20° to +125°C	-20° to +125°C	-20° to +125°C	-20° to +125°C
Average Power	1 Watt (25°C)	1 Watt (25°C)	0.5 Watt (25°C)	0.5 Watt (25°C)
Peak Power	750 Watts, 3µSec. pulse	750 Watts, 3µSec. pulse	750 Watts, 3µSec. pulse	750 Watts, 3µSec. pulse
Rotation	30 degrees	30 degrees	30 degrees	27 degrees
Weight	10 ounces	10 ounces	13.5 ounces	13.5 ounces
Housing	Irridited Aluminum	Irridited Aluminum	Irridited Aluminum	Irridited Aluminum
Dimensions	See Figure 1	See Figure 1	See Figure 2	See Figure 2

* Connector types should be included in model number.
Example: RA-50 BNC

Note: Specifications valid through rated frequency range of each model.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP