

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *MAC 34B-AAB-GDNB-1BE* at our website: *Click HERE*

Circuit bar mounting

non plug-in cylinder ports in base	non plug-in cylinder ports in valve	plug-in	plug-in with F. C.	plug-in with Pr. Reg.	plug-in with Pr. Reg. and F. C.	add-on style plug-in	add-on style plug-in with F. C.
add-on style plug-in with Pr. Reg.	add-on style plug-in with Pr. Reg. and F. C.	plug-in add-a-unit stations	plug-in add-a-unit stations with F. C.	plug-in add-a-unit stations with Pr. Reg.	plug-in add-a-unit stations with F. C. and Pr. Reg.	plug-in with pre-wired connector	plug-in with F. C. and pre-wired connector
plug-in with Pr. Reg. and pre-wired connector	din rail, plug-in with pre-wired connector	din rail, plug-in with F. C. and pre-wired connector					



SERIES FEATURES

- High force MACSOLENOID®.
- Universal porting.
- #10-32 or M5 ports.
- Rated for lubricated or non-lubricated service.
- 10mm direct operated.
- Cylinder port in valve or in circuit bar.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series **34**

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.11C_v**	non plug-in cylinder ports in base

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.



Reset

HOW TO ORDER 34B-xxx-Gxxx-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Pressure range : 0 to 120 PSI	○ 34B-LOO-G*xxx-xxx*	○ 34B-NOO-G*xxx-xxx*

SOLENOID OPERATOR ➤ G *XX X- X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Wire length
○ *A*	18"
○ *C*	36"
○ *x*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *KA*	Mini connector
○ *KT*	Mini connector with light
○ *BA*	Flying leads
○ *BT*	Flying leads with light
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR EBP34B-xxxx-xx

Port size	Side cylinder ports	Bottom cylinder ports
M5	○ EBP34B-001D-*xx*	○ EBP34B-002D-*xx*
# 10-32	○ EBP34B-001B-*xx*	○ EBP34B-002B-*xx*

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to 50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.11C_v, 2.5 W : 0.084C_v, 1.8 W : 0.061C_v
:	50 cm^3/min
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 3.4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.

Options : • Isolation of inlet and/or exhaust. Special bar. Consult factory.

DIMENSIONS



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size (Inlet & Exhaust)	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**# 10-32 - 1/8"**	**0.11C_v**	non plug-in cylinder ports in valve

OPERATIONAL BENEFITS

1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.





Reset

HOW TO ORDER

34B-xxx-Gxxx-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Valve port size	Universal valve	NC only valve
		
M5	○ 34B-ABA-G*xxx-xxx*	○ 34B-ABB-G*xxx-xxx*
# 10-32	○ 34B-AAA-G*xxx-xxx*	○ 34B-AAB-G*xxx-xxx*

SOLENOID OPERATOR ➤ G *XX X- X XX**

XX	Voltage	*X*	Wire length	*X*	Manual operator	*XX*	Electrical connection
○ *DC*	24VDC (1.8 W)	○ *A*	18"	○ *1*	Non-locking	○ *KA*	Mini connector
○ *DD*	24VDC (2.5 W)	○ *C*	36"			○ *KT*	Mini connector with light
○ *DF*	24VDC (4.0 W)	○ *x*	Other Options			○ *BA*	Flying leads
○ *xx*	Other Options					○ *BT*	Flying leads with light
						○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR

EBM34A-xxxx-xx

Port size COMMON INLET & EXHAUST	
# 10-32	○ EBM34A-001B-*xx*
1/8" NPTF	○ EBM34A-002A-*xx*

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.11C_v, 2.5 W : 0.084C_v, 1.8 W : 0.061C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 3.4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Valve fastening kit : M34001-01 (1/8" Bar); M34001-21 (#10-32 Bar) • Blanking plate : 30456-A.

Options : • Isolation of inlet and/or exhaust. Special bar. Consult factory.

DIMENSIONS



Port size	A	B	C	D	E	F	G
1/8"	16.0	47.5	57.4	8.0	23.0	31.0	8.0
M5	12.0	43.5	51.5	9.0	18.0	26.0	6.0

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series **34**

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C$_V$**	plug-in

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.



Reset

HOW TO ORDER 34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve 	NC only valve 
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	**Voltage**
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	**Manual operator**
○ *1*	Non-locking

XX	**Electrical connection**
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR ECD034B-00xxx-AOxx

Port size	Side cylinder ports (10.5 mm)	Bottom cylinder ports (10.5 mm)
M5	○ ECD034B-001AD-AO*xx*	○ ECD034B-002AD-AO*xx*
# 10-32	○ ECD034B-001AB-AO*xx*	○ ECD034B-002AB-AO*xx*

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.
clic for multi-pin connector option (9, 15 or 25).

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	55.5	66.0	76.5	87.0	97.5	108.0	118.5	129.0	139.5

Consult "Precautions" before use, installation or service of MAC Valves.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C$_V$**	plug-in with F. C.



OPERATIONAL BENEFITS

1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER 34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR WITH FLOW CONTROLS ECD034B-00xxx-AOxx

Port size	Side cylinder ports (10.5 mm)	Bottom cylinder ports (10.5 mm)
M5	○ ECD034B-005AD-AO*xx*	○ ECD034B-006AD-AO*xx*
# 10-32	○ ECD034B-005AB-AO*xx*	○ ECD034B-006AB-AO*xx*

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.
clic for multi-pin connector option (9, 15 or 25).

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	55.5	66.0	76.5	87.0	97.5	108.0	118.5	129.0	139.5

Consult "Precautions" before use, installation or service of MAC Valves.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C_v**	plug-in with Pr. Reg.

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	◯ 34B-LOO-G*xx*O-*xxx*	◯ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
◯ *DC*	24VDC (1.8 W)
◯ *DD*	24VDC (2.5 W)
◯ *DF*	24VDC (4.0 W)
◯ *xx*	Other Options

X	Manual operator
◯ *1*	Non-locking

XX	Electrical connection
◯ *DJ*	Plug-in
◯ *DT*	Plug-in with light
◯ *DE*	Plug-in with suppression diode
◯ *DV*	Plug-in with light and suppression diode
◯ *xx*	Other Options

ECD034B-00xxx-AOxx

HOW TO ORDER CIRCUIT BAR FOR PRESSURE REGULATORS ** (to be ordered separately)

Port size	Bottom cylinder ports (10.5 mm)	Side cylinder ports (10.5 mm)
M5	◯ ECD034B-004AD-AO*xx*	◯ ECD034B-003AD-AO*xx*
# 10-32	◯ ECD034B-004AB-AO*xx*	◯ ECD034B-003AB-AO*xx*

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.
clic for multi-pin connector option (9, 15 or 25).

** Pressure Regulators :

PR44A-AOxx

- ◯ Y=A (no gage port)
- ◯ Y=B (with gage port)
- ◯ X=A (0 to 100 PSI)
- ◯ X=B (0 to 60 PSI)
- ◯ X=C (0 to 40 PSI)
- ◯ X=D (0 to 15 PSI)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Blanking plate for regulator : N-44003. • Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	55.5	66.0	76.5	87.0	97.5	108.0	118.5	129.0	139.5

Consult "Precautions" before use, installation or service of MAC Valves.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


MAC

Series **34**

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.09C_v**	plug-in with Pr. Reg. and F. C.

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.



Reset

HOW TO ORDER 34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve 	NC only valve 
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

ECD034B-00xxx-AOxx

HOW TO ORDER CIRCUIT BAR WITH FLOW CONTROLS AND PRESSURE REGULATORS ** (pressure regulators to be ordered separately)

Port size	Bottom cylinder ports (10.5 mm)	Side cylinder ports (10.5 mm)
M5	○ ECD034B-007AD-AO*xx*	○ ECD034B-008AD-AO*xx*
# 10-32	○ ECD034B-007AB-AO*xx*	○ ECD034B-008AB-AO*xx*

Number of stations (03=3 stations) ☐
Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.
clic for multi-pin connector option (9, 15 or 25).

** Pressure Regulators :

PR44A-AOxx

- ○ Y=A (no gage port)
- ○ Y=B (with gage port)
- ○ X=A (0 to 100 PSI)
- ○ X=B (0 to 60 PSI)
- ○ X=C (0 to 40 PSI)
- ○ X=D (0 to 15 PSI)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180. • Blanking plate for regulator : N-44003.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	55.5	66.0	76.5	87.0	97.5	108.0	118.5	129.0	139.5

Consult "Precautions" before use, installation or service of MAC Valves.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C$_v$**	add-on style plug-in

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	◯ 34B-LOO-G*xx*O-*xxx*	◯ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
◯ *DC*	24VDC (1.8 W)
◯ *DD*	24VDC (2.5 W)
◯ *DF*	24VDC (4.0 W)
◯ *xx*	Other Options

X	Manual operator
◯ *1*	Non-locking

XX	Electrical connection
◯ *DJ*	Plug-in
◯ *DT*	Plug-in with light
◯ *DE*	Plug-in with suppression diode
◯ *DV*	Plug-in with light and suppression diode
◯ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR

ECD034B-00xxx-AOxx

Port size	Side cylinder ports (10.5 mm)	Bottom cylinder ports (10.5 mm)
M5	◯ ECD034B-001BD-AO*xx*	◯ ECD034B-002BD-AO*xx*
# 10-32	◯ ECD034B-001BB-AO*xx*	◯ ECD034B-002BB-AO*xx*

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.
clic for multi-pin connector option (9, 15 or 25).
add-a-unit stations may be added to above bars. Clic here for model numbers.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	57.0	67.5	78.0	88.5	99.0	109.5	120.0	130.5	141.0

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C$_V$**	add-on style plug-in with F. C.

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ DC	24VDC (1.8 W)
○ DD	24VDC (2.5 W)
○ DF	24VDC (4.0 W)
○ xx	Other Options

X	Manual operator
○ 1	Non-locking

XX	Electrical connection
○ DJ	Plug-in
○ DT	Plug-in with light
○ DE	Plug-in with suppression diode
○ DV	Plug-in with light and suppression diode
○ xx	Other Options

HOW TO ORDER CIRCUIT BAR WITH FLOW CONTROLS

ECD034B-00xxx-AOxx

Port size	Side cylinder ports (10.5 mm)	Bottom cylinder ports (10.5 mm)
M5	○ ECD034B-005BD-AO*xx*	○ ECD034B-006BD-AO*xx*
# 10-32	○ ECD034B-005BB-AO*xx*	○ ECD034B-006BB-AO*xx*

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.
clic for multi-pin connector option (9, 15 or 25).
add-a-unit stations may be added to above bars. Clic here for model numbers.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	57.0	67.5	78.0	88.5	99.0	109.5	120.0	130.5	141.0

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C$_V$**	add-on style plug-in with Pr. Reg.

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ DC	24VDC (1.8 W)
○ DD	24VDC (2.5 W)
○ DF	24VDC (4.0 W)
○ xx	Other Options

X	Manual operator
○ 1	Non-locking

XX	Electrical connection
○ DJ	Plug-in
○ DT	Plug-in with light
○ DE	Plug-in with suppression diode
○ DV	Plug-in with light and suppression diode
○ xx	Other Options

ECD034B-00xxx-AOxx

HOW TO ORDER CIRCUIT BAR FOR PRESSURE REGULATORS ** (to be ordered separately)

Port size	Bottom cylinder ports (10.5 mm)	Side cylinder ports (10.5 mm)
M5	○ ECD034B-004BD-AO*xx*	○ ECD034B-003BD-AO*xx*
# 10-32	○ ECD034B-004BB-AO*xx*	○ ECD034B-003BB-AO*xx*

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.
clic for multi-pin connector option (9, 15 or 25).
add-a-unit stations may be added to above bars. Clic here for model numbers.

** Pressure Regulators :

PR44A-AOxx

- ○ Y=A (no gage port)
- ○ Y=B (with gage port)
- ○ X=A (0 to 100 PSI)
- ○ X=B (0 to 60 PSI)
- ○ X=C (0 to 40 PSI)
- ○ X=D (0 to 15 PSI)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180. • Blanking plate for regulator : N-44003.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	57.0	67.5	78.0	88.5	99.0	109.5	120.0	130.5	141.0

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


MAC

Series **34**

Function	Port size	Flow [Max]	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.09C_V**	add-on style plug-in with Pr. Reg. and F. C.

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.



Reset

HOW TO ORDER 34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

ECD034B-00xxx-AOxx

HOW TO ORDER CIRCUIT BAR WITH FLOW CONTROLS AND PRESSURE REGULATORS ** (pressure regulators to be ordered separately)

Port size	Bottom cylinder ports (10.5 mm)	Side cylinder ports (10.5 mm)
M5	○ ECD034B-007BD-AO*xx*	○ ECD034B-008BD-AO*xx*
# 10-32	○ ECD034B-007BB-AO*xx*	○ ECD034B-008BB-AO*xx*

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.
clic for multi-pin connector option (9, 15 or 25).
add-a-unit stations may be added to above bars. Clic here for model numbers.

** Pressure Regulators :

PR44A-AOxx

- ○ Y=A (no gage port)
- ○ Y=B (with gage port)
- ○ X=A (0 to 100 PSI)
- ○ X=B (0 to 60 PSI)
- ○ X=C (0 to 40 PSI)
- ○ X=D (0 to 15 PSI)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Blanking plate for regulator : N-44003. • Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	57.0	67.5	78.0	88.5	99.0	109.5	120.0	130.5	141.0

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C$_V$**	plug-in add-a-unit stations

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR

ECD034B-00xxx-AOxx

Port size	Side cylinder ports	Bottom cylinder ports
M5	○ ECD034B-001CD-AO*xx*	○ ECD034B-002CD-AO*xx*
# 10-32	○ ECD034B-001CB-AO*xx*	○ ECD034B-002CB-AO*xx*

Number of stations (03=3 stations) - Maximum length is 4 stations ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number. when add-a-unit stations are added to bars with a multi-pin connector, MOD. SD03 should be included with add-a-unit model number.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	57.0	67.5	78.0	88.5	99.0	109.5	120.0	130.5	141.0

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow [Max]	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C_v**	plug-in add-a-unit stations with F. C.

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤

G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR WITH FLOW CONTROLS

ECD034B-00xxx-AOxx

Port size	Side cylinder ports	Bottom cylinder ports
M5	○ ECD034B-005CD-AO*xx*	○ ECD034B-006CD-AO*xx*
# 10-32	○ ECD034B-005CB-AO*xx*	○ ECD034B-006CB-AO*xx*

Number of stations (03=3 stations) - Maximum length is 4 stations ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number. when add-a-unit stations are added to bars with a multi-pin connector, MOD. SD03 should be included with add-a-unit model number.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	57.0	67.5	78.0	88.5	99.0	109.5	120.0	130.5	141.0

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C_v**	plug-in add-a-unit stations with Pr. Reg.



OPERATIONAL BENEFITS

1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER 34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

ECD034B-00xxx-AOxx

HOW TO ORDER CIRCUIT BAR FOR PRESSURE REGULATORS ** (to be ordered separately)

Port size	Side cylinder ports	Bottom cylinder ports
M5	○ ECD034B-003CD-AO*xx*	○ ECD034B-004CD-AO*xx*
# 10-32	○ ECD034B-003CB-AO*xx*	○ ECD034B-004CB-AO*xx*

Number of stations (03=3 stations) - Maximum length is 4 stations ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number. when add-a-unit stations are added to bars with a multi-pin connector, MOD. SD03 should be included with add-a-unit model number.

** Regulator ordered separately-see below

PR44A-AOxx

- ○ Y=A (no gage port)
- ○ Y=B (with gage port)
- ○ X=A (0 to 100 PSI)
- ○ X=B (0 to 60 PSI)
- ○ X=C (0 to 40 PSI)
- ○ X=D (0 to 15 PSI)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180. • Blanking plate for regulator : N-44003.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	57.0	67.5	78.0	88.5	99.0	109.5	120.0	130.5	141.0

Consult "Precautions" before use, installation or service of MAC Valves.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


MAC

Series **34**

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C_v**	plug-in add-a-unit stations with F. C. and Pr. Reg.

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.



Reset

HOW TO ORDER 34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve 	NC only valve 
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

ECD034B-00xxx-AOxx

HOW TO ORDER CIRCUIT BAR WITH FLOW CONTROLS AND PRESSURE REGULATORS ** (pressure regulators to be ordered separately)

Port size	Side cylinder ports	Bottom cylinder ports
M5	○ ECD034B-008CD-AO*xx*	○ ECD034B-007CD-AO*xx*
# 10-32	○ ECD034B-008CB-AO*xx*	○ ECD034B-007CB-AO*xx*

Number of stations (03=3 stations) - Maximum length is 4 stations ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number. when add-a-unit stations are added to bars with a multi-pin connector, MOD. SD03 should be included with add-a-unit model number.

** Regulator ordered separately-see below

PR44A-AOxx

- ○ Y=A (no gage port)
- ○ Y=B (with gage port)
- ○ X=A (0 to 100 PSI)
- ○ X=B (0 to 60 PSI)
- ○ X=C (0 to 40 PSI)
- ○ X=D (0 to 15 PSI)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Blanking plate for regulator : N-44003. • Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Number of stations	2	3	4	5	6	7	8	9	10
DIM. L	57.0	67.5	78.0	88.5	99.0	109.5	120.0	130.5	141.0

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow [Max]	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32, 4mm tube receptacle**	**0.11C_v**	plug-in with pre-wired connector

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤

G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR

ECF34B-00xxx-xxxx

Port size	Side cylinder ports (10.5 mm)	Bottom cylinder ports (10.5 mm)
M5	○ ECF34B-00ADA-*zzxx*	○ ECF34B-00BDA-*zzxx*
# 10-32	○ ECF34B-00ABA-*zzxx*	○ ECF34B-00BBA-*zzxx*
4 mm tube receptacle	○ ECF34B-00AEA-*zzxx*	---------

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.

L=Left Side; R=Right Side

ZZ	Connector	ZZ	Connector
○ LA	9 Pin Sub D*	○ RA	9 Pin Sub D*
○ LB	15 Pin Sub D*	○ RB	15 Pin Sub D*
○ LC	25 Pin Sub D*	○ RC	25 Pin Sub D*
○ LD	10 Pin Ribbon Cable**	○ RD	10 Pin Ribbon Cable**
○ LE	16 Pin Ribbon Cable**	○ RE	16 Pin Ribbon Cable**
○ LF	20 Pin Ribbon Cable**	○ RF	20 Pin Ribbon Cable**
○ LG	26 Pin Ribbon Cable**	○ RG	26 Pin Ribbon Cable**
○ LH	3/8" NPSM Conduit Port	○ RH	3/8" NPSM Conduit Port
	Standard Base Wires		Standard Base Wires

* MIL. Spec; MIL-C-24308

** MIL. Spec; MIL-C-83503

Note: Left and right end is determined by facing conduit passage.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow [Max]	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32, 4mm tube receptacle**	**0.11C_v**	plug-in with F. C. and pre-wired connector



OPERATIONAL BENEFITS

1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER 34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR WITH FLOW CONTROLS

ECF34B-00xxx-xxxx

Port size	Side cylinder ports (10.5 mm)	Bottom cylinder ports (10.5 mm)
M5	○ ECF34B-00CDA-*zzxx*	○ ECF34B-00DDA-*zzxx*
# 10-32	○ ECF34B-00CBA-*zzxx*	○ ECF34B-00DBA-*zzxx*
4 mm tube receptacle	○ ECF34B-00CEA-*zzxx*	--------

Number of stations (03=3 stations) ☐

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.

L=Left Side; R=Right Side

ZZ	Connector	ZZ	Connector
○ LA	9 Pin Sub D*	○ RA	9 Pin Sub D*
○ LB	15 Pin Sub D*	○ RB	15 Pin Sub D*
○ LC	25 Pin Sub D*	○ RC	25 Pin Sub D*
○ LD	10 Pin Ribbon Cable**	○ RD	10 Pin Ribbon Cable**
○ LE	16 Pin Ribbon Cable**	○ RE	16 Pin Ribbon Cable**
○ LF	20 Pin Ribbon Cable**	○ RF	20 Pin Ribbon Cable**
○ LG	26 Pin Ribbon Cable**	○ RG	26 Pin Ribbon Cable**
○ LH	3/8" NPSM Conduit Port Standard Base Wires	○ RH	3/8" NPSM Conduit Port Standard Base Wires

* MIL. Spec; MIL-C-24308

** MIL. Spec; MIL-C-83503

Note: Left and right end is determined by facing conduit passage.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.11C_v, 2.5 W : 0.09C_v, 1.8 W : 0.06C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


MAC

Series 34

Function	Port size	Flow [Max]	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32**	**0.10C_v**	plug-in with Pr. Reg. and pre-wired connector

OPERATIONAL BENEFITS

1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.





Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve 	NC only valve 
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR FOR PRESSURE REGULATORS ** (to be ordered separately)

ECF34B-00xxx-xxxx

Port size	Bottom cylinder ports (10.5 mm)
M5	○ ECF34B-00EDA-*zzxx*
# 10-32	○ ECF34B-00EBA-*zzxx*

Number of stations (03=3 stations) ☐

** Pressure Regulators :

PR44A-AOxx

- ○ Y=A (no gage port)
- ○ Y=B (with gage port)
- ○ X=A (0 to 100 PSI)
- ○ X=B (0 to 60 PSI)
- ○ X=C (0 to 40 PSI)
- ○ X=D (0 to 15 PSI)

L=Left Side; R=Right Side

ZZ	Connector	ZZ	Connector
○ LA	9 Pin Sub D*	○ RA	9 Pin Sub D*
○ LB	15 Pin Sub D*	○ RB	15 Pin Sub D*
○ LC	25 Pin Sub D*	○ RC	25 Pin Sub D*
○ LD	10 Pin Ribbon Cable**	○ RD	10 Pin Ribbon Cable**
○ LE	16 Pin Ribbon Cable**	○ RE	16 Pin Ribbon Cable**
○ LF	20 Pin Ribbon Cable**	○ RF	20 Pin Ribbon Cable**
○ LG	26 Pin Ribbon Cable**	○ RG	26 Pin Ribbon Cable**
○ LH	3/8" NPSM Conduit Port Standard Base Wires	○ RH	3/8" NPSM Conduit Port Standard Base Wires

* MIL. Spec; MIL-C-24308

** MIL. Spec; MIL-C-83503

Note: Left and right end is determined by facing conduit passage.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.10C_v, 2.5 W : 0.09C_v, 1.8 W : 0.07C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Blanking plate for regulator : N-44003. • Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


MAC

Series 34

Function	Port size	Flow (Max)	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32, 4mm tube receptacle**	**0.11C_v**	din rail, plug-in with pre-wired connector

OPERATIONAL BENEFITS

1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.





Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤ G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR

ECF34B-00xxx-xxxx

Port size	Side cylinder ports (10.5 mm)
M5	○ ECF34B-00ADB-*zzxx*
# 10-32	○ ECF34B-00ABB-*zzxx*
4 mm tube receptacle	○ ECF34B-00AEB-*zzxx*

Number of stations (03=3 stations) ☐

Din rail spec. (EN50 022)

Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.

L=Left Side; R=Right Side

ZZ	Connector	ZZ	Connector
○ LA	9 Pin Sub D*	○ RA	9 Pin Sub D*
○ LB	15 Pin Sub D*	○ RB	15 Pin Sub D*
○ LC	25 Pin Sub D*	○ RC	25 Pin Sub D*
○ LD	10 Pin Ribbon Cable**	○ RD	10 Pin Ribbon Cable**
○ LE	16 Pin Ribbon Cable**	○ RE	16 Pin Ribbon Cable**
○ LF	20 Pin Ribbon Cable**	○ RF	20 Pin Ribbon Cable**
○ LG	26 Pin Ribbon Cable**	○ RG	26 Pin Ribbon Cable**
○ LH	3/8" NPSM Conduit Port	○ RH	3/8" NPSM Conduit Port
	Standard Base Wires		Standard Base Wires

* MIL. Spec; MIL-C-24308

** MIL. Spec; MIL-C-83503

Note: Left and right end is determined by facing conduit passage.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.11C_v, 2.5 W : 0.09C_v, 1.8 W : 0.06C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

Function	Port size	Flow [Max]	Circuit bar mounting
3/2 NO-NC	**M5 - #10-32, 4 mm tube receptacle**	**0.11C_v**	din rail, plug-in with F. C. and pre-wired connector

OPERATIONAL BENEFITS



1. 10 mm valve, direct solenoid operated.
2. Balanced poppet, immune to variations of pressure.
3. Short stroke with high flow.
4. The patented solenoid develops high shifting forces.
5. Powerful return spring.
6. Flow is specifically adjusted on each valve.
7. Manual operator standard on all valves.

Reset

HOW TO ORDER

34B-xxx-GxxO-xxx

HOW TO ORDER VALVE FOR CIRCUIT BAR MOUNTING

Port size (see base)	Universal valve	NC only valve
		
Valve less base	○ 34B-LOO-G*xx*O-*xxx*	○ 34B-NOO-G*xx*O-*xxx*

SOLENOID OPERATOR ➤

G *XX* O- *X XX**

XX	Voltage
○ *DC*	24VDC (1.8 W)
○ *DD*	24VDC (2.5 W)
○ *DF*	24VDC (4.0 W)
○ *xx*	Other Options

X	Manual operator
○ *1*	Non-locking

XX	Electrical connection
○ *DJ*	Plug-in
○ *DT*	Plug-in with light
○ *DE*	Plug-in with suppression diode
○ *DV*	Plug-in with light and suppression diode
○ *xx*	Other Options

HOW TO ORDER CIRCUIT BAR WITH FLOW CONTROLS

ECF34B-00xxx-xxxx

Port size	Side cylinder ports (10.5 mm)
M5	○ ECF34B-00CDB-*zzxx*
# 10-32	○ ECF34B-00CBB-*zzxx*
4 mm tube receptacle	○ ECF34B-00CEB-*zzxx*

Number of stations (03=3 stations) ☐
Din rail spec. (EN50 022)
Note : ☐ clic for valves mounted on base at the factory, add - 9 to the model number.

L=Left Side; R=Right Side

ZZ	Connector	ZZ	Connector
○ LA	9 Pin Sub D*	○ RA	9 Pin Sub D*
○ LB	15 Pin Sub D*	○ RB	15 Pin Sub D*
○ LC	25 Pin Sub D*	○ RC	25 Pin Sub D*
○ LD	10 Pin Ribbon Cable**	○ RD	10 Pin Ribbon Cable**
○ LE	16 Pin Ribbon Cable**	○ RE	16 Pin Ribbon Cable**
○ LF	20 Pin Ribbon Cable**	○ RF	20 Pin Ribbon Cable**
○ LG	26 Pin Ribbon Cable**	○ RG	26 Pin Ribbon Cable**
○ LH	3/8" NPSM Conduit Port	○ RH	3/8" NPSM Conduit Port
	Standard Base Wires		Standard Base Wires

* MIL. Spec; MIL-C-24308
** MIL. Spec; MIL-C-83503
Note: Left and right end is determined by facing conduit passage.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MAC

Series 34

100% OF PRODUCTION TESTED 100%

WARRANTY 18 MONTHS

TECHNICAL DATA


Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 120 PSI
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
Filtration :	40 µ
Temperature range :	0°F to 120°F (-18°C to +50°C)
Orifice :	1.8 mm
Flow (at 6 bar, ΔP=1bar) :	4 W : 0.11C_v, 2.5 W : 0.09C_v, 1.8 W : 0.06C_v
Coil :	General purpose class A, continuous duty, encapsulated
Voltage range :	-15% to +10% of nominal voltage
Power :	4 W - 2.5 W - 1.8 W
Response times :	Energize : 4 ms
(with 4 W coil)	De-energize : 1.5 ms

Note : • Valve and coil are not interchangeable.

Spare parts : • Seal between valve and bar : 16595. • Mounting screw (x2) : 35031. • Blanking plate : M-34005.
• Base wire Plug-in protector : 24180.

Options : • Isolation of inlet and/or exhaust. • BSPP Threads.

DIMENSIONS



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Section 2 Options

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Codification table for voltages / Manual operator / Electrical connection

VALVE CODE ➤ $-G\frac{XX}{1}\frac{X}{2}-\frac{X}{3}\frac{XX}{4}$

OPTIONS AVAILABLE FOR
- solenoid valves 34 & 44 Series

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

OPTIONS

Back

1. VOLTAGE (type 34 Series)	
-G XX X - X XX	VOLTAGE
○ DC	24 VDC (1,8 W)
○ DD	24 VDC (2,5 W)
○ DE	24 VDC (3,0 W)
◉ DF	24 VDC (4,0 W)
○ DJ	12 VDC (1,8 W)
○ DK	12 VDC (2,5 W)
○ DM	12 VDC (3,0 W)
○ DN	12 VDC (4,0 W)

1. VOLTAGE (type 44 Series)	
-G XX X - X XX	VOLTAGE
DA	24 VDC (1,0 W)
DC	24 VDC (1,8 W)
DD	24 VDC (2,5 W)
DF	24 VDC (4,0 W)
DG	12 VDC (1,0 W)
DJ	12 VDC (1,8 W)
DK	12 VDC (2,5 W)
DN	12 VDC (4,0 W)

2. WIRE LENGTH (Common options for 34 & 44 Series)	
-G XX X - X XX	WIRE LENGTH
○ A	18″
○ B	24″
○ C	36″
○ D	48″
○ E	72″
○ F	96″
○ G	120″
○ H	144″

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

3. MANUAL OPERATOR (COMMON OPTIONS FOR 34 & 44 SERIES)

-G XX X - X XX	MANUAL OPERATOR
1	Non-locking recessed
3	Non-locking extended

4. ELECTRICAL CONNECTION (COMMON OPTIONS FOR 34 & 44 SERIES)


-G XX X - X XX	NO CONNECTOR
BA	Flying leads
BB	BA with ground wire
BC	BA with light
BD	BA with light and ground wire
BE	BA with suppression diode
BF	BA with suppression diode and ground wire
BG	BA with suppression diode and light
BH	BA with suppression diode, light and ground wire
BN	BA with suppression diode and blocking diode
BP	BA with suppression diode, blocking diode and ground wire
BR	BA with suppression diode, blocking diode and light
BS	BA with suppression diode, blocking diode, light and ground wire
BT	BA with light
BU	BA with light and ground wire
BV	BA with suppression diode and light
BW	BA with suppression diode, light and ground wire
BX	BA with suppression diode, blocking diode and light
BY	BA with suppression diode, blocking diode, light and ground wire

-G XX X - X XX	PLUG-IN CONNECTOR
KA	Mini connector with flying leads
KB	KA with ground wire
KE	KA with suppression diode
KF	KA with suppression diode and ground wire
KJ	Mini connector for **KA** option
KM	Mini connector for **KB** option
KN	KA with suppression diode and blocking diode
KP	KA with suppression diode, blocking diode and ground wire
KT	KA with light
KU	KA with light and ground wire
KV	KA with suppression diode and light
KW	KA with suppression diode, light and ground wire
KX	KA with suppression diode, blocking diode and light
KY	KA with suppression diode, blocking diode, light and ground wire

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

MOD. SD09






TECHNICAL DATA

- Type «SUB_D»
- Number of contacts : 9
- Solder termination (Dia. 0.6 mm/0.14 mm^2/26-22 AWG)
- Operating current 5 A/contact
- Rated voltage 125 V~
- Temp. range –40° to +125°C
- Insulation resistance ≥ 5.0^9 Ω
- Protection class IP40 (DIN 40050)
- Number of solenoids : 7 max.
- Max. 24 V=/5.4 W per solenoid
- 2 common wires

MOD. SD15






TECHNICAL DATA

- Type «SUB_D»
- Number of contacts : 15
- Solder termination (Dia. 0.6 mm/0.14 mm^2/26-22 AWG)
- Operating current 5 A/contact
- Rated voltage 125 V~
- Temp. range –40° to +125°C
- Insulation resistance ≥ 5.0^9 Ω
- Protection class IP40 (DIN 40050)
- Number of solenoids : 12 max.
- Max. 24 V=/5.4 W per solenoid
- 3 common wires

MOD. SD25






TECHNICAL DATA

- Type «SUB_D»
- Number of contacts : 25
- Solder termination (Dia. 0.6 mm/0.14 mm^2/26-22 AWG)
- Operating current 5 A/contact
- Rated voltage 125 V~
- Temp. range –40° to +125°C
- Insulation resistance ≥ 5.0^9 Ω
- Protection class IP40 (DIN 40050)
- Number of solenoids : 20 max.
- Max. 24 V=/5.4 W per solenoid
- 5 common wires


Note : Use desired MOD. number after circuit bar part number

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Connector termination details




Single solenoid circuit bar




Double solenoid circuit bar


SD09



SD15



SD25



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

PRECAUTIONS CONCERNING THE APPLICATION, INSTALLATION AND SERVICE OF MAC VALVES

The precautions below are important to be read and understood before designing into a system any MAC valve, and before installing or servicing any MAC valve. Improper use, installation or servicing of any MAC valve in some systems could create a hazard to personnel or equipment.

APPLICATION PRECAUTIONS :

INDUSTRIAL USE -

MAC valves are intended for use in industrial pneumatic and/or vacuum systems. They are not intended for consumer use or service. They are general purpose industrial valves with literally thousands of different applications in industrial systems. These products are not inherently dangerous, but they are only a component of an overall system. The system in which they are used must provide adequate safeguards to prevent injury or damage in the event failure occurs, whether it be failure of switches, regulators, cylinders, valves or any other component.

POWER PRESSES -

MAC valves are not designed nor intended to be used to operate and/or control the operation of clutch and/or brake systems on power presses. There are special products on the market for such use.

2-POSITION VALVES -

Some MAC valves are 2-position, 4-way valves. When air is supplied to the inlet port(s) of these valves, there will always be a flow path from the inlet to one of the outlets regardless of which of the two positions the valve is situated. Therefore, if pressurized air retained in the system would present a hazard in the application or servicing of the valve or system, a separate method in the system must be provided to remove the trapped air.

3- POSITION VALVES-

Some MAC valves are 3-position, 4-way valves. These valves are either double solenoid or double remote air operated.
If either of the two operators is in control, air supplied to the inlet port(s) will pass through the valve to one of the outlets as on 2-position, 4-way valves. However, if neither operator is in control, the valve moves to a center position. Listed below are the various center position functions :

A. CLOSED CENTER-

With this type valve, when in the center position all ports are blocked (inlets and exhausts) meaning the air at both outlet ports is trapped. If trapping the air in both outlet ports would present a hazard in the application or servicing, a separate method in the system must be provided to remove the trapped air or this type valve should not be used.

B. OPEN CENTER-

With this type valve, when in the center position, the inlet port(s) is blocked and the two outlet ports are open to the exhaust port(s) of the valve. If having no air in either outlet port would present a hazard in the application or servicing, this type valve should not be used.

C. PRESSURE CENTER-

With this type valve, when in the center position, the inlet port(s) is connected to both outlet ports of the valve. If having pressurized air to either or both outlet ports would present a hazard in the application or servicing of the valve or system, a separate method in the system must be
provided to remove the retained air.

OPERATING SPECIFICATIONS -

MAC valves are to be installed only on applications that meet all operating specifications described in the MAC catalog for the valve.

MANUAL OPERATORS-

Most MAC valves can be ordered with manual operators. Manual operators when depressed, are designed to shift the valve to the same position as would the corresponding solenoid or remote air pilot operator if it were activated. Care must be taken to order a type, if any, that will be safe for the physical location of the manual operator in the system. Accidental activation of a manual operator could create a dangerous situation. If intentional or accidental operation of a valve by a manual operator could create a dangerous situation then the "no operator" option should be used.

REMOTE AIR OPERATED VALVES

Pilot valves supplying signal pressure to remote air operated valves should be 3-way valves with adequate supply and exhaust capacity to provide positive pressurizing and exhausting of the pilot supply line. Pilot lines should be open to exhaust when valves are deenergized.

INSTALLATION AND SERVICE PRECAUTIONS :

A. Do not install or service MAC valves without first making sure both the air and electrical power to the machine are off and that all air has been completely bled from the system.

B. MAC valves should only be installed and/or serviced by qualified, knowledgeable personnel who understand how the specific valve is to be pneumatically piped and electrically connected (where applicable). Flow paths through the valve are shown in the catalog and on the valve by use of ANSI or ISO type standard and graphic symbols. Do not install unless these symbols and the valve functions and operations are thoroughly understood.

C. Before service, maintenance, repair or cleaning, consult local distributor or factory for Parts & Operation Sheet and information on proper cleaning and lubrication agents. Do not subject MAC valves' parts to any foreign substance including lubricants and cleaning agents not specifically recommended by MAC valves, Inc.

D. MAC valves are never to be stepped on while working on a machine. Damage to the valve, or lines to the valve (either air or electrical lines) or accidental activating of a manual operator on the valve could result in a dangerous condition.

WARNING :

Under no circumstances are Mac valves to be used in any application where failure of the valve to operate as intended could jeopardize the safety of the operator or any other person.
- Do not operate outside of pressure range listed on valve label or outside of designated temperature range.
- Air supply must be clean. Contamination of valve can affect proper operation.
- Before attempting to repair, adjust or clean valve, consult catalog, parts & operation sheet, or factory for proper maintenance procedures, lubrication, and cleaning agents. Never attempt to repair or perform other maintenance with air pressure to valve.
- If airline lubrication is used, consult catalog, parts & operation sheet, or factory for recommended lubricants.

LIMITATION OF GUARANTEE

This Guarantee is limited to the replacement or rebuilding of any valve which should fail to operate properly. Valves, under the MAC Guarantee, must be returned (with or without bases) transportation prepaid and received at our factory within the Guarantee period. They will be returned to the customer at the expense of MAC Valves, Inc., and will carry the same guarantee as provided under the Flat Rate Rebuild Program.

DISCLAIMER OF GUARANTEE

No claims for labor, material, time, damage, or transportation are allowable nor will any valve be replaced or rebuilt under this guarantee which has been damaged by the purchaser not in the normal course of its use and maintenance during the warranty period. The guarantee does not apply to loss or damage caused by fire, theft, riot, explosion, labor dispute, act of God, or other causes beyond the control of MAC Valves,Inc. MAC Valves, Inc. shall in no event be liable for remote, special or consequential damages under the MAC Guarantee, nor under any implied warranties, including the implied warranty of merchantability.

The above Guarantee is our manner of extending the engineering and service resources of the MAC Valves, Inc. organization to assure our customer long, and continued satisfaction.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP