ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Mad City Labs PA25-2* at our website: ***Click HERE***

PA25 Amplifier

Features

- *Open Loop Control*
- *Low Noise*
- *High Stability*
- *High Power*
- *Output Voltage: 0 - 150V*
- *Compatible with Mad City Labs piezo actuators*



Product Description

The PA25 is a single channel amplifier suitable for driving low voltage (150V) piezo actuators. The PA25 amplifier combines low noise and outstanding stability with high power output making it ideal for open loop, high resolution control of piezos. The PA25 is equipped with a front panel analog input BNC for high precision command voltage control. A single channel high voltage (0 - 150V) output is conveniently located on the front panel This high voltage BNC connector can be interfaced to our bare piezoactuators for precision motion applications.

Specifications	
Analog Input	*0 V to +10 V*
Command Signal Input Impedance	*10 kΩ*
Gain (0 - 10V input)	*15 V_{our}/1V_{in}*
Amplifier Output Voltage	*0 V to +150 V*
Maximum Drive Current (continuous)	*160 mA*
Power Output (continuous)	*10 W*
Output Impedance	*10 Ω*
Output Noise	*< 50 µV_{rms} (1 - 100Hz)*
Output Short Circuit Protection	*YES*
Steady State Power Consumption	*< 0.5 W*
Current Consumption (max.)	*500 mA*
-3 dB Bandwidth	
No Load (200 mV_{p-p} input)	*32 kHz*
No Load (10 V_{p-p} input)	*32 kHz*
1.0 µF load, current limited	*550 Hz*
Stability	*< 0.01% over 16 hours*
General	
AC Input Voltage	*100 - 240 VAC*
AC Input Frequency	*60/50 Hz*
AC Input Power (max.)	*30 W*
Analog Input	*BNC*
High Voltage Output	*BNC*
Operating Temperature	*5°C to 40°C*
Dimensions	*12" × 8.375" × 3.5" (305 × 213 × 89 mm)*

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP