

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*



marathon™ Special Products

Product Data Sheet

140X404

Replace "x" with 2,or 3 for number of poles

Power Terminal Block

310 Amps 600 Volts AC/DC

Wire Range

- Line: (1) 350kcmil - #6 AWG
- Load: (6) #4 - #14 AWG

Electrical Ratings

- 310 Amps
- 600V per UL 1059 & CSA 22.2 No.158, Class B & C requirements
- Short circuit current ratings (SCCR): See SCCR section below for specifications.
- CU7AL - 75°C connector terminal rating with copper or aluminum wire
- Factory & Field Wiring


Agency Compliance

- UR - UL Recognized Terminal Block, Evaluated to UL 1059, File No.XCFR2.E62806
- CSA - certifed to C22.2 No. 158, File No. LR19766 (wire classes B & C only)
- CE compliant to IEC 60947-7-1


Material Information

- Insulator base:
  - Phenolic
  - Flammability rating of insulator base UL94V0
  - Insulator base temperature rating: -40°C to 150°C (UL RTI)
- Connector: aluminum, tin plated
- Line terminal screws: aluminum, tin plated
- Load terminal screws: steel, nickel plated
- Connector mounting screws: steel, zinc plated
- RoHS compliant

Termination Specifications

Line Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) [1]
	350 - 300 kcmil	13.6 N·m (275 lbf·in)	1	B, C
	250 - 2	13.6 N·m (275 lbf·in)	1	B, C, G, H, I (DLO)
	4 - 6	13.6 N·m (275 lbf·in)	1	B, C

- Aluminum wire range: #350kcmil - #6 AWG
- Wire strip length: line & load side tap - 1 1/16 in. (27mm)
- Terminal screw drive: 5/16 in. (8mm) hex

Load Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) [1]
	4 AWG	4 N·m (35 lbf·in)	1	B, C
	6 - 8	4 N·m (35 lbf·in)	1	B, C, G, H, I (DLO)
	10	4 N·m (35 lbf·in)	1 - 2	B, C, I (DLO)
	12 - 14	4 N·m (35 lbf·in)	1 - 2	I (DLO)
			1 - 4	B, C

- Aluminum wire range: #4 - #14
- Wire strip length:
  - top row: 9/16 in. (14mm)
  - bottom row: 1.0 in. (25mm)
- Terminal screw drive: slotted

[1] For information on copper stranded wire classes please reference:
http://www.marathonsp.com/CatalogPDFs/Flexible-Stranded-Wire.pdf

Short Circuit Current Ratings (SCCR)

- The suitable conductor ranges are limited to the table values only for achieving the SCCR in excess of the default rating of 10,000A.
- Other conductor combinations within the "Terminal Specifications" noted are suitable for achieving a SCCR of 10,000A (the default rating of terminal blocks).
- Enclosure size – investigated with a minimum 16x12x6 enclosure. Use in smaller enclosures is subject to end use evaluation.

SCCR With Fuses

Wire Type	Suitable Conductors		Max Overcurrent Protection **Fuse** Required Amp Rating / Class						SCCR RMS Sym. Amps 600V. Max
	Line	Load	J	T	RK1	RK5	G	CC	
B, C	350 - 3/0	4 - 8	400	400	400	200	60	30	100,000
B, C	350 - 6	4 - 10	250	250	200	100	60	30	100,000
G, H, I	250 - 6	6 - 10	150	150	100	30	60	30	100,000
(*)	350 - 6	4 - 14	None						10,000

* Any wire class evaluated (see terminal specification section)

Installation & Accessories


- Mounting (Panel):
  - For use with 1/4 fastener.
  - Torque mounting fastener to 30-40 lbf·in (3.4 - 4.5 N·m).

- Covers:
  - Flat covers available upon request
  - Catalog Number: CH140x (replace "x" with number of poles)
  - Covers are clear polycarbonate
  - Accessory covers are not intended to provide insulation for electrical spacings.

- Marker Strip: white vinyl strip with mounting screws available.

- Printing options available, consult customer service for specifications.

Drawing


4.13
[104.8]
.95
[24.1]
1.00
[25.4]
3.38
[85.7]
3.52
[89.3]
5.38
[136.5]
4.63
[117.5]
4.77
[121]
2.06
[52.3]
2.90
[73.7]
(2)SLOTS
.27 X .38 [6.7 X 9.5]
(4)SLOTS
.22 X .38 [5.5 X 9.5]

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP